



**Selected by Professionals**

# Stealth

## WELDING MACHINES PRODUCT INFORMATION



Input Voltage



Generator Friendly

**9024H**

### DIGI-ARC 205 DV CEL

Cellulosic Model – 110V/230V

#### PRODUCT SUMMARY

An all-round dual voltage MMA stick welder capable of running E6010 and E7018 up to 4mm on 110V. Great duty cycle, an OCV of DC74V and hot start on MMA. The ability to scratch start Tig and an easy read digital display.

Supplied with a carry case



Supplied with **EARTH RETURN LEAD** and **ELECTRODE LEAD**

#### OPTIONAL EXTRAS

**9807** Scratch Start Tig Package

#### SPECIFICATIONS

	110V	230V
Minimum fuse rating (A)		24
I1 max (A)		45.5
Generator friendly		+ / - 10%
Input power voltage (V)	110	230
Rated input power capacity (KVA)	3.8	6.6
Input voltage frequency (Hz)		50/60 Hz
Output current rate (A)	10-120	10-200
Duty cycle (A) (40°C 10 min)	95 @ 100%	155 @ 100%
	120 @ 60%	200 @ 60%
Protection class		Ip21S
Diameter of rod (mm)	1.6-2.5	1.6-5.0
Overall dimensions (mm)	380 x 160 x 250	
Weight (kg)	7.5	
Accessories included	3m earth clamp and cable, 3m electrode holder and cable	

Try our Vac-pac E6010 Super Optimal rods.



5.0kg	Diameter	Length
<b>7405</b>	2.5mm	350mm
<b>7406</b>	3.2mm	350mm
<b>7407</b>	4.0mm	350mm

SCAN HERE FOR SWP WEBSITE



Perfect for the Stealth 9024H.

Tel: **01420 588180** | Email: [sales@swp.uk.net](mailto:sales@swp.uk.net) | [www.specialisedwelding.co.uk](http://www.specialisedwelding.co.uk)

