




Selected by Professionals

Stealth PLASMA CUTTING PRODUCT INFORMATION



9030H DIGI-CUT 42 PFC

Multi Voltage – 110V/230V

PRODUCT SUMMARY

The Stealth Digi-Cut 42PFC is a great dual voltage plasma cutter capable of cutting up to 15mm. Ideal for low carbon steels, stainless and aluminium. Features a built in air regulator and has Power Factor Correction to save on energy costs. Supplied with a carry case



SPECIFICATIONS

	110V	230V
Input power voltage (V)	110±10%	230±10%
Frequency (Hz)	50/60	
Effective input current (A)	20.4	16
Maximum (KVA)	3.8	5.2
Current adjustment range (A)	20-30	20-40
Maximum no-load voltage (V)	320	
Duty cycle (A) (40°C 10 min)	35% @ 30 60% @ 22 100% @ 20	50% @ 40 60% @ 36 100% @ 30
Severance cut for carbon steel (mm)	≤20	≤25
Production cut for carbon steel (mm)	≤10	≤15
stainless steel (mm)	≤10	≤15
aluminium (mm)	≤8	≤12
copper (mm)	≤6	≤10
Air operating pressure (psi)	50-90 (3.5-6 bar)	
Air operating flow (l/min)	160 (5.65 cfm)	
Protection class	Ip23	
Insulation class	H	
Cooling	Air	
Overall dimensions (mm)	480 x 148 x 292	
Weight (kg)	8	
Accessories included	3m earth return lead, 3m gas hose	



PC7100H
Plasma torch included



Recommended Compressor at 100% Duty Cycle:
BA3/200BS1 or **BA3/200BS3** (not included)
See Catalogue Air Equipment

SCAN HERE FOR SWP WEBSITE

