

Steyith WELDING MACHINES PRODUCT INFORMATION



Ste>lth

(() 10

9395H DIGI-MIG 300E

PRODUCT SUMMARY

This machine is a programmable syn standard Mig MMA >5mm electrode with a large LCD display. It offers a four rolls wire feed for 15kg spool, 2T-4T trigger action and pre and post gas flow.

FEATURES

Synergic programmes

Input power voltage (V)	3 x 400	
Supply current max. (A)	16	
Rated power (kVA)	11.1	
Fuse, slow (A)	T 16	
No load voltage (V)	65	
Welding current range (A)	30~300	
Duty cycle (A)	40% @ 300	
	60% @ 250	
	100% @ 200	
Wire speed (m/min)	0.6 – 22	
Welding wire diameter (mm)	0.8 - 1.2	
Efficiency (%)	87	
Power factor	0.95	
Insulation class	Н	
Protection class	IP21	
Cooling	Air	
Overall dimensions (mm)	795 x 540 x 700	
Weight (kg)	31.0	
Accessories included	Eco 36-3 torch, 3m Argon hose, 3m earth lead	

Supplied with **2068 ARGON/CO2 PRESSURE REGULATOR** Single Stage 2g – Argon/ CO₂ Regulator – 30 lpm



SCAN HERE FOR

AR WA

EALTH

Tel: 01420 588180 | Email: sales@swp.uk.net | www.specialisedwelding.co.uk 🛛 🛐

in O