



TECHNICAL DATA

Premium Grade Compressor Oils

The SWP range of compressor oils are blended using high vi premium grade base oils and selected additives to provide long-term protection and reliability for your compressor. The new generation formula using compressor specific chemistry enables the range to be used in all types of compressor.

Features

- Recommended for single and multi stage compressors
- Suitable for continuous use at temperatures of up to 220°C
- Low evaporative loss ensures less oil thickening
- Excellent demulsibility
- High resistance to oxidation and deposit formation
- Superb load carrying and anti-wear characteristics

Compressor type	Product
Screw	AC 2032
Vane	AC 2046
Piston	AC 2068
Reciprocating	AC 2100
Hydrovane	AC 2150

The above must only be used as a guide – always consult the manufacturers handbook.

The AC 2000 range meets or exceeds the following specifications:

DIN 51 506 VDL	SPERRY VICKERS I-286-S
DIN 51 524 PART 2	CINNATI MILACRON P-68, P-69, P-70
AFNOR NF E 48-603 (HM)	

Typical Physical Characteristics

	AC2032	AC2046	AC2068	AC2100	AC2150
ISO VG	32	46	68	100	150
Density at 15°C	0.868	0.871	0.879	0.882	0.882
Viscosity at 40°C	32.0	46.1	68.4	100.1	150.3
Viscosity at 100°C	5.4	7.0	9.1	11.6	15.5
Viscosity index	108	108	107	105	105
Appearance	amber	amber	amber	amber	red
Product Code	11030	11040	11050	11060	11070

Specialised Welding Products Ltd

Unit 1 Farringdon Industrial Centre, Farringdon Nr Alton, Hants GU34 3DD
Tel: +44 (0)1420 588180 Fax: +44 (0)1420 588184
Email: sales@swp.uk.net www.specialisedwelding.co.uk