



Part No. **ZYFUTBL-HD-1x25**

Description:

New Fire Working temperature 1100 °C, high silica cloth products soft, heat insulation, can satisfy the requirement of high temperature resistant

Application:

Can do welding blanket; Can be coated silica gel, vermiculite, aluminum foil, ground protection, fire protection products

特性 Characteristic	单位 Unit	数据 Data				测试标准 Method		
织纹 Weave		8HS SATIN 缎纹						
用纱 Yarn	tex	经纱	WARP	纬纱	WEFT			
		EC9 136 1x2		EC9 136 1x2				
重量 Weight	g/m ²	600				ASTM-D3776-2009		
厚度 Thickness	mm	0.7				ASTM-D1777-1996		
密度 Thread Count	per cm	经纱	WARP	18	纬纱	WEFT	13	ASTM-D3775-2008
涂层类型 Coating		2% PU						
涂层重量 Coating Weight	g/m ²	/				ASTM-D3776-2009		
产品总重 Total Weight	g/m ²	600				ASTM-D3776-2009		
产品总厚 Total Thickness	mm	0.7				ASTM-D1777-1996		
抗张强度 Tensile Strength	N/2.5cm	经纱	WARP	2500	纬纱	WEFT	1500	ASTM-D5034-2001
耐温度 Service Temperature	°C	1100						
获得认证 Certification		欧洲 BSEN 476 PART 7						
		欧盟 CE						
		美国 FM 4950						
		IMO A 653						

标准幅宽 Width	m	0.914/1.15
标准卷长 Length	m	45.7
备注 Remarks		