



Part No. **ZYFUTBL-LD-1X25**

**Description:**

New Fire High temperature resistant fiber cloth soft, flame retardant, high temperature resistant, 100% do not contain asbestos composition, with low bulk density, insulation, antioxidant and other properties

**Application:**

Can make the aluminum foil, neoprene, acrylic, dyeing, PU coating; Welding blanket; The silicone flexible removable inner insulation component

特性 Characteristic	单位 Unit	数据 Data	测试标准 Method
织纹 Weave		平纹 PLAIN	
用纱 Yarn	tex	经纱 WARP 纬纱 WEFT	
		ET9 430 Tex ET9 430 Tex	
重量 Weight	g/m <sup>2</sup>	580	ASTM-D3776-2009
厚度 Thickness	mm	0.75	ASTM-D1777-1996
密度 Theread Count	per cm	经纱 WARP 8 纬纱 WEF 5.7	ASTM-D3775-2008
涂层类型 Coating		Heat Treatment	
涂层重量 Coating Weight	g/m <sup>2</sup>	/	ASTM-D3776-2009
产品总重 Total Weight	g/m <sup>2</sup>	/	ASTM-D3776-2009
产品总厚 Total Thickness	mm	/	ASTM-D1777-1996
抗张强度 Tensile Strength	N/2.5cm	经纱 WARP 1200 纬纱 WEF 800	ASTM-D5034-2001
耐温度 Service Temperat	°C	550°C	
获得认证 Certification		欧洲 BSEN 476 PART 7	
		欧盟 CE	
		美国 FM4950	
		GB 8624-2012 《建筑材料及制品燃烧性能分级》 A (A1) 级	

标准幅宽 Width	m	1.02/1.51/1.83
标准卷长 Length	m	45.7/50