



Part No. **ZYFUTBL-MD-1X25**

Description:

New Fire Vermiculate Coated Fiberglass Cloth, fire resistance, 100% asbestos-free, anti-allergy,

Application:

Welding Blanket

特性 Characteristic	单位	数据 Data					测试标准 Method
织纹 Weave		平纹 PLAIN					
用纱 Yarn	tex	经纱		WARP	纬纱		WEFT
		ET9 860 Tex			ET9 860 Tex		
重量 Weight	g/m ²	815					ASTM-D3776-2009
厚度 Thickness	mm	1					ASTM-D1777-1996
密度 Thread Count	per cm	经纱	WARP	6	纬纱	WEFT	3.4
涂层类型 Coating		Black Vermiculate Coated					
涂层重量 Coating Weight	g/m ²	30					ASTM-D3776-2009
产品总重 Total Weight	g/m ²	845					ASTM-D3776-2009
产品总厚 Total Thickness	mm	1.06					ASTM-D1777-1996
抗张强度 Tensile Strength	N/2.5cm	经纱	WARP	1650	纬纱	WEFT	1100
耐温度 Service Temperature	°C	1000					
获得认证 Certification		欧洲 BSEN 476 PART 7					
		美国 FM 4950					
		欧盟 CE					

Width	m	1.02/1.51/1.83
Length	m	50
Remarks	All the data - 2% ~ + 5%	