




## **Features**

- Authentic masonry style without the costs of a site-built masonry fireplace
- 36", 42" and 50" viewing areas
- Variable flame control up to 65,000 BTUs
- High-efficiency, AFUE-rated performance
- IntelliFire® touchscreen remote comes standard; add the IntelliFire app or wireless wall switch for the solution that fits your life
- Choose from standard traditional or herringbone interior panels, or optional fade-resistant reflective black glass interior panels (36" and 42" only)
- Finish it your way with a choice of decorative firescreen fronts with fine mesh for a clear view of the fire
- Heater listed to ANSI Z21.88 standards

# **Options**

## **Fronts and Doors**









Black



New Bronze





Firescreen Arch



Herringbone

Fade-resistant reflective black glass (36" and 42" only)

#### **Controls**

## IntelliFire App

All the features of a remote control with an app installed on your smart device. Monitor your fire from anywhere or even control it with the sound of your voice. IntelliFire is compatible with voice assistants Amazon Alexa and Google Assistant.




#### **Touchscreen Remote**

Features: on/off, flame height adjustment, fan speed, lights adjustment, thermostat mode, room temperature readout, child lock, timer mode, battery backup, cold climate mode, power vent, wall docking station (fan, lights and power vent are dependent on your fireplace).

## Wireless Wall Switch

Features: on/off, battery strength indicator, cold climate mode










## **Technical Specifications**

MODEL	FRONT WIDTH (A)	BACK WIDTH (H)	HEIGHT (E)	DEPTH	GLASS SIZE
HEIR36	61" (1549mm)	59-1/4" (1505mm)	57-5/8" (1464mm)	24" (610mm)	36" x 31" (914 x 787mm)
HEIR42	67" (1702mm)	65-5/16" (1659mm)	62-5/8" (1591mm)	24" (610mm)	42" x 36" (1067 x 914mm)
HEIR50	75" (1905mm)	73-5/16" (1862mm)	66-5/8" (1692mm)	24" (610mm)	50" x 40" (1270 x 1016mm)










**Top View** 

\*Front dimensions include non-combustible material which overlaps framing

	MODEL	Α	В	С	D	Е	F	G	Н	1	J
	HEIR36	61" (1549mm)	35-7/8" (911mm)	39-7/8" (1013mm)	31-1/16" (789mm)	57-5/8" (1464mm)	54-15/16" (1395mm)	41-3/8" (1042mm)	59-1/4" (1505mm)	16" (406mm)	29-5/8" (752mm)
ĺ	HEIR42	67" (1702mm)	41-7/8" (1064mm)	45-7/8" (1165mm)	36-1/16" (916mm)	62-5/8" (1591mm)	59-15/16" (1522mm)	46-3/8" (1178mm)	65-5/16" (1659mm)	16" (406mm)	32-11/16" (830mm)
[	HEIR50	75" (1905mm)	49-7/8" (1267mm)	53-7/8" (1368mm)	40-1/16" (1018mm)	66-5/8" (1692mm)	63-15/16" (1624mm)	50-3/8" (1280mm)	73-5/16" (1862mm)	16" (406mm)	36-11/16" (932mm)


## **Clearances**

Α	В	С
74-1/4"	59-1/2"	105"
(1886mm)	(1511mm)	(2667mm)
78-9/16"	65-9/16"	111-1/16"
(1995mm)	(1665mm)	(2821)
84-1/4"	73-9/16"	119-1/8"
(2140mm)	(1868mm)	(3026mm)
D	Ε	F
26-1/2"	23-1/2"	29-3/4"
(673mm)	(597mm)	(756mm)
28-5/8"	23-1/2"	32-13/16"
(727mm)	(597mm)	(33mm)
31-1/2"	23-1/2"	36-13/16"
(800mm)	(597mm)	(935mm)
	74-1/4" (1886mm) 78-9/16" (1995mm) 84-1/4" (2140mm) <b>D</b> 26-1/2" (673mm) 28-5/8" (727mm) 31-1/2"	74-1/4" (1886mm) (1511mm) 78-9/16" (55-9/16" (1995mm) (1665mm) 84-1/4" (73-9/16" (1868mm)  D



## Framing

MODEL	A ROUGH OPENING (VENT PIPE)	B ROUGH OPENING (HEIGHT)	C ROUGH OPENING (DEPTH)	D ROUGH OPENING (WIDTH)	E CLEARANCE TO CEILING
HEIR36	10"	56"	24"	59-1/2"	52"
HEINOU	(254mm)	(1422mm)	(610mm)	(1511mm)	(1321mm)
HEIR42	10"	61"	24"	65-9/16"	52"
HEIN42	(254mm)	(1549mm)	(610mm)	(1665mm)	(1321mm)
HEIR50	10"	65"	24"	73-9/16"	52"
HEINOU	(254mm)	(1651mm)	(610mm)	(1868mm)	(1321mm)
MODEL	F COMBUSTIBLE TO FLOOR	G COMBUSTIBLE FLOORING	H BEHIND APPLIANCE	 SIDES OF APPLIANCE	J FRONT OF APPLIANCE
HEIR36	0"	See Install	1"	1"	36"
HEIROD	(0mm)	Manual	(25mm)	(25mm)	(914mm)
HEIR42	0"	See Install	1"	1"	36"
HEIN42	(0mm)	Manual	(25mm)	(25mm)	(914mm)
HEIR50	0"	See Install	1"	1"	36"
HEIROU	(0mm)	Manual	(25mm)	(25mm)	(914mm)



## **Technologies**

## Intellifire Touch® Ignition System

IntelliFire Touch is our most advanced intermittent-pilot ignition (IPI) system, making operating your appliance simple, smart and safe. Select from the IntelliFire app, touchscreen remote or wireless wall switch for the solution that fits your life.

## **Direct Vent Technology**

Direct vent technology removes 100% of combustion exhaust and fumes from your home. These sealed fireplaces provide optimal heat, conserve energy and ensure clean, safe indoor air quality.

# EnerGuide (CSA P.4.1-15) Ratings

Used in Canada and some U.S. states to measure annual fireplace efficiency.

RATING	HEIR36T/H	HEIR42T/H	HEIR50T/H
EnerGuide (CSA P.4.1-15)	59.6%	67.0%	67.5%

# Exceptional Value + Dependability

Why do contractors, architects and homebuyers trust Heatilator? Because we mix value with dependability. Established in 1927, Heatilator has built a long standing reputation for providing quality, dependable hearth products at unbeatable values. Today, Heatilator remains the most preferred, recommended and installed fireplace brand among building professionals.

### **Available from**



800-927-6841 | heatilator.com

facebook.com/Heatilator

twitter.com/Heatilator

youtube.com/HeatilatorFireplaces

HTL-1081U-0522

**Limited Lifetime Warranty**<sup>1</sup> The strongest in the industry, Heatilator provides a limited lifetime warranty on gas-burning products of the most important aspects: firebox and heat exchanger.

1 For full warranty details go to heatilator.com

Amazon.com. Inc. or its affiliates.

The information provided in this literature is for planning purposes only and subject to change. Please consult the installation manual for actual installation. Actual product appearance may differ from product images.

Fireplace glass and other surfaces get extremely HOT and can cause severe burns if touched. Keep a safe distance away. To learn more visit www.heatilator.com/fireplacesafety Google, YouTube and Google Home are trademarks of Google LLC. Amazon, Alexa, and all related logos are trademarks of



