

1 L Make-up Solution

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 - Product identifier

Trade name/designation 1 L Make-up Solution

Chemical name

Product-type Mixture Product code TH-Type B

UFI: 9R66-P0GS-4008-6E8S

1.2 - Relevant identified uses of the substance or mixture and uses advised against

1.3 - Details of the supplier of the safety data sheet

Southern Technology Ltd 2A Birmingham Drive, Middleton Christchurch 8024, New Zealand

Phone: 03 3899258 southerntech.co.nz

1.4 - Emergency telephone number

Emergency 111, New Zealand Poisons Centre 0800 764 766

SECTION 2: Hazards identification

2.1 - Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids, Category 2
Acute Tox. 4 Oral	Acute toxicity (oral), Category 4
Acute Tox. 4 Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4 Inhalation	Acute toxicity (inhal.), Category 4
Eye Irrit. 2	Eye irritation - Category 2
STOT SE 1	Specific target organ toxicity — single exposure, Category 1

2.2 - Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains: butanone, ethyl methyl ketone (CAS No.: 78-93-3) | methanol (CAS No.: 67-56-1)

Signal word Danger

Hazard pictograms







Hazard statements

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H312	Harmful in contact with skin
H319	Causes serious eye irritation

17/08/2023 - Anglais 1/12

LogicSDS



1 L Make-up Solution

H332	Harmful if inhaled
H370	Causes damage to organs

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust, fume, gas, mist, vapours, spray.
P280	Wear protective gloves, protective clothing, eye protection, face protection.
EUH-phrases	
EUH066	Repeated exposure may cause skin dryness or cracking

2.3 - Other hazards

SECTION 3: Composition / information on ingredients

3.1 - Substances

Not applicable

3.2 - Mixtures

Chemical name	No	%	Class(es)	Specific concentration limit
butanone, ethyl methyl ketone	CAS No. : 78-93-3 Index No. : 606-002-00-3 EC No. : 201-159-0 REACH No. : 01-2119457290-43-XXXX	80 - 90	Eye Irrit. 2 - H319 Flam. Liq. 2 - H225 STOT SE 3 (H336) - H336	Not applicable
methanol	CAS No.: 67-56-1 Index No.: 603-001-00-X EC No.: 200-659-6 REACH No.: 01-2119433307-44	10 - 20	Acute Tox. 3 Dermal - H311 Acute Tox. 3 Inhalation - H331 Acute Tox. 3 Oral - H301 Flam. Liq. 2 - H225 STOT SE 1 - H370	STOT SE 1 - H370 : 10<=%<=100 STOT SE 2 - H371 : 3<=%<10

SECTION 4: First aid measures

4.1 - Description of first aid measures

Following inhalation	Provide fresh air.Get medical advice/attention.Remove victim out of the danger area.
Following skin contact	 Irritating to skin. Remove contaminated, saturated clothing immediately. Medical examination necessary even merely on suspicion of intoxication.
After eye contact	 Irritating to eyes. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
After ingestion	- Get medical advice/attention.



1 L Make-up Solution

	person with cramps.
4.2 - Most important symptoms and effects, t	ooth acute and delayed
Symptoms and effects - Following inhalation	- Irritating to respiratory system.
Symptoms and effects - Following skin contact	Causes skin irritation.Repeated exposure may cause skin dryness or cracking.

<u>Symptoms and effects - After eye contact</u> - Irritating to eyes.

- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Nover give anything by mouth to an unconscious person of

<u>Symptoms and effects - After ingestion</u> - The following symptoms may occur: Vomiting

- Nausea

- 4.3 Indication of any immediate medical attention and special treatment needed
- Treat symptomatically.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1 - Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO2)Dry extinguishing powderWater mist
Unsuitable extinguishing media	- High power water jet

5.2 - Special hazards arising from the substance or mixture

Special hazards arising from the substance or mixture	 Use water spray jet to minimise or disperse vapours. Use water spray jet to protect personnel and to cool endangered containers.
Hazardous decomposition products	- Carbon dioxide (CO2) - Carbon monoxide

5.3 - Advice for firefighters

- Wear a self-contained breathing apparatus and chemical protective clothing.
- flammable liquids

SECTION 6: Accidental release measures

6.1 - Personal precautions, protective equipment and emergency procedures

	• • •
For non-emergency personnel	- Use personal protection equipment.
	- Provide adequate ventilation.
	- Evacuate area.
	 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
For emergency responders	 No information available.



1 L Make-up Solution

6.2 - Environmental precautions

- Do not allow to enter into surface water or drains.
- Absorb spillage to prevent material damage.

6.3 - Methods and material for containment and cleaning up

Methods and material for containment special attention.
 Collect in closed and suitable containers for disposal.
 Collect spillage.
 Methods and material for cleaning up
 Wash with plenty of water.
 No information available.

6.4 - Reference to other sections

- Disposal: see section 13
- SECTION 6: Accidental release measures

SECTION 7: Handling and storage

7.1 - Precautions for safe handling

Recommendation	 Avoid: Eye contact Avoid: Skin contact Provide adequate ventilation. Emergency shower installed Provide eye shower and label its location conspicuously
Advices on general occupational hygiene	When using do not eat, drink, smoke, sniff.Wash contaminated clothing prior to re-use.Wash hands before breaks and after work.

7.2 - Conditions for safe storage, including any incompatibilities

- Keep container tightly closed in a cool, well-ventilated place.

7.3 - Specific end use(s)

- Keep away from sources of ignition. No smoking.
- Handle and open container with care.

SECTION 8: Exposure controls/personal protection

8.1 - Control parameters

methanol (67-56-1)	
VME ppm (FR)	200 ppm
VME mg/m3 (FR)	260 mg/m3

8.2 - Exposure controls

Appropriate engineering controls	 No information available. 	



1 L Make-up Solution

Individual protection measures, such as personal protective equipment

- Suitable eye protection: Eye glasses with side protection

- Protective gloves

- Suitable protective clothing: lab coat



SECTION 9: Physical and chemical properties

9.1 - Information on basic physical and chemical properties

Physical state	Liquid	Appearance	Liquid		
Colour	clear	Odour	Solvant		
Odour threshold		No data available			
pH					
Melting point		78 °C < V < 80 °C			
Freezing point		No data available			
Boiling point		80 °C			
Flash point		-4,5 °C	-4,5 °C		
Evaporation rate		No data available			
flammability		No data available			
Lower explosion limit		1,8 % Vol.			
Upper explosion limit		11,5 % Vol.			
Vapour pressure		10500 Pa			
Vapour density		No data available			
Relative density		0,81			
Density		No data available			
Solubility (Water)		No data available			
Solubility (Ethanol)		No data available			
Solubility (Acetone)		No data available			
Solubility (Organic solvents)		No data available			
Log KOC		No data available			
Auto-ignition temperature		505 °C			
Decomposition temperature		No data available			
Kinematic viscosity		No data available			
Dynamic viscosity		No data available			
Particle characteristics					
Particle size		No data available			
Dustiness		No data available			
Specific surface area		No data available			



1 L Make-up Solution

Shape	No data available
9.2 - Other information	
VOC content	No data available
Minimum ignition energy	No data available
Conductivity	No data available
VOC Composite Partial Pressure (Calculated @ 20oC/68oF)	No data available
C.A.R.B. V.O.C.	No data available
% Photo Chemically Reactive	No data available

SECTION 10: Stability and reactivity

10.1 - Reactivity

- This material is considered to be non-reactive under normal use conditions.

10.2 - Chemical stability

- The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 - Possibility of hazardous reactions

- No hazardous reaction when handled and stored according to provisions.

10.4 - Conditions to avoid

- In case of warming: Ignition hazard

10.5 - Incompatible materials

- No information available.

10.6 - Hazardous decomposition products

- No information available.

SECTION 11: Toxicological information

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	- Acute toxicity (dermal), Category 4 - Harmful in contact with skin
	 Acute toxicity (inhal.), Category 4 - Harmful if inhaled
	- Acute toxicity (oral), Category 4 - Harmful if swallowed

Toxicity: Mixture

LD50 oral (rat)	2737 mg/kg
LD50 dermal (rat)	No data available
LD50 dermal (rabbit)	6480 mg/kg
LC50 inhalation (rat)	No data available
LC50 inhalation dusts and mists (rat)	No data available
LC50 inhalation vapours (rat)	No data available

- Based on available data, the classification criteria are not met.

Toxicity: Substances



1 L Make-up Solution

	butanone, ethyl methyl ketone (78	-93-3)	
	LD50 oral (rat)		2193 mg/kg
	LD50 dermal (rabbit)		5000 mg/kg
Skin corrosion/irritation	- Not classified		
Serious eye damage/eye irritation	- Eye irritation - Category 2 - Causes serious eye irritation		
	- Irritating to eyes.		
Respiratory or skin sensitisation	- Not classified		
Germ cell mutagenicity	- Not classified		
Carcinogenicity	- Not classified		
Reproductive toxicity	- Not classified		
STOT-single exposure	 Specific target organ toxicity — s to organs 	single exposure,	Category 1 - Causes damage
STOT-repeated exposure	- Not classified		
Aspiration hazard	- Not classified		
11.0 Information on other	r bowardo		

11.2 - Information on other hazards

SECTION 12: Ecological information

12.1 - Toxicity

Toxicity: Mixture

EC50 48 hr crustacea	5600 mg/l
LC50 96 hr fish	No data available
ErC50 algae	No data available
ErC50 other aquatic plants	No data available
NOEC chronic fish	No data available
NOEC chronic crustacea	No data available
NOEC chronic algae	No data available
NOEC chronic other aquatic plants	No data available

⁻ The substance/mixture does not fullfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

12.2 - Persistence and degradability

Biochemical oxygen demand (BOD)	No data available
Chemical oxygen demand (COD)	No data available
% of biodegradation in 28 days	No data available

- No information available.

12.3 - Bioaccumulative potential

Bioconcentration factor (BCF)	No data available
Log KOC	No data available



1 L Make-up Solution

- No indication of bioaccumulation potential.
- 12.4 Mobility in soil
- No information available.
- 12.5 Results of PBT and vPvB assessment
- 12.6 Endocrine disrupting properties
- 12.7 Other adverse effects
- No information available.

SECTION 13: Disposal considerations

13.1 - Waste treatment methods

Waste treatment methods - Dispose of waste according to applicable legislation.

Sewage disposal - No information available.

Special precautions for waste treatment - No information available.

Community or national or regional provisions - No information available.

SECTION 14: Transport information

14.1 - UN number or ID number

 UN number (ADR)
 : UN1210

 UN number (RID)
 : UN1210

 UN number (ADN)
 : UN1210

 UN number (IMDG)
 : UN1210

 UN number (IATA)
 : UN1210

14.2 - UN proper shipping name



1 L Make-up Solution

UN proper shipping name

(ADR)

PRINTING INK. flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

pressure

at 50 °C not more than

110 kPa) 640D

UN proper shipping name

(RID)

PRINTING INK, flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

pressure

at 50 °C not more than

110 kPa) 640D

UN proper shipping name

(ADN)

PRINTING INK, flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

at 50 °C not more than

110 kPa) 640D

UN proper shipping name

(IMDG)

PRINTING INK. flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

pressure

at 50 °C not more than

110 kPa) 640D

UN proper shipping name

(IATA)

PRINTING INK, flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

pressure

at 50 °C not more than

110 kPa) 640D

14.3 - Transport hazard class(es)

ADR Transport hazard

class(es)

3

ADR Classification code:

Pictograms

F1

3

3

Transport hazard class(es)

(RID)

Pictograms

Transport hazard class(es)

(ADN)

Pictograms

Transport hazard class(es)

(IMDG)

3



1 L Make-up Solution

Pictograms

Transport hazard class(es) 3

(IATA)

Pictograms



14.4 - Packing group

Packing group Ш Ш Packing group (RID) Ш Packing group (ADN) Packing group (IMDG) Ш Packing group (IATA) Ш

14.5 - Environmental hazards

Environmental hazards No Marine pollutant No

14.6 - Special precautions for user

ADR

ADR Classification code: F1 ADR Special provisions 163+ 640D+367

ADR Limited quantity (LQ) 5 L ADR Excepted quantities E2

ADR Packing instructions P001 IBC02 R001

ADR Special packing provisions PP1 **MP19** ADR Mixed packing provisions Instructions for portable tanks and bulk containers T4 TP1 TP8 Special provisions for portable tanks and bulk containers ADR tank code **LGBF**

ADR tanks special provisions

Vehicle for tank carriage FL ADR Transport category 2 ADR Tunnel restriction code D/E

ADR Special provisions loading, unloading and handling

Special provisions - Packages

Special provisions - Bulk

Special provisions - Operation S2, S20 33

ADR Hazard identification number (Kemler No.)



1 L Make-up Solution

RIDSpecial provisions:Limited quantity (LQ):

Excepted quantities :

ADN

Special provisions :

Limited quantity (LQ) :

Excepted quantities :

IMDG

Special provisions

 Limited quantity (LQ)
 :
 5

 Excepted quantities
 :
 E2

 Packing instructions
 :
 P001

Special packing provisions

IBC instruction(s)

IBC provisions : Instructions for portable tanks and bulk containers :

instructions for portable tarks and bulk containers

Special provisions for portable tanks and bulk containers
EmS codes

Stowage and handling :

Segregation :

Properties and observations :

IATA

PCA - Excepted quantitiesE2PCA - Limited Quantity - Packing Instructions: Y341PCA - Limited Quantity - Maximum Net Quantity per Package: 1PCA - Packing Instructions: 353PCA - Maximum Net Quantity per Package: 5CAO - Packing Instructions: 364CAO - Maximum Net Quantity per Package: 60

Special Provisions

ERG Code :

14.7 - Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 - Safety, health and environmental regulations/legislation specific for the substance or mixture

Substances REACH None

candidates

Substances Annex XIV None

Substances Annex XVII methanol (Index No.: 603-001-00-X - EC No.: 200-659-6 - CAS No.: 67-56-1)

VOC content No data available

15.2 - Chemical Safety Assessment



1 L Make-up Solution

 $\frac{\mbox{Chemical safety assessment carried}}{\mbox{out for the product}} \ \ \mbox{- No information available}.$

SECTION 16: Other information

SDS versions

Version	Issue date	Author	Description of the amendments
2,1	17/08/2023		
1	26/01/2018		

Texts of the regulatory sentences

A . T .	
Acute Tox. 3 Dermal	Acute toxicity (dermal) - Category 3
Acute Tox. 3 Inhalation	Acute toxicity (inhalative) - Category 3
Acute Tox. 3 Oral	Acute toxicity (oral) - Category 3
Acute Tox. 4 Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4 Inhalation	Acute toxicity (inhal.), Category 4
Acute Tox. 4 Oral	Acute toxicity (oral), Category 4
Eye Irrit. 2	Eye irritation - Category 2
Eye Irrit. 2A	Eye irritation - Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 3 (H336)	STOT-single exposure - Category 3 (H336)

*** *** ***