

1 L Make-up Solution

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 - Product identifier

Trade name/designation 1 L Make-up Solution

Chemical name

Product-type Mixture
Product code TH18

UFI: K766-N0CD-9009-7CSD

1.2 - Relevant identified uses of the substance or mixture and uses advised against

1.3 - Details of the supplier of the safety data sheet

Southern Technology Ltd 2A Birmingham Drive, Middleton Christchurch 8024, New Zealand

Phone: 03 3899258 southerntech.co.nz

1.4 - Emergency telephone number

Emergency 111, New Zealand Poisons Centre 0800 764 766

SECTION 2: Hazards identification

2.1 - Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids, Category 2
Eye Irrit. 2	Eye irritation - Category 2
STOT SE 3 (H336)	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

2.2 - Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains: butanone, ethyl methyl ketone (CAS No.: 78-93-3)

Signal word : Danger

Hazard pictograms





Hazard statements

H225	Highly flammable liquid and vapour	
H319	Causes serious eye irritation	
H336	May cause drowsiness or dizziness	

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



1 L Make-up Solution

P240	Ground/bond container and receiving equipment.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust, fume, gas, mist, vapours, spray.
P280	Wear protective gloves, protective clothing, eye protection, face protection.
EUH-phrases	
EUH066	Repeated exposure may cause skin dryness or cracking

2.3 - Other hazards

SECTION 3: Composition / information on ingredients

3.1 - Substances

Not applicable

3.2 - Mixtures

Chemical name	No	%	Class(es)	Specific concentration limit
butanone, ethyl methyl ketone	CAS No. : 78-93-3 Index No. : 606-002-00-3 EC No. : 201-159-0 REACH No. : 01-2119457290-43-XXXX	90 - 100	Eye Irrit. 2 - H319 Flam. Liq. 2 - H225 STOT SE 3 (H336) - H336	Not applicable
acetone, propan-2-one, propanone	CAS No. : 67-64-1 Index No. : 606-001-00-8 EC No. : 200-662-2	5 - 15	Eye Irrit. 2 - H319 Flam. Liq. 2 - H225 STOT SE 3 (H336) - H336	Not applicable

SECTION 4: First aid measures

4.1 - Description of first aid measures

Following inhalation	Irritating to respiratory system.Provide fresh air.Get medical advice/attention.
Following skin contact	 When in doubt or if symptoms are observed, get medical advice. Irritating to skin. After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately.
After eye contact	 Irritating to eyes. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
After ingestion	Do NOT induce vomiting.VomitingNauseaGet medical advice/attention.

4.2 - Most important symptoms and effects, both acute and delayed

Symptoms and effects - Following inhalation - Irritating to respiratory system.

Symptoms and effects - Following skin contact - Causes skin irritation.



1 L Make-up Solution

	- Repeated exposure may cause skin dryness or cracking.
Symptoms and effects - After eye contact	 Irritating to eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Symptoms and effects - After ingestion	The following symptoms may occur: VomitingNausea

4.3 - Indication of any immediate medical attention and special treatment needed

- Treat symptomatically.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

51-	Extingu	ıishina	media

Suitable extinguishing media	Carbon dioxide (CO2)Dry extinguishing powder
Unsuitable extinguishing media	- High power water jet

5.2 - Special hazards arising from the substance or mixture

Special hazards arising from the substance or mixture	- Vapours are heavier than air.
	- Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.
Hazardous decomposition products	- Carbon dioxide (CO2) - Carbon monoxide

5.3 - Advice for firefighters

- Wear a self-contained breathing apparatus and chemical protective clothing.
- Move undamaged containers from immediate hazard area if it can be done safely.
- In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 - Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Use personal protection equipment.Provide adequate ventilation.Remove all sources of ignition.Evacuate area.
For emergency responders	- No information available.

6.2 - Environmental precautions

- Do not allow to enter into surface water or drains.
- Absorb spillage to prevent material damage.

6.3 - Methods and material for containment and cleaning up



1 L Make-up Solution

Methods and material for containment	Soak up inert absorbent and dispose as waste requiring special attention.Collect in closed and suitable containers for disposal.Collect spillage.
Methods and material for cleaning up	- Wash with plenty of water.
Inappropriate techniques	- No information available.
6.4 - Reference to other sections	

- Disposal: see section 13
- Personal protection equipment: see section 8
- SECTION 6: Accidental release measures

SECTION 7: Handling and storage

7.1 - Precautions for safe handling

Recommendation	 Avoid: Eye contact Avoid: Skin contact Provide adequate ventilation. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Keep away from sources of ignition No smoking.
Advices on general occupational hygiene	When using do not eat, drink, smoke, sniff.Wash contaminated clothing prior to re-use.Wash hands before breaks and after work.

7.2 - Conditions for safe storage, including any incompatibilities

- Keep container tightly closed in a cool, well-ventilated place.

7.3 - Specific end use(s)

- Keep away from sources of ignition. No smoking.
- Handle and open container with care.

SECTION 8: Exposure controls/personal protection

8.1 - Control parameters

8.2 - Exposure controls

Appropriate engineering controls - No information avai	Appropriate engineering controls	 No information available
--	----------------------------------	--

Individual protection measures, such as personal protective equipment

- Suitable eye protection: Eye glasses with side protection

- Protective gloves





1 L Make-up Solution

- Suitable protective clothing: lab coat



SECTION 9: Physical and chemical properties

9.1 - Information on basic physical and chemical properties

Physical state	Liquid	<u>Appearance</u>	Liquid		
Colour	transparent	<u>Odour</u>	characteristic		
Odour threshold		No data available	No data available		
рН		No data available			
Melting point		No data available	No data available		
Freezing point		No data available	No data available		
Boiling point		80 °C	80 °C		
Flash point		-9 °C			
Evaporation rate		No data available			
flammability		No data available			
Lower explosion limit		No data available	No data available		
Upper explosion limit		No data available	No data available		
Vapour pressure		10500 Pa	10500 Pa		
Vapour density		No data available	No data available		
Relative density		0,8	0,8		
Density		No data available			
Solubility (Water)		No data available	No data available		
Solubility (Ethanol)		No data available	No data available		
Solubility (Acetone)		No data available	No data available		
Solubility (Organic solvents)		No data available	No data available		
Log KOC		No data available	No data available		
Auto-ignition temperature		505 °C	505 °C		
Decomposition temperature		No data available	No data available		
Kinematic viscosity		No data available	No data available		
Dynamic viscosity		No data available	No data available		

Particle characteristics

Particle size	No data available
Dustiness	No data available
Specific surface area	No data available
Shape	No data available

9.2 - Other information

VOC content	No data available
Minimum ignition energy	No data available
Conductivity	No data available
VOC Composite Partial Pressure (Calculated @ 20oC/68oF)	No data available
C.A.R.B. V.O.C.	No data available



1 L Make-up Solution

% Photo Chemically Reactive

No data available

SECTION 10: Stability and reactivity

10.1 - Reactivity

- This material is considered to be non-reactive under normal use conditions.

10.2 - Chemical stability

- The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 - Possibility of hazardous reactions

- No hazardous reaction when handled and stored according to provisions.

10.4 - Conditions to avoid

- In case of warming: Ignition hazard

10.5 - Incompatible materials

- No information available.

10.6 - Hazardous decomposition products

- No information available.

SECTION 11: Toxicological information

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

- Not classified

Toxicity: Mixture

LD50 oral (rat)	2737 mg/kg
LD50 dermal (rat)	8200 mg/kg
LD50 dermal (rabbit)	6480 mg/kg
LC50 inhalation (rat)	11700 ppmV
LC50 inhalation dusts and mists (rat)	No data available
LC50 inhalation vapours (rat)	No data available

⁻ Based on available data, the classification criteria are not met.

Toxicity: Substances

irritation

	butanone, ethyl methyl ketone (78-93-3)	
	LD50 oral (rat)	2193 mg/kg
	LD50 dermal (rabbit) 5000 mg/kg	
acetone, propan-2-one, propanone (67-64-1)		7-64-1)
	LD50 oral (rat)	5800 mg/kg
	LC50 inhalation (rat)	50100 ppmV
Skin corrosion/irritation	- Not classified	
Serious eye damage/eye	- Eye irritation - Category 2 - Causes serious eye irritation	



1 L Make-up Solution

- Irritating to eyes. - Not classified Respiratory or skin sensitisation Germ cell mutagenicity Not classified Carcinogenicity Not classified Reproductive toxicity - Not classified STOT-single exposure - Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation - May cause drowsiness or dizziness STOT-repeated exposure - Not classified Aspiration hazard - Not classified

11.2 - Information on other hazards

SECTION 12: Ecological information

12.1 - Toxicity

Toxicity: Mixture

EC50 48 hr crustacea	70600 mg/l
LC50 96 hr fish	No data available
ErC50 algae	No data available
ErC50 other aquatic plants	No data available
NOEC chronic fish	No data available
NOEC chronic crustacea	No data available
NOEC chronic algae	No data available
NOEC chronic other aquatic plants	No data available

Toxicity: Substances

acetone, propan-2-one, propanone (67-64-1)	
LC50 96 hr fish	5540 mg/l

- The substance/mixture does not fullfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

12.2 - Persistence and degradability

Biochemical oxygen demand (BOD)	No data available	
Chemical oxygen demand (COD)	No data available	
% of biodegradation in 28 days	No data available	

- No information available.

12.3 - Bioaccumulative potential

Bioconcentration factor (BCF)	No data available
Log KOC	No data available

- No indication of bioaccumulation potential.

12.4 - Mobility in soil



1 L Make-up Solution

- No information available.
- 12.5 Results of PBT and vPvB assessment
- 12.6 Endocrine disrupting properties
- 12.7 Other adverse effects
- No information available.

SECTION 13: Disposal considerations

13.1 - Waste treatment methods

Waste treatment methods - Dispose of waste according to applicable legislation.

Sewage disposal - No information available.

Special precautions for waste treatment - No information available.

Community or national or regional provisions - No information available.

SECTION 14: Transport information

14.1 - UN number or ID number

 UN number (ADR)
 : UN1210

 UN number (RID)
 : UN1210

 UN number (ADN)
 : UN1210

 UN number (IMDG)
 : UN1210

 UN number (IATA)
 : UN1210

14.2 - UN proper shipping name



1 L Make-up Solution

UN proper shipping name

(ADR)

PRINTING INK. flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

pressure

at 50 °C not more than

110 kPa) 640D

UN proper shipping name

(RID)

PRINTING INK, flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

pressure

at 50 °C not more than

110 kPa) 640D

UN proper shipping name

(ADN)

PRINTING INK, flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

at 50 °C not more than

110 kPa) 640D

UN proper shipping name

(IMDG)

PRINTING INK. flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

pressure

at 50 °C not more than

110 kPa) 640D

UN proper shipping name

(IATA)

PRINTING INK, flammable or PRINTING INK RELATED MATERIAL

(including printing ink thinning or reducing compound), flammable (vapour

pressure

at 50 °C not more than

110 kPa) 640D

14.3 - Transport hazard class(es)

ADR Transport hazard

class(es)

3

ADR Classification code:

Pictograms

F1

3

3

Transport hazard class(es)

(RID)

Pictograms

Transport hazard class(es)

(ADN)

Pictograms

Transport hazard class(es)

(IMDG)

3



1 L Make-up Solution

Pictograms

Transport hazard class(es) 3

(IATA)

Pictograms



14.4 - Packing group

Packing group Ш Ш Packing group (RID) Ш Packing group (ADN) Packing group (IMDG) Ш Packing group (IATA) Ш

14.5 - Environmental hazards

Environmental hazards No Marine pollutant No

14.6 - Special precautions for user

ADR

ADR Classification code: F1 ADR Special provisions 163+ 640D+367

ADR Limited quantity (LQ) 5 L ADR Excepted quantities E2

ADR Packing instructions P001 IBC02 R001

ADR Special packing provisions PP1 **MP19** ADR Mixed packing provisions Instructions for portable tanks and bulk containers T4 TP1 TP8 Special provisions for portable tanks and bulk containers ADR tank code **LGBF**

ADR tanks special provisions

Vehicle for tank carriage FL ADR Transport category 2 ADR Tunnel restriction code D/E

ADR Special provisions loading, unloading and handling

Special provisions - Packages

Special provisions - Bulk

Special provisions - Operation S2, S20 33

ADR Hazard identification number (Kemler No.)



1 L Make-up Solution

RID
Special provisions
Limited quantity (LQ)

Excepted quantities :

ADN

Special provisions
Limited quantity (LQ)

Excepted quantities :

IMDG

Special provisions

 Limited quantity (LQ)
 :
 5

 Excepted quantities
 :
 E2

 Packing instructions
 :
 P001

Special packing provisions

IBC instruction(s)

IBC provisions

Instructions for portable tanks and bulk containers

Special provisions for portable tanks and bulk containers

EmS codes

Stowage and handling :

<u>Segregation</u> :

Properties and observations

IATA

PCA - Excepted quantities : E2

PCA - Limited Quantity - Packing Instructions : Y341

PCA - Limited Quantity - Maximum Net Quantity per Package : 1

PCA - Packing Instructions : 353

PCA - Maximum Net Quantity per Package : 5

CAO - Packing Instructions : 364

CAO - Maximum Net Quantity per Package : 60

Special Provisions :

ERG Code :

14.7 - Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 - Safety, health and environmental regulations/legislation specific for the substance or mixture

Substances REACH None

candidates

Substances Annex XIV None
Substances Annex XVII None

VOC content No data available

15.2 - Chemical Safety Assessment



1 L Make-up Solution

 $\frac{\mbox{Chemical safety assessment carried}}{\mbox{out for the product}} \ \ \mbox{- No information available}.$

SECTION 16: Other information

SDS versions

Version	Issue date	Author	Description of the amendments
2,1	17/08/2023		
1	01/12/2017		

Texts of the regulatory sentences

Eye Irrit. 2	Eye irritation - Category 2
Eye Irrit. 2A	Eye irritation - Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
STOT SE 3 (H336)	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

*** *** ***