

1 L Yellow Pigmented Ink

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 - Product identifier

Trade name/designation 1 L Yellow Pigmented Ink

Chemical name

Product-type Mixture

Product code Y108

UFI: YPA6-Y081-7001-M42R

1.2 - Relevant identified uses of the substance or mixture and uses advised against

1.3 - Details of the supplier of the safety data sheet

Southern Technology Ltd
2A Birmingham Drive, Middleton
Christchurch 8024, New Zealand
Phone: 03 3899258
southerntech.co.nz

1.4 - Emergency telephone number

Emergency 111, New Zealand Poisons Centre 0800 764 766

SECTION 2: Hazards identification

2.1 - Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids, Category 2
Eye Irrit. 2	Eye irritation - Category 2
STOT SE 3 (H336)	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

2.2 - Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains: butanone, ethyl methyl ketone (CAS No.: 78-93-3)

Signal word : Danger

Hazard pictograms



Hazard statements

H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	--

1 L Yellow Pigmented Ink

P240	Ground/bond container and receiving equipment.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust, fume, gas, mist, vapours, spray .
P280	Wear protective gloves, protective clothing, eye protection, face protection .

EUH-phrases

EUH066	Repeated exposure may cause skin dryness or cracking
--------	--

2.3 - Other hazards

SECTION 3: Composition / information on ingredients

3.1 - Substances

Not applicable

3.2 - Mixtures

Chemical name	No	%	Class(es)	Specific concentration limit
butanone, ethyl methyl ketone	CAS No. : 78-93-3 Index No. : 606-002-00-3 EC No. : 201-159-0 REACH No. : 01-2119457290-43-XXXX	60 - 70	Eye Irrit. 2 - H319 Flam. Liq. 2 - H225 STOT SE 3 (H336) - H336	Not applicable

SECTION 4: First aid measures

4.1 - Description of first aid measures

<u>Following inhalation</u>	- Provide fresh air. - Get medical advice/attention.
<u>Following skin contact</u>	- After contact with skin, wash immediately with plenty of water and soap. - Remove contaminated, saturated clothing immediately.
<u>After eye contact</u>	- In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
<u>After ingestion</u>	- Do NOT induce vomiting. - Get medical advice/attention.

4.2 - Most important symptoms and effects, both acute and delayed

<u>Symptoms and effects - Following inhalation</u>	- Irritating to respiratory system.
<u>Symptoms and effects - Following skin contact</u>	- Causes skin irritation. - Repeated exposure may cause skin dryness or cracking.
<u>Symptoms and effects - After eye contact</u>	- Irritating to eyes.
<u>Symptoms and effects - After ingestion</u>	- The following symptoms may occur: Vomiting - Nausea - central nervous system depression

4.3 - Indication of any immediate medical attention and special treatment needed

1 L Yellow Pigmented Ink

- Get medical advice/attention.

SECTION 5: Firefighting measures

5.1 - Extinguishing media

Suitable extinguishing media

- Carbon dioxide (CO₂)
- Dry extinguishing powder
- alcohol resistant foam
- Extinguishing media
- Water mist

Unsuitable extinguishing media

- High power water jet

5.2 - Special hazards arising from the substance or mixture

Special hazards arising from the substance or mixture

- Vapours are heavier than air.
- Gases/vapours, toxic
- Highly flammable

Hazardous decomposition products

- Carbon dioxide (CO₂)
- Carbon monoxide

5.3 - Advice for firefighters

- Wear a self-contained breathing apparatus and chemical protective clothing.
- In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 - Personal precautions, protective equipment and emergency procedures

For non-emergency personnel - Avoid contact with eyes and skin.

For emergency responders - No information available.

6.2 - Environmental precautions

- Do not allow to enter into surface water or drains.
- Absorb spillage to prevent material damage.

6.3 - Methods and material for containment and cleaning up

Methods and material for containment

- Soak up inert absorbent and dispose as waste requiring special attention.
- Collect in closed and suitable containers for disposal.
- Collect spillage.

Methods and material for cleaning up

- Wash with plenty of water.

Inappropriate techniques - No information available.

6.4 - Reference to other sections

- Disposal: see section 13

1 L Yellow Pigmented Ink

- Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1 - Precautions for safe handling

Recommendation

- Avoid: Eye contact
- Avoid: Skin contact
- Provide adequate ventilation.
- Precautions for safe handling

Advices on general occupational hygiene

- When using do not eat, drink, smoke, sniff.
- Wash contaminated clothing prior to re-use.
- Wash hands before breaks and after work.

7.2 - Conditions for safe storage, including any incompatibilities

- Keep container tightly closed in a cool, well-ventilated place.

7.3 - Specific end use(s)

- Industrial uses

SECTION 8: Exposure controls/personal protection

8.1 - Control parameters

8.2 - Exposure controls

Appropriate engineering controls

- No information available.

Individual protection measures, such as personal protective equipment

- Suitable eye protection: Eye glasses with side protection

- Protective gloves

- Suitable protective clothing: lab coat



SECTION 9: Physical and chemical properties

9.1 - Information on basic physical and chemical properties

<u>Physical state</u>	Liquid	<u>Appearance</u>	Liquid
<u>Colour</u>	yellow	<u>Odour</u>	characteristic
<u>Odour threshold</u>	No data available		

1 L Yellow Pigmented Ink

pH	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	78 °C
Flash point	-4 °C
Evaporation rate	No data available
flammability	No data available
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	0,878
Density	No data available
Solubility (Water)	insoluble
Solubility (Ethanol)	No data available
Solubility (Acetone)	No data available
Solubility (Organic solvents)	No data available
Log KOC	No data available
Auto-ignition temperature	404 °C < V < 408 °C
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available

Particle characteristics

Particle size	No data available
Dustiness	No data available
Specific surface area	No data available
Shape	No data available

9.2 - Other information

VOC content	No data available
Minimum ignition energy	No data available
Conductivity	No data available

SECTION 10: Stability and reactivity

10.1 - Reactivity

- This material is considered to be non-reactive under normal use conditions.

10.2 - Chemical stability

- The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 - Possibility of hazardous reactions

- No hazardous reaction when handled and stored according to provisions.

10.4 - Conditions to avoid

- In case of warming: Ignition hazard

1 L Yellow Pigmented Ink

10.5 - Incompatible materials

- No information available.

10.6 - Hazardous decomposition products

- No information available.

SECTION 11: Toxicological information

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Not classified

Toxicity : Mixture

LD50 oral (rat)	2737 mg/kg
LD50 dermal (rat)	No data available
LD50 dermal (rabbit)	6480 mg/kg
LC50 inhalation (rat)	No data available
LC50 inhalation dusts and mists (rat)	No data available
LC50 inhalation vapours (rat)	No data available

- Based on available data, the classification criteria are not met.

Toxicity : Substances

butanone, ethyl methyl ketone (78-93-3)	
LD50 oral (rat)	2193 mg/kg
LD50 dermal (rabbit)	5000 mg/kg

Skin corrosion/irritation - Not classified

Serious eye damage/eye irritation - Eye irritation - Category 2 - Causes serious eye irritation

- Irritating to eyes.

Respiratory or skin sensitisation - Not classified

Germ cell mutagenicity - Not classified

Carcinogenicity - Not classified

Reproductive toxicity - Not classified

STOT-single exposure - Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation - May cause drowsiness or dizziness

STOT-repeated exposure - Not classified

Aspiration hazard - Not classified

11.2 - Information on other hazards

SECTION 12: Ecological information

12.1 - Toxicity

1 L Yellow Pigmented Ink

Toxicity : Mixture

EC50 48 hr crustacea	No data available
LC50 96 hr fish	180 mg/l
ErC50 algae	No data available
ErC50 other aquatic plants	No data available
NOEC chronic fish	No data available
NOEC chronic crustacea	No data available
NOEC chronic algae	No data available
NOEC chronic other aquatic plants	No data available

- The substance/mixture does not fulfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

12.2 - Persistence and degradability

Biochemical oxygen demand (BOD)	No data available
Chemical oxygen demand (COD)	No data available
% of biodegradation in 28 days	No data available

- No information available.

12.3 - Bioaccumulative potential

Bioconcentration factor (BCF)	No data available
Log KOC	No data available

- No indication of bioaccumulation potential.

12.4 - Mobility in soil

- No information available.

12.5 - Results of PBT and vPvB assessment

12.6 - Endocrine disrupting properties

12.7 - Other adverse effects

- No information available.

SECTION 13: Disposal considerations

13.1 - Waste treatment methods

Waste treatment methods - Dispose of waste according to applicable legislation.

Sewage disposal - No information available.

Special precautions for waste treatment - No information available.

Community or national or regional provisions - No information available.

SECTION 14: Transport information

14.1 - UN number or ID number

1 L Yellow Pigmented Ink

<u>UN number (ADR)</u>	:	UN1210
<u>UN number (RID)</u>	:	UN1210
<u>UN number (ADN)</u>	:	UN1210
<u>UN number (IMDG)</u>	:	UN1210
<u>UN number (IATA)</u>	:	UN1210

14.2 - UN proper shipping name

<u>UN proper shipping name (ADR)</u>	:	PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D
<u>UN proper shipping name (RID)</u>	:	PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D
<u>UN proper shipping name (ADN)</u>	:	PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D
<u>UN proper shipping name (IMDG)</u>	:	PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D
<u>UN proper shipping name (IATA)</u>	:	PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D

14.3 - Transport hazard class(es)

<u>ADR Transport hazard class(es)</u>	:	3
<u>ADR Classification code:</u>	:	F1
<u>Pictograms</u>		



<u>Transport hazard class(es) (RID)</u>	:	3
<u>Pictograms</u>		



<u>Transport hazard class(es) (ADN)</u>	:	3
---	---	---

1 L Yellow Pigmented Ink

Pictograms



Transport hazard class(es) (IMDG) : 3

Pictograms



Transport hazard class(es) (IATA) : 3

Pictograms



14.4 - Packing group

Packing group : II

Packing group (RID) : II

Packing group (ADN) : II

Packing group (IMDG) : II

Packing group (IATA) : II

14.5 - Environmental hazards

Environmental hazards : No

Marine pollutant : No

14.6 - Special precautions for user

1 L Yellow Pigmented Ink

ADR

<u>ADR Classification code:</u>	:	F1
<u>ADR Special provisions</u>	:	163+ 640D+367
<u>ADR Limited quantity (LQ)</u>	:	5 L
<u>ADR Excepted quantities</u>	:	E2
<u>ADR Packing instructions</u>	:	P001 IBC02 R001
<u>ADR Special packing provisions</u>	:	PP1
<u>ADR Mixed packing provisions</u>	:	MP19
<u>Instructions for portable tanks and bulk containers</u>	:	T4
<u>Special provisions for portable tanks and bulk containers</u>	:	TP1 TP8
<u>ADR tank code</u>	:	LGBF
<u>ADR tanks special provisions</u>	:	
<u>Vehicle for tank carriage</u>	:	FL
<u>ADR Transport category</u>	:	2
<u>ADR Tunnel restriction code</u>	:	D/E
<u>ADR Special provisions loading, unloading and handling</u>	:	
<u>Special provisions - Packages</u>	:	
<u>Special provisions - Bulk</u>	:	
<u>Special provisions - Operation</u>	:	S2, S20
<u>ADR Hazard identification number (Kemler No.)</u>	:	33

RID

<u>Special provisions</u>	:	
<u>Limited quantity (LQ)</u>	:	
<u>Excepted quantities</u>	:	

ADN

<u>Special provisions</u>	:	
<u>Limited quantity (LQ)</u>	:	
<u>Excepted quantities</u>	:	

IMDG

<u>Special provisions</u>	:	
<u>Limited quantity (LQ)</u>	:	5
<u>Excepted quantities</u>	:	E2
<u>Packing instructions</u>	:	P001
<u>Special packing provisions</u>	:	
<u>IBC instruction(s)</u>	:	
<u>IBC provisions</u>	:	
<u>Instructions for portable tanks and bulk containers</u>	:	
<u>Special provisions for portable tanks and bulk containers</u>	:	
<u>EmS codes</u>	:	
<u>Stowage and handling</u>	:	
<u>Segregation</u>	:	
<u>Properties and observations</u>	:	

1 L Yellow Pigmented Ink

IATA

<u>PCA - Excepted quantities</u>	:	E2
<u>PCA - Limited Quantity - Packing Instructions</u>	:	Y341
<u>PCA - Limited Quantity - Maximum Net Quantity per Package</u>	:	1
<u>PCA - Packing Instructions</u>	:	353
<u>PCA - Maximum Net Quantity per Package</u>	:	5
<u>CAO - Packing Instructions</u>	:	364
<u>CAO - Maximum Net Quantity per Package</u>	:	60
<u>Special Provisions</u>	:	
<u>ERG Code</u>	:	

14.7 - Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 - Safety, health and environmental regulations/legislation specific for the substance or mixture

Substances REACH candidates None

Substances Annex XIV None

Substances Annex XVII None

VOC content No data available

15.2 - Chemical Safety Assessment

Chemical safety assessment carried out for the product - No information available.

SECTION 16: Other information

SDS versions

Version	Issue date	Author	Description of the amendments
2,1	17/08/2023		
1	26/01/2018		

Texts of the regulatory sentences

Eye Irrit. 2	Eye irritation - Category 2
Eye Irrit. 2A	Eye irritation - Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
STOT SE 3 (H336)	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

*** **