

ASKO
Inspired by Scandinavia



Dishwashers 40 Series



Turbo Combi Drying™

Combination of fan drying and auto door opening. No more hand-drying.



Premium Flexiracks™ with top tray

Can hold 16 place settings.
XXL: tallest interior tub on the market.



8 Steel™

Eight of the most important parts are made of robust steel or high grade stainless steel. Designed to last for 20 years.



9 Spray™ Zones

Including 2 adjustable PowerZones for all kinds of dishes.



Enjoy the power of silence - 42 dB(A)

Brushless motors.
(40 dB(A) in Night Mode).



Status Light™

Indicating the progress of the program.

40 Series Dishwasher

Durable and sturdy steel racks: 3 level Flexiracks™, **Low noise level:** 42 db(A), (40 dB(A) in Night mode), **Effective and fast drying:** Turbo Combi Drying™ system, **Heavy duty design:** 8 Steel™ construction, **Superior cleaning performance:** 9 Spray™ system



DBI364IS
Pocket Handle
Built-In, XL
Stainless Steel
Interface: Classic
ADA Height



DBI564IS
Pocket Handle
Built-In, XL
Stainless Steel
Interface: Logic
ADA Height



DBI564ISSOF
Pocket Handle
Built-In, XL
Stainless Steel
Interface: Logic
Water Softener
ADA Height



DBI564TS
ASKO T-bar Handle
Built-In, XL
Stainless Steel
Interface: Logic
ADA Height



DBI564THS
Tubular Handle
Built-In, XL
Stainless Steel
Interface: Logic
ADA Height



DBI564PHS
Pro Handle
Built-In, XL
Stainless Steel
Interface: Logic
ADA Height



DBI564IXXLS
Pocket Handle
Built-In, XXL
Stainless Steel
Interface: Logic



DFI564
Panel Ready, XL
Interface: Logic
ADA Height



DFI564XXL
Panel Ready, XXL
Interface: Logic



(Shown: DBI564IS)

Features

- 8 Steel™ construction: non-magnetic stainless steel container, inner door, spray arms, strainers, spray pipes; nylon-coated steel racks; steel feet and outer base in steel.
- Both circulation and drain pump have extra durable and quiet brushless motors
- Fully graphical FFSTN display.
- XXL: Tallest interior tub in the market.
- XL models are ADA height compliant.

Performance

- Super Cleaning System™: Intensive rinsing that cleans the dishes and the machine before main wash.
- Unique 9 Spray™ system, designed for reaching every corner of the dishwasher.
- Adjustable power zones, possible to set for cleaning pots & pans or bottles & vases. Also possible to turn off.
- Turbo Combi Drying™ - fan-assisted drying, and automatic door open drying, that eliminates all humidity.
- 20 years of domestic use. (Quality test: 12,500 hours, 280 cycles per year).

Programs / Options

- 9 programs: Normal, Light, Intensive, Quick, Time, Sanitize, Rinse and Hold, Self-Cleaning, Anti-Odor.
- Washing temperatures: 131 to 158°F.
- 3 Modes: Normal, Speed, Night.
- 2 options: Automatic door opening, Delayed start (1-24 h).

Comfort / Safety

- Status Light™ indicating the progress of the program.
- The Aqua Safe™ system guarantees protection against water leaks.
- Easy installation: From front adjustable door springs (panel ready models) and rear foot (all models).

Dimensions

- Appliance dimensions (H / W / D): XL 32 3/4" - 34 13/16" / 23 15/16" / 21 13/16".
XXL 33 5/16" - 36 7/16" / 23 15/16" / 21 13/16"
- Necessary space dimensions (H / W / D): XL 32 11/16" / 24" / 21 7/8". XXL 34 1/4" / 24" / 21 7/8"
- Length of the power cable / Location: 71 7/8", 1825 mm / Back right.
- Length of PEX inlet hose / Locknut dimensions* / Location: 64", 1625 mm / 3/4", 19.5 mm / Back left
- Length of outlet hose / Outlet diameter / Location: 59 5/8", 1515 mm / 3/4", 19.5 mm / Back left
- Custom door length / Rotation point: XL 27 9/16" - XXL 31 1/2" (sliding door: XL 29 15/16" - XXL 33 1/16") / 27 15/16", XL 700 - XXL 800 (sliding door: XL 760 - XXL 840) / 710mm).

Baskets and drawers

- Height adjustable top tray
- Premium height adjustable upper rack
- Premium lower rack
- Cutlery basket

Installation

- Consult the product installation manual for all updated dimensions.

Measurements: inches / millimetres

