

# DBI564ISSOF.U Built-in undercounter dishwasher

## General description

Turbo Combi Drying Product line: Logic Mode of installation: Built In Size: ADA height compliant Number of baskets: 3 Number of place settings: 16 place settings Top tray: Easy height adjustment; Handle; Removable Upper basket type: Premium Lower basket type: Premium Removable cutlery basket for easy unloading



#### Construction

- Welded stainless steel container
- Exterior float detects water leakage on the base
- Stand by water protection
- Anti-block drain pump
- 8 Steel™ Construction
- Hidden heater
- SCS+ Super Cleaning System+™
- Softener
- Number of spray arms: 3
- Number of spray zones: 9
- Turbo Combi Drying
- Automatic door opening
- Cutlery Power Zone extra dishwashing power for the cutlery basket
- Door handle type: Integrated soft closing handle

#### Use and flexibility

- Number of place settings: 16 place settings
- Number of baskets: 3
- Top tray: Easy height adjustment; Handle; Removable
- Upper basket type: Premium
- Lower basket type: Premium
- Tight mesh base in the baskets
- Removable cutlery basket for easy unloading
- Required inlet water pressure: 0,03-1 MPa

# Interaction & control

- Display Type: LCD display
- Ability to create own programs: Memory program
- Number of programs: 9
- Number of options: 6 .
- Status Light™
- Time remaining indicator: Yes
- Cycle end indication: Displayed with sound and light
- . Adaptable power zones

## Programs

- 9 programs: Normal wash; Quick wash; Intensive program; Time program; Rinse and hold; Self-cleaning; Light wash; Sanitize; Anti odour
  - Delayed start: 1-24 hours
- Speed mode
- Night mode
- Heat boost mode Normal mode

# **Design & integration**

- From front adjustable rear foot •
- Trim kit
- Multi fit outlet hose
- Simplified installation with integrated anti-siphon
- Depth (incl. wall spacing): 21 7/8" (555 mm) 0





Height setting: 2 1/16" (53 mm)

# Safety & Maintenance

- Aqua Safe™
- . Kid Safe™ lockable controls
- Rinse-aid indication: Notification in display
- Salt indication: Salt indication: Notification in display

## Technical data

- Hot or cold water connection 9/16 •
- Max. temperature of inflow water: 140 F
- Noise level: 42 dB(A) •
- Duration of normal wash cycle: 125 min 0
- Estimated annual energy consumption: 220 kWh .
- Energy consumption/cycle: 1 kWh •
- Estimated annual water consumption: 647 US Gal
- Water consumption/cycle: 3 US Gal
- . Consumption in standby mode: 0.5 W
- Connection rating: 1300 W •
- Number of phases: 1
- Current: 15 A
- Frequency: 60 Hz
- . Required inlet water pressure: 0,03-1 MPa
- Net weight: 90 lbs

## Dimensions


- Width: 23 15/16" (608 mm)
- . Height: 32 11/16" (831 mm)
- . Depth: 21 13/16" (554 mm)
- Maximum product height: 34 13/16" (884 mm)
- Cord length: 71 7/16" (1815 mm)
- Depth with door open: 46 7/8" (1191 mm)
- Length of inflow hose: 64 3/16" (1630 mm)
- Length of outflow hose: 90 9/16" (2300 mm)

# Logistic information

- Packaging width: 25 3/16" (640 mm)
- Packaging height: 35 1/16" (890 mm)
- Packaging depth: 26 3/4" (680 mm)
- Total weight of packaged product: 97 lbs
- Code: 740108
- EAN code: 3838782645464
- Market: Domestic Range: Logic



Measurements: inches / millimetres



DW60 Built-in Dishwasher XL USA

