or use only as a surface biocide against moulds, mosses, lichen and algae on internal and external surface: such as masonry and tiles. FOR USE ONLY BY PROFESSIONAL OPERATORS. The (COSHH) Control of Substances Hazardous to Health Regulations 2002 may apply to the use of this product at work. Engineering control of operator exposure must be used where reasonably practicable in addition to the following items of personal rotective equipment. Wear suitable protective clothing, suitable gloves and eye/face protection. AVOID EXCESSIVE CONTAMINATION OF COVERALLS AND LAUNDER REGULARLY, Do not breathe spray, Otherwise wear respiratory protective equipment and eye protection (See HSE Guidance Booklet HS(G)53: "The Se Use and Maintenance of Respiratory Protective Equipment - A Practical Guide"). However engineering controls may replace personal protective equipment if a COSHH assessment shows they provide an equal or higher standard of protection. DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES. This material and its container must be disposed of in a safe way. Avoid contact with skin. Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. UNPROTECTED PERSONS AND ANIMAL'S SHOULD BE KEPT AWAY FROM TREATED AREAS FOR 48 HOURS OR UNTIL SURFACES ARE DRY. COVER ALL WATER STORAGE TANKS before application. DO NOT USE NEAR DRAINS, PREVENT ANY SURFACE RUN-OFF FROM ENTERING DRAINS, REMOVE OR COVER ALL FISH TANKS AND BOWLS before application. This product contains substances which are known to be hazardous to the environment. Do not contaminate ground, waterbodies or watercourses with chemicals or used container. READ ALL PRECAUTIONS BEFORE USE (HSE 8392).

DANGER

H314 - Causes severe skin burns and eye damage. H410 - Very toxic to aquatic life with long lasting effects

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.
P303 + P361 + P353 - IF ON SKIN (or hair):Remove/Take off immediately all

contaminated clothing Rinse skin with water/shower.

P304 + P340 - If inhaled move person to fresh air and keep comfortable for breathing. EUH031 - Contact with acids liberates toxic gas.



STATUTORY CONDITIONS RELATING TO USE

UN3266

1310-73-2- Sodium Hydroxide

П Emb 56.206

5 Litre Product Code: 3012



SPCB (UK) Limited, PO Box 1349, Lincoln LN2 3XS 01673 895130 info@mosskillers.co.uk www.mosskillers.co.uk

For use only as a surface biocide against moulds, mosses, lichen and algae on internal and external surfaces such as masonry and tiles. FOR USE ONLY BY PROFESSIONAL OPERATORS. The (COSHH) Control of Substances Hazardous to Health Regulations 2002 may apply to the use of this product at work. Engineering control of operator exposure must be used where reasonably practicable in addition to the following items of personal protective equipment. Wear suitable protective clothing, suitable gloves and eye/face protection. AVOID EXCESSIVE CONTAMINATION OF COVERALLS AND LAUNDER REGULARLY. Do not breathe spray, Otherwise wear respiratory protective equipment and eye protection (See HSE Guidance Booklet HS(G)53: "The Selection Use and Maintenance of Respiratory Protective Equipment - A Practical Guide"). However engineering controls may replace personal protective equipment if a COSHH assessment shows they provide an equal or nigher standard of protection. DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES. This material and its container must be disposed of in a safe way. Avoid contact with skin. Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Unprotected persons and animal's should be kept away from treated areas for 48 hours OR UNTIL SURFACES ARE DRY. COVER ALL WATER STORAGE TANKS before application. DO NOT USE NEAR DRAINS, PREVENT ANY SURFACE RUN-OFF FROM ENTERING DRAINS. REMOVE OR COVER ALL FISH TANKS AND BOWLS before application. This product contains substances which are known to be hazardous to the environment. Do not contaminate ground, waterbodies or watercourses with chemicals or used container READ ALL PRECAUTIONS BEFORE USE (HSE 8392).

H314 - Causes severe skin burns and eye damage

H410 - Very toxic to aquatic life with long lasting effects

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.

 $P303 + P361 + P353 - IF\ ON\ SKIN\ (or\ hair): Remove/Take\ off\ immediately\ all$

contaminated clothing Rinse skin with water/shower.

P304 + P340 - If inhaled move person to fresh air and keep comfortable for breathing.

EUH031 - Contact with acids liberates toxic gas.



UN3266

II

Emb 56 206

1310-73-2- Sodium Hydroxide



SPCB (UK) Limited, PO Box 1349, Lincoln LN2 3XS 01673 895130 info@mosskillers.co.uk www.mosskillers.co.uk

BATIFAST

RAPID ACTING CLEANER Quickly clean internal & external surfaces.

USE PURE OR DILUTED Apply then rinse. Works on contact. 1 Litre covers up to 12m²

Batifast is a high power alkaline, surface cleaner for use on hard surfaces. It can be used pure or diluted, acting quickly without the need to scrub. Gives a new appearance to tarmac and walls. Following the use of Batifast, use Baticlean CR and/or Hydrosil to keep surfaces clean.

May be used at all times of year in dry weather, preferably at a temperature of 5-30°C. For best results ensure the surface to be treated is dry. For light conditions, dilute 1 litre of product with 1 litre of water, apply 1 litre of diluted product per 4-62 metres of surface. For heavily soiled surfaces, apply 1 litre of pure product per 4-6² metres. Apply by spray or brush. Leave to act for 5-15 minutes & rinse with water. Pressure may be used. Apply a second application if necessary. Do not let treated area dry before rinsing.

EXAMPLES OF USE

Roofing: Slate, tile, corrugated sheeting, flat roofs... Walls: Plaster, brick, stone, blockwork, render... Gardens: Patios, driveways, paths, balconies, rockeries, ornaments... Other: Sports courts, play areas, car parks...

BATIFAST

RAPID ACTING CLEANER Quickly clean internal & external surfaces.

USE PURE OR DILUTED Apply then rinse. Works on contact. 1 Litre covers up to 12m²

Batifast is a high power alkaline, surface cleaner for use on hard surfaces. It can be used pure or diluted, acting quickly without the need to scrub. Gives a new appearance to tarmac and walls. Following the use of Batifast, use Baticlean CR and/or Hydrosil to keep surfaces clean.

May be used at all times of year in dry weather, preferably at a temperature of 5-30°C. For best results ensure the surface to be treated is dry. For light conditions, dilute 1 litre of product with 1 litre of water, apply 1 litre of diluted product per 4-62 metres of surface. For heavily soiled surfaces, apply 1 litre of pure product per 4-62 metres. Apply by spray or brush. Leave to act for 5-15 minutes & rinse with water. Pressure may be used. Apply a second application if necessary. Do not let treated area dry before rinsing.

EXAMPLES OF USE

Roofing: Slate, tile, corrugated sheeting, flat roofs... Walls: Plaster, brick, stone, blockwork, render... Gardens: Patios, driveways, paths, balconies, rockeries, ornaments... Other: Sports courts, play areas, car parks...