

FN-INK BARRIER BLACK

Plastisol ink for printing backgrounds that block sublimation, phthalates free.

DESCRIPTION

Plastisol ink to be used as a background print on all synthetic or natural substrates in which there are problems of migration of the substrate dye.

The use of this product guarantees a high barrier effect that blocks the phenomenon of sublimation and does not allow the dyeing of the fabric to alter the overprinted colours.

PRODUCT PROPERTIES

Description	Typical Value
APPEARANCE	Grey paste

APPLICATION

Plastisol ink to be used as a background, to be printed with screens having threads between 34 and 43 threads/cm, in order to obtain an extremely uniform and covered background, which after flashing can be overprinted with all the products of the FN-INK range.

Its particular formulation allows rapid drying and does not come out under subsequent flashes, ensuring that the overprinted colours are not subject to alteration after curing and over time.

Notes: the inks of this series are not resistant to dry cleaning, bleaching and ironing.

Fixation: by thermofusion oven at 130°C for 3 minutes.

STORAGE

PROTECT FROM FROST	•	Store at temperatures between 5°C and 40°C.
MIX BEFORE USE	•	
OTHER NOTES	•	Store in a dry place away from flames or sparks. Avoid contact with oxidants, strong acids and salts in general.

STANDARD PACKAGING

250kg drum

SECURITY

When handling this product, please observe the information contained in the relevant safety data sheet and observe the necessary protective measures.

NOTES

Data contained in this document are based on our current knowledge and experience, should not be considered a guarantee, considering the numerous factors that can affect the process and the application of our product. These data do not relieve users from carrying out their own preventive tests, therefore we cannot be held responsible for the results obtained with our products and for any loss or incident that may arise from their use. The agreed quality of the product derives exclusively from the statements contained in the product specifications.