# SAFETY DATA SHEET

### 1. Identification

**BLAST** Product identifier

Company information CHEMICAL CONSULTANTS INC

1850 WILD TURKEY CIRCLE

CORONA, CA 92880 United States

Company phone 1-951-735-5511

**Emergency telephone US** INFOTRAC: 1-800-535-5053

02 Version #

Recommended use Screen Opener Recommended restrictions None known.

# 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Skin corrosion/irritation Health hazards Category 2 Serious eye damage/eye irritation Category 2 Aspiration hazard Category 1 **Environmental hazards** Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

Not classified. OSHA defined hazards

Label elements



Signal word

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation.

Causes serious eye irritation. Harmful to aquatic life. Harmful to aquatic life with long lasting

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Avoid release to the environment, Wear protective gloves, Wear

eve/face protection.

If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If in Response

eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash

before reuse.

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Solvent Naphtha (Petroleum), Light Aromatic		64742-95-6	20 - 40
1,2,3-trimethylbenzene		526-73-8	10 - 20
Butane		106-97-8	10 - 20
Cyclohexanone		108-94-1	10 - 20
Propane		74-98-6	10 - 20
Xylenes		1330-20-7	1 - 2.5
Other components below reportable lev	els		0.1 - 1

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

# 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Dizziness. Headache. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Ingestion

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting

equipment/instructions

Specific methods

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

### **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 2 Aerosol.

# 8. Exposure controls/personal protection

## Occupational exposure limits

Components	Type	Value	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
•		50 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
Xylenes (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	
US. ACGIH Threshold Limit Value	s		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
•	TWA	20 ppm	
Xylenes (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Type	Value	
1,2,3-trimethylbenzene (CAS 526-73-8)	TWA	125 mg/m3	
		25 ppm	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m3	
		25 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
-		1000 ppm	

### Biological limit values

<b>ACGIH I</b>	Biological	Exposure	Indices
----------------	------------	----------	---------

Components	Value	Determinant	Specimen	Sampling Time
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*
Xylenes (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

<sup>\* -</sup> For sampling details, please see the source document.

### Exposure guidelines

US - California OELs: Skin designation

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cyclohexanone (CAS 108-94-1) Skin designation applies.

US - Tennesse OELs: Skin designation

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

### **Appearance**

Physical state Liquid.
Form Aerosol.
Color Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

312.08 °F (155.6 °C) estimated

Flash point 16.2 °F (-8.8 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

1.2 % estimated

Flammability limit - upper

(%)

9.5 % estimated

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

19.03 psig @70F estimated Vapor pressure

Vapor density Not available.

Relative density 0.807 g/cm3 estimated

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

894 °F (478.89 °C) estimated Auto-ignition temperature

Decomposition temperature Not available. Viscosity Not available.

Other information

Density 0.81 g/cm3 estimated Flammability class Flammable IB estimated 23.8 kJ/g estimated Heat of combustion Heat of combustion (NFPA 23.8 kJ/g estimated

30B)

Percent volatile 48.97 % estimated 0.807 estimated Specific gravity VOC (Weight %) 48.97 % estimated

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials. Incompatible materials Strong acids. Strong oxidizing agents. Nitrates, Halogens, Fluorine, Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

### 11. Toxicological information

Information on likely routes of exposure

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Inhalation Prolonged inhalation may be harmful.

Causes skin irritation. Skin contact

Causes serious eye irritation. Eye contact

Symptoms related to the physical, chemical and toxicological characteristics

Dizziness. Headache. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

May be fatal if swallowed and enters airways. Acute toxicity

Product	Species	Test Results
15 OZ CHEMICAL CNSLTN	T SCRN OPNR LT 12PK (CAS Mixture)	
Acute		
Dermal	Date:	5470 7505 marilan 04 Harris and in the d
LD50	Rabbit	5479.7505 mg/kg, 24 Hours estimated
	Rat	7682.4409 mg/kg, 24 Hours estimated
Inhalation		
LC100	Cat	321.3138 % estimated
LC50	Mouse	4416.2798 mg/l, 120 Minutes estimated
		1722.7418 mg/l, 7 Hours estimated
		185.648 %, 120 Minutes estimated
		57.1225 mm/l, 2 Hours estimated
	Mouse, Rat	11843.8506 mg/m3, 12 Hours estimated
	Rat	46494.1094 ppm, 4 Hours estimated
		11824.8564 mg/m3, 4 Hours estimated
		15.0629 mg/l/4h estimated
		9.9958 mg/l, 4 Hours estimated
Oral		o.oooo mgm, + roomo oommatou
LD50	Rat	861.3709 ml/kg estimated
		23.5799 mg/kg estimated
Components	Species	Test Results
1,2,3-trimethylbenzene (CAS		rest results
Acute	3 320-73-6)	
Dermal		
LD50	Rat	3440 mg/kg, 24 Hours
Inhalation		0 0
LC50	Mouse, Rat	2000 - 9833 mg/m3, 12 Hours
	Rat	10200 mg/m3, 4 Hours
Oral		3
LD50	Rat	4 - 3440 mg/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Cyclohexanone (CAS 108-9	4-1)	, and the second
Acute	,	
Inhalation		
LC50	Rat	> 6.2 mg/l, 4 Hours
Oral		
LD50	Rat	1620 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
		<u>-</u>

Test Results Components Species

Solvent Naphtha (Petroleum), Light Aromatic (CAS 64742-95-6)

Acute

Dermal

LD50 Rabbit > 1900 mg/kg, 24 Hours

Inhalation

LC50 Rat > 5020 mg/m3, 4 Hours

> 4980 mg/m3

> 4980 mg/m3, 4 Hours > 4.96 mg/l, 4 Hours

Oral

LD50 Rat > 4800 mg/kg

Xylenes (CAS 1330-20-7)

Acute

Dermal

LD50 Rabbit > 5000 ml/kg, 4 Hours

12126 mg/kg, 24 Hours

Inhalation

LC50 Rat 5922 ppm, 4 Hours

Oral

LD50 Mouse 5251 mg/kg

> 3523 mg/kg Rat

> > 10 ml/kg

Causes skin irritation. Skin corrosion/irritation

Causes serious eye irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Not available. Respiratory sensitization

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cyclohexanone (CAS 108-94-1) 3 Not classifiable as to carcinogenicity to humans. Xylenes (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Components in this product have been shown to cause birth defects and reproductive disorders in Reproductive toxicity

laboratory animals.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Product		Species	Test Results
15 OZ CHEMICAL CNS	SLTNT SCRN OPI	NR LT 12PK (CAS Mixture)	
Aquatic			
Algae	IC50	Algae	517.3394 mg/L, 72 Hours estimated
Crustacea	EC50	Daphnia	10.7779 mg/L, 48 Hours estimated
Fish	LC50	Fish	16.3407 mg/L, 96 Hours estimated
Components		Species	Test Results
1,2,3-trimethylbenzene	(CAS 526-73-8)		
Aquatic			
Crustacea	EC50	Daphnia	6.14 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.19 - 8.28 mg/l, 96 hours
Cyclohexanone (CAS 1	08-94-1)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	481 - 578 mg/l, 96 hours
Solvent Naphtha (Petro	leum), Light Arom	atic (CAS 64742-95-6)	
Aquatic			
Crustacea	EC50	Daphnia	6.14 mg/L, 48 Hours
Xylenes (CAS 1330-20-	-7)		
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

 Butane
 2.89

 Cyclohexanone
 0.81

 Propane
 2.36

 Xylenes
 3.12 - 3.2

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

....

US RCRA Hazardous Waste U List: Reference

Cyclohexanone (CAS 108-94-1) U057 Xylenes (CAS 1330-20-7) U239

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

# 14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) None

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

N82 Special provisions Packaging exceptions 306 None Packaging non bulk None Packaging bulk

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

### IATA

UN1950 UN number

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Not applicable. Packing group

**Environmental hazards** Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed. Packaging Exceptions LTD QTY

**IMDG** 

UN1950 **UN number AEROSOLS** UN proper shipping name

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) None

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant Yes F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

LTD QTY Not applicable.

# DOT



### IATA; IMDG



# Marine pollutant



General information

IMDG Regulated Marine Pollutant.

# 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cyclohexanone (CAS 108-94-1) Listed. Xylenes (CAS 1330-20-7) Listed.

# SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

# SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Xylenes	1330-20-7	1 - 2.5
Cumene	98-82-8	0.1 - 1

# Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Xylenes (CAS 1330-20-7)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

### US state regulations

### US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6) Xylenes (CAS 1330-20-7)

### US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6)

Xylenes (CAS 1330-20-7)

# US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6)

Xylenes (CAS 1330-20-7)

### US. Rhode Island RTK

Butane (CAS 106-97-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6)

Xylenes (CAS 1330-20-7)

### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

Cumene (CAS 98-82-8) Listed: April 6, 2010

### International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date 10-10-2014

Version # 02

Disclaimer CCI cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or

in any process, unless specified in the text.

11 / 11

On inventory (yes/no)\*