

Heat Activated

Data Sheet

Fusion 4000® (Acid Free)

Fusion 4000® is a thermal-activated 100% acid-free adhesive film. The adhesive melts during the heating process, bonds as it cools, and is removable when reheated. It can be patched, overlapped and pieced together because it flows under heat and pressure. Fusion 4000® is also self-trimming and is ideal for mounting lithographs, newsprint, photographs, inkjet media, vellum engravings, silks, canvas, foils and much more.

SPECIFICATION

Construction

Adhesive

Processing time and temperature

100% Pure adhesive film with no tissue carrier.

Acid free pH neutral pure adhesive and removable when reheated.

77° – 85°C Dwell time 2 – 4mins depending on the substrate used. Fusion 4000 is very versatile and can be used with a variety of substrates.

HEALTH & SAFETY

When used for the purpose intended this product presents no known hazard

WARRANTY

All data pertaining to this product has been compiled from research and is believed to be correct however it is for guidance only. It is recommended that the purchaser independently determines that the product is suitable for purpose.

Mountingsubstrates.com reserves the right to alter or amend information without giving prior notice.

Mountingsubstrates.com Moulton Park Business Centre Redhouse Road Northampton NN3 6AQ 01604 497775

sales@mountingsubstrates.com www.mountingsubstrates.com