

DTF FILM

- Product Code: DT

■ PRODUCT INFORMATION



The most consistent & premium Korean DTF Film available.





- 100% Dae Ha coating technology.
- Ensure Consistent & stable quality roll after roll.
- Genuine instant HOT PEEL for one time heat press.
- No shrinkage of image design after printing.
- Lower oven temperature possible.
- Easy to print ultra-fine detail.
- The only DTF Film produced with Recycled Blended Polyester.

[Reports or Certifications: OEKO TEX / CPSIA / EN71 / SGS TEST REPORT](#)

■ MATERIAL SPECIFICATION

- * Both side Matt
- * Thickness: 75 μ m
- * Standard roll size: 600mm x 100M

■ PRINTING & TRANSFER CONDITIONS

 Ink Type	 Temperature	 Time	 Peel
Water Base ink for DTF	140°C~150°C / 284°F~302°F	8~10 seconds	Hot

■ HOW TO USE

1. Print directly onto the film.
2. Apply hotmelt powder on the printed images.
3. Shake off the excess hotmelt powder well.
4. Melt the hotmelt powder in the oven.
5. Set a heat press to 140°C~150°C.
6. Apply medium and even pressure across your transfer.
6. Press for 8~10 seconds.
7. Peel the DTF Film when it is Hot.

NB: Depending on the specification or setting of a DTF machine, different printing results may come out.

We highly recommend performing a test before proceeding with standard production.



■ STORAGE CONDITIONS

- * Temperature: Less than 25°C (\pm 3°C)
- * Relative Humidity: 30% (\pm 20%)
- * Keep out of direct sunlight.

■ SUITABLE FOR

- * 100% Cotton or 100% Polyester
- * Mixtures of polyester/cotton
- * Acrylic and similar fabrics
- * Not suitable for Nylon or Coated Fabrics