METALLIC FLEX

Product Code: DNM

PRODUCT INFORMATION



Dae Ha Metallic Flex is a true metallic film in every sense.

- High glossy and mirrored effects.
- Sublimation printing is possible on the surface.
- Excellent durability.
- Easy to cut and weed.
- Cut the finest of detail.
- Great for fashion, party and leisure wear.
- Various color options available.

MATERIAL SPECIFICATION

- * Composition: Polyester
- * Adhesive carrier
- * Thickness: 100 ± 5µm
- * Standard roll size: 500mm x 100M

CUTTING & TRANSFER CONDITIONS Plotter Machine: GCC Jaguar IV / Mimaki CJV150 75

Я	Cut Direction	P	Cutting Force	>>>	Speed	Blade
	Reverse		110gfs		15cm/s	45°
	Temperature	\bigcirc	Time		Press Pressure	Peel
160°0	C~170°C / 320°F~338°F	Ę	3~10 seconds	-	Medium	Warm

NB: The plotter machine settings should be adjusted based on the age and brand of the machine.

HOW TO USE

- 1. Cut your design in reverse on a plotter machine.
- 2. Weed out excess film.

4. Apply medium and even pressure across your transfer. 5. Press for 8~10 seconds.

6. Peel the release liner when it is Warm.

3. Set a heat press to 160°c~170°c NB: We highly recommend performing a test before proceeding with standard production.

WASHING CONDITIONS Washing Machine: LG Drum / Detergent: Persil Liquid

Washing	Water Temp.	Tumble Dry	ار ال	Bleach
Standard	40°C	Available on low setting	Inside Out	Not Allowed

NB: It is recommended to wait at least 24hours after the heat pressing before a first washing.

STORAGE CONDITIONS

- * Temperature: Less than 25°C (±3°C)
- * Relative Humidity: 40% (±20%)
- * Keep out of direct sunlight.
- * Shelf life: 1 year from manufacturing date

SUITABLE FOR

- * 100% Cotton or 100% Polyester
- * Mixtures of polyester/cotton
- * Acrylic and similar fabrics
- * Not suitable for Nylon or Coated Fabrics



Manufacturer of HTV and DTF Film

DAE HA CO., LTD. Main Office: 9F, 10F Daeha Bldg. 499 Gangseo-ro, Gangseo-gu Seoul 07523 Korea Phone: 82 2 2675 2758 I Email: info@garmentfilms.com I Web: www.garmentfilms.com

