

PRINTABLE SUBLI-BLOCK PU

● Product Code: PTUSB

■ PRODUCT INFORMATION











Printable Subli-Block PU makes your designs really stand out.

- Creates the ultimate barrier to dye migration.
- Suitable for Eco Solvent ink on print & cut machine.
- Perfect printable material for dark garment
- Vivid and clear color printing.
- Instant drying with bright print results.
- Brilliant white base film which is very easy cut and weed.
- Excellent wash durability
- Not suitable for Eco Sol Max 3 or TrueVIS inks.

■ MATERIAL SPECIFICATION

- * Composition: PU
- * Non adhesive carrier
- * Thickness: 160 ± 20µm
- * Standard roll size: 500mm x 50M

■ PRINTING & TRANSFER CONDITIONS Mimaki CJV150 75 / Roland VP-540

 Ink Type	 Print Direction	 Drying Temp.	 Blade
Eco Solvent ink	No Reverse	41~45°	45°
 Temperature	 Time	 Press Pressure	 Peel
150°C / 302°F	10 seconds	Medium	Warm






NB: The plotter machine settings should be adjusted based on the age and brand of the machine

■ HOW TO USE

1. Print and cut directly onto the face of the film.
2. Do not mirror design.
3. Weed out excess film.
4. Use Dae Ha Application tape to transfer the design.
5. Set a heat press to 150°C.
6. Apply medium and even pressure across your transfer.
7. Press for 10 seconds.
8. Peel the PET liner when it is Warm.

NB: We highly recommend performing a test before proceeding with standard production.

■ WASHING CONDITIONS Washing Machine: LG Drum / Detergent: Persil Liquid

 Washing	 Water Temp.	 Tumble Dry	 Iron	 Bleach
Standard	60°C	Available on low setting	Inside Out	Not Allowed

NB: It is recommended to wait at least 24hours after the heat pressing before a first washing.

■ STORAGE CONDITIONS

- * Temperature: Less than 25°C (±3°C)
- * Relative Humidity: 40% (±20%)
- * Keep out of direct sunlight.
- * Shelf life: 1 year from manufacturing date

■ SUITABLE FOR

- * 100% Cotton or 100% Polyester
- * Mixtures of polyester/cotton
- * Acrylic and similar fabrics
- * Not suitable for Nylon or Coated Fabrics