


SUBLI FLOCK

• Product Code: SFK

PRODUCT INFORMATION



Subli Flock is a white flock developed for sublimation printing.

- The Flock texture will provide bright & colorful images.
- Great result after sublimation printing due to dense fiber.
- Adds texture effect with unique colors and patterns.
- Matt finish.
- Suitable for creating unique design patches.
- Available for both the dark and white garments.
- Compatible with sublimation paper.
- No loss of color after washing.

MATERIAL SPECIFICATION

- * Composition: Polyester Fabric
- * Adhesive carrier * Thickness: $500 \pm 50 \mu m$
- * Standard roll size: 440mm x 50M

■ CUTTING & TRANSFER CONDITIONS

| Я | Cut Direction | Cutting Force | >>> | Speed | | Blade |
|--|---------------|---------------|---------------------|----------------|--|-------|
| | No Reverse | 150gfs | | 15cm/s | | 45° |
| Temperature & Time | | | \triangleq | Press Pressure | | Peel |
| Heat Pressing: 160°C / 320°F for 8~10 seconds Sublimation: 180°C~200°C / 356°F~392°F for 20~30 seconds | | | Medium | | Heat Pressing: Cold Sublimation: Hot / Warm | |

NB: The plotter machine settings should be adjusted based on the age and brand of the machine.

HOW TO USE

- 1. Cut your design in reverse on Subli Flock.
- 2. Weed out excess film.
- 3. Print a design in reverse on Sublimation paper.
- 4. Set a heat press to 160°C and press for 8~10 seconds. 7. Peel the release liner when it is Hot / Warm.
- 5. Align printed Sublimation paper onto Subli Flock.
- 6. Set a heat press to 180°C~200°C.
- 7. Press for 20~30 seconds.

NB: We highly recommend performing a test before proceeding with standard production.

■ WASHING CONDITIONS Washing Machine: LG Drum / Detergent: Persil Liquid

| Washing | Water Temp. | Tumble Dry | ☐ Iron | Bleach |
|---------|-------------|------------|------------|-------------|
| Wool | 40°C | Avoid | Inside Out | Not Allowed |

NB: It is recommended to wait at least 24hours after the heat pressing before a first washing.

■ STORAGE CONDITIONS

- * Temperature: Less than 25°C (±3°C) * Relative Humidity: 40% (±20%)
- * Keep out of direct sunlight.
- * Shelf life: 1 year from manufacturing date

■ SUITABLE FOR

- * 100% Cotton or 100% Polyester
- * Mixtures of polyester/cotton
- * Acrylic and similar fabrics
- * Not suitable for Nylon or Coated Fabrics



