

# *Prosthetics*









Conical Connection | Active Hex





# Healing Caps

Material: Titanium (Ti6Al4V ELI). Recommended torque: 20 Ncm.

## Healing Cap Conical Connection NP 3.5 & RP 4.3



L	2.0	3.0	4.0	5.0
Ø 4.5 mm				
	HCC-2-NP	HCC-3-NP	HCC-4-NP	HCC-5-NP
Ø 4.5 mm				
	HCC-2-RP	HCC-3-RP	HCC-4-RP	HCC-5-RP





# Implant Analogs

Material: Stainless Steel (Grade 316).

## Implant Analogs Conical Connection NP 3.5 & RP 4.3



Type	H (mm)	Ø (mm)	Ref:
	12.0	3.5	SAC-NP
	10.0	3.9	SAC-RP




# Impression Transfers



Material: Stainless Steel (Grade 316)


## Open Tray Transfer Conical Connection NP 3.5

Type	H (mm)	Ø (mm)	Ref:
	Body 12.0	4.7	<b>ITCS-NP</b>
	Short Screw 14.0	2.0	
	Body 15.0	4.7	<b>ITCL-NP</b>
	Long Screw 22.0	2.0	






## Open Tray Transfer Conical Connection RP 4.3

Type	H (mm)	Ø (mm)	Ref:
	Body 12.0	4.7	<b>ITCS-RP</b>
	Short Screw 14.0	2.0	
	Body 15.0	4.7	<b>ITCL-RP</b>
	Long Screw 22.0	2.0	






### Click Transfer Conical Connection NP 3.5

Type	L (mm)	H (mm)	Ø (mm)	Ref:
	10.3	14.5	3.5	<b>SCLT9-NP</b>
	16.4	20.5	3.75	<b>SCLT15-NP</b>






### Click Transfer Conical Connection RP 4.3

Type	L (mm)	H (mm)	Ø (mm)	Ref:
	10.5	15.0	4.25	<b>SCLT9-RP</b>
	16.5	21.0	4.75	<b>SCLT15-RP</b>






### Fixation Screw Conical Connection NP 3.5 & RP 4.3


Type	H (mm)	Ø D (mm)	Ref:
	Screw for abutment Platform NP 8.5	1.25	<b>SCA-NP</b>
	Screw for abutment Platform RP 8.5	1.35	<b>SCA-RP</b>






The **Transfer** with a plastic cap is designed for impressions using the closed-tray technique. The cap remains in the impression tray after removing it from the mouth. Material: Titanium (Ti6Al4V ELI). Recommendation: Hand-tighten using a 1.25 mm hex driver or a motor mount with a force of 30 Ncm.


### Straight Anatomic Transfer Abutment NP 3.5

H	11.5	13.0	15.0
L	1.5	3.0	4.5
Ø 4.0 mm			
	<b>TA-NB-NP15</b>	<b>TA-NB-NP30</b>	<b>TA-NB-NP45</b>





### Straight Anatomic Transfer Abutment RP 4.3

H	11.5	13.0	15.0
L	1.5	3.0	4.5
Ø 4.7 mm			
	<b>TA-NB-RP15</b>	<b>TA-NB-RP30</b>	<b>TA-NB-RP45</b>








### Included with abutments (available separately)

Type	H (mm)	Ø (mm)	Ref:
 Transfer plastic cap	11.0	4.75	<b>SPUTO</b>








**Snap-On Transfer Angulated Abutment 15°/25° NP 3.5**

°	15°		25°	
H	1.5	3.0	1.5	3.0
L	10.0	12.0	10.0	12.0
Ø D				
	TAP-NB-NP1515M    TAP-NB-NP1530M    TAP-NB-NP2515M    TAP-NB-NP2530M			





**Snap-On Transfer Angulated Abutment 15°/25° RP 4.3**

°	15°		25°	
H	1.5	3.0	1.5	3.0
L	10.0	12.0	10.0	12.0
Ø D				
	TAP-NB-RP1515M    TAP-NB-RP1530M    TAP-NB-RP2515M    TAP-NB-RP2530M			



**Included with abutments (available separately)**

Type	H (mm)	Ø (mm)	Ref:
 Transfer plastic cap	11.0	4.75	<b>SPUTO</b>




# Temporary Restoration

Material: Peek (Polyether ether ketone). Recommended torque: 20 Ncm.


## Straight Anatomic Peek Abutment NP 3.5

H	11.5	12.5	13.5	14.5
L	1.0	2.0	3.0	4.0
Ø 4.75 mm				
	<b>SPSA1-NB-NP</b>	<b>SPSA2-NB-NP</b>	<b>SPSA3-NB-NP</b>	<b>SPSA4-NB-NP</b>




## Straight Anatomic Peek Abutment RP 4.3

H	11.5	12.5	13.5	14.5
L	1.0	2.0	3.0	4.0
Ø 4.75 mm				
	<b>SPSA1-NB-RP</b>	<b>SPSA2-NB-RP</b>	<b>SPSA3-NB-RP</b>	<b>SPSA4-NB-RP</b>




## Angulated Anatomic Peek Abutment 15° NP 3.5

H	11.5	13.5	14.5
L	1.5	3.0	4.5
Ø 3.6 mm			
	<b>SPAA15-1-NB-NP</b>	<b>SPAA15-2-NB-NP</b>	<b>SPAA15-3-NB-NP</b>



### Angulated Anatomic Peek Abutment 15° RP 4.3

H	11.5	13.5	14.5
L	1.5	3.0	4.5
Ø 3.8 mm			
	<b>SPAA15-1-NB-RP</b>	<b>SPAA15-2-NB-RP</b>	<b>SPAA15-3-NB-RP</b>




## Cemented Restoration

Material: Titanium (Ti6Al4V ELI). Recommendation: Hand-tighten using a 1.25 mm hex driver and then use a ratchet or motor mount with a torque of 30 Ncm.


### Straight Shoulder Abutment NP 3.5

H	11.0	12.0	13.0
L	1.0	2.0	3.0
Ø 3.6 mm			
	<b>SSAC-1NP</b>	<b>SSAC-2NP</b>	<b>SSAC-3NP</b>



### Straight Shoulder Abutment RP 4.3

H	11.0	12.0	13.0
L	1.0	2.0	3.0
Ø 4.0 mm			
	<b>SSAC-1RP</b>	<b>SSAC-2RP</b>	<b>SSAC-3RP</b>






**Straight Abutment NP 3.5**

H	10.5	14.5
L	9.0	13.0
Ø 3.6 mm		
	<b>SSAC-9NP</b>	<b>SSAC-13NP</b>

**Straight Abutment RP 4.3**

H	10.5	14.5
L	9.0	13.0
Ø 4.0 mm		
	<b>SSAC-9RP</b>	<b>SSAC-13RP</b>





**Angled Abutment NP 3.5**

H	12.5	12.5
L	9.0	9.0
°	15°	25°
Ø 3.6 mm		
	<b>SCAA-NP</b>	<b>SCA A25-NP</b>


**Angled Abutment RP 4.3**

H	12.5	12.5
L	9.0	9.0
°	15°	25°
Ø 4.0 mm		
	<b>SCAA-RP</b>	<b>SCA A25-RP</b>







**Angulated Anatomic Abutment 15° NP 3.5**

H	11.5	13.5	14.5
L	1.5	3.0	4.5
Ø 3.6 mm			
	<b>TA-NB-NP1515</b>	<b>TA-NB-NP1530</b>	<b>TA-NB-NP1545</b>







**Angulated Anatomic Abutment 15° RP 4.3**

H	11.5	13.5	14.5
L	1.5	3.0	4.5
Ø 3.8 mm			
	<b>TA-NB-RP1515</b>	<b>TA-NB-RP1530</b>	<b>TA-NB-RP1545</b>







**Angulated Anatomic Abutment 25° NP 3.5**

H	11.5	13.5	14.5
L	1.5	3.0	4.5
Ø 3.6 mm			
	<b>TA-NB-NP2515</b>	<b>TA-NB-NP2530</b>	<b>TA-NB-NP2545</b>



**Angulated Anatomic Abutment 25° RP 4.3**

H	11.5	13.5	14.5
L	1.5	3.0	4.5
Ø 3.8 mm			
	<b>TA-NB-RP2515</b>	<b>TA-NB-RP2530</b>	<b>TA-NB-RP2545</b>



Satisfaction guaranteed  
with every *dip*.




# Zirconia Restoration

Material: Zirconium dioxide (ZrO<sub>2</sub>) / Titanium Grade 5 (Ti-6AL-4V ELI) base  
 Recommended torque: 30 Ncm.

## Straight Anatomic Zirconia Abutment NP 3.5

L	1.0	2.0	3.0	4.0
Ø 3.6 mm				
	<b>SZSA1-NB-NP</b>	<b>SZSA2-NB-NP</b>	<b>SZSA3-NB-NP</b>	<b>SZSA4-NB-NP</b>




## Straight Anatomic Zirconia Abutment RP 4.3

L	1.0	2.0	3.0	4.0
Ø 4.0 mm				
	<b>SZSA1-NB-RP</b>	<b>SZSA 2-NB-RP</b>	<b>SZSA3-NB-RP</b>	<b>SZSA4-NB-RP</b>


## Angulated Anatomic Zirconia Abutment 15° NP 3.5

L	1.5	2.0	3.0
Ø 3.6 mm			
	<b>SZAA15-NB-NP</b>	<b>SZAA15-2-NB-NP</b>	<b>SZAA15-3-NB-NP</b>



### Angulated Anatomic Zirconia Abutment 15° RP 4.3

L	1.5	2.0	3.0
Ø 3.8 mm			
	<b>SZAA15-NB-RP</b>	<b>SZAA15-2-NB-RP</b>	<b>SZAA15-3-NB-RP</b>



## Custom Restoration


Material: Acetalpolymer and optional metal base (Titanium/Chrome Cobalt).  
 Recommended torque: 30 Ncm.

### Plastic Abutment NP 3.5

H	11.0	11.5
Type	HEX	non-Hex
Ø 4.5 mm		
	<b>SACC-NP</b>	<b>NACC-NP</b>

### Plastic Abutment RP 4.3

H	10.5	11.5
Type	HEX	non-Hex
Ø 4.5 mm		
	<b>SACC-RP</b>	<b>NACC-RP</b>




### UCLA CoCr Castable NP 3.5

H	13.5	13.5
Type	HEX	non-Hex
Ø 4.5 mm		
	<b>CAMC-NP</b>	<b>NAMC-NP</b>

### UCLA CoCr Castable RP 4.3

H	13.5	13.5
Type	HEX	non-Hex
Ø 4.5 mm		
	<b>CAMC-RP</b>	<b>NAMC-RP</b>



# CAD/CAM Digital Solutions



**CAD-CAM Libraries Software** contain all relevant Cad/Cam parts – Scan Bodies, Ti-Bases, Screws, Analogs and Pre-Milled Blanks. **dip** libraries enable the simple design to manufacture your restorations and support most popular implant platforms.


Products are supported by leading CAD/CAM systems: Exocad and 3Shape.

Recommendation: Hand-tighten using a 1.25 mm hex driver or a motor mount with a force of 30 Ncm.



Material: Titanium (Ti6Al4V ELI).


## ScanPost Body implant-level NP 3.5 & RP 4.3

H	12.7	H	12.7	
Ø 3.0 mm	Conical Platform NP		Conical Platform RP	
				
SP-DSNP		SP-DSRP		





## Digital Analog for 3D Printing – Implant Level NP 3.5 & RP 4.3



L	10.0	L	10.0	
Ø 3.5 mm	Conical Platform NP		Conical Platform RP	
				
SIA-3D-NP		SIA-3D-RP		



## Ti-Base Abutment NP 3.5

## Ti-Base Abutment RP 4.3

L	0.5	0.5	L	0.5	0.5
Ø 3.6 mm	Hex	Non-Hex	Ø 3.75 mm	Hex	Non-Hex
					
TB-DSC1-NP		TB-DSCR-NP	TB-DSC1-RP		TB-DSCR-RP



# *Multi-Unit & Screw-Retained*





Conical Connection | Active Hex




# dip Premium Conical Connection MUA





Recommended torque: 35 Ncm for abutment, 20 Ncm for prosthetic parts.  
Material: Titanium (Ti6Al4V ELI).


## Conical Straight Multi-Unit Abutment NP 3.5

H	9.0	10.0	11.0	12.0
L	1.0	2.0	3.0	4.0
Ø 4.7 mm				
	<b>MUA-NB-NP15</b>	<b>MUA-NB-NP25</b>	<b>MUA-NB-NP35</b>	<b>MUA-NB-NP45</b>















## Conical Straight Multi-Unit Abutment RP 4.3

H	9.0	10.0	11.0	12.0
L	1.0	2.0	3.0	4.0
Ø 4.7 mm				
	<b>MUA-NB-RP15</b>	<b>MUA-NB-RP25</b>	<b>MUA-NB-RP35</b>	<b>MUA-NB-RP45</b>



## Angulated Conical Connection Multi-Unit 3.5 NP & 4.3 RP

°	17°		30°		45°
L	1.0	2.0	1.0	2.0	1.0
NP					
Ref:	<b>MUA-NB-NP1710</b>	<b>MUA-NB-NP1720</b>	<b>MUA-NB-NP3010</b>	<b>MUA-NB-NP3020</b>	<b>MUA-NB-NP4510</b>
RP					
Ref:	<b>MUA-NB-RP1710</b>	<b>MUA-NB-RP1720</b>	<b>MUA-NB-RP3010</b>	<b>MUA-NB-RP3020</b>	<b>MUA-NB-RP4510</b>





## dip Conical Connection MUA Kits NP 3.5

**Kit contents:** Straight/Angled MUA; Temporary titanium Sleeve; Castable Sleeve; Open Tray Transfer (with screw); Closed Tray Transfer; MUA Analog; Healing Cap; 2 fixation screws; Position Holder (for angled MUA).

### Premium Straight Conical MUA Kit NP 3.5

L (mm)	H (mm)	Ref:
1.0	9.0	PMUA-NB-NP15
2.0	10.0	PMUA-NB-NP25
3.0	11.0	PMUA-NB-NP35
4.0	12.0	PMUA-NB-NP45



### 17° Premium Angulated Conical MUA Kit NP 3.5

L (mm)	H (mm)	Ref:
1.0	6.0	PMUA-NB-NP1710
2.0	7.0	PMUA-NB-NP1720



### 30° Premium Angulated Conical MUA Kit NP 3.5

L (mm)	H (mm)	Ref:
1.0	7.0	PMUA-NB-NP3010
2.0	8.0	PMUA-NB-NP3020



## dip Conical Connection MUA Kits RP 4.3

**Kit contents:** Straight/Angled MUA; Temporary titanium Sleeve; Castable Sleeve; Open Tray Transfer (with screw); Closed Tray Transfer; MUA Analog; Healing Cap; 2 fixation screws; Position Holder (for angled MUA).

### Premium Straight Conical MUA Kit RP 4.3

L (mm)	H (mm)	Ref:
1.0	9.0	<b>PMUA-NB-RP15</b>
2.0	10.0	<b>PMUA-NB-RP25</b>
3.0	11.0	<b>PMUA-NB-RP35</b>
4.0	12.0	<b>P M UA-N B-R P4 5</b>



### 17° Premium Angulated Conical MUA Kit RP 4.3

L (mm)	H (mm)	Ref:
1.0	6.0	<b>PMUA-NB-RP1710</b>
2.0	7.0	<b>PMUA-NB-RP1720</b>



### 30° Premium Angulated Conical MUA Kit RP 4.3

L (mm)	H (mm)	Ref:
1.0	7.0	<b>PMUA-NB-RP3010</b>
2.0	8.0	<b>PMUA-NB-RP3020</b>



**Premium Conical Connection MUA Accessories Information Table**

Type	Product	Ø (mm)	L (mm)	H (mm)	Ref:
	Premium Transfer Screw	2.0	11.0	14.4	<b>SSF TMU-K</b>
	Open Tray Transfer	4.8	8.5	10.7	<b>STFMU-K</b>
	Titanium Analog	4.8	7.0	13.5	<b>SAFMU-K</b>
	Healing Cap	4.9	2.35	5.0	<b>SHCFMU-K</b>
	Titanium Sleeve Abutment	4.8	10.0	12.0	<b>SSTFMU-K</b>
	Castable Sleeve Abutment	4.8	10.0	12.0	<b>SSPFMU-K</b>
	Snap-on Closed Transfer	4.75	5.0	7.2	<b>STFMU-KC</b>
	Scan Post Abutment	5.0	3.5	10.0	<b>SP-DS3</b>
	Ti-Base for Multi-Unit	5.0	4.6	5.0	<b>T B-DS 4</b>
	Fixation Long Screws	2.1	5.9	8.3	<b>LSFMU-K</b>
	Fixation Short Screws	2.0	2.6	3.9	<b>SSFMU-K</b>
	Metal Position Holder	1.6	12.2	25.2	<b>MUD-M1.6</b>

\* Abutments are supplied with fixation screw (long screw).

# *Overdentures Restoration*






Conical Connection | Active Hex




## dip Overlock Attachments






Material: Titanium (Ti6Al4V ELI). Recommended torque: 30 Ncm.


### Straight Overlock Attachments Conical Connection NP 3.5

H	9.0	10.0	11.0	12.0	13.0
L	1.0	2.0	3.0	4.0	5.0
Ø 3.6 mm					
	<b>LOC-NB-NP10</b>	<b>LOC-NB-NP20</b>	<b>LOC-NB-NP30</b>	<b>LOC-NB-NP40</b>	<b>LOC-NB-NP50</b>





### Straight Overlock Attachments Conical Connection RP 4.3







H	8.7	9.7	10.7	11.7	12.7
L	1.0	2.0	3.0	4.0	5.0
Ø 3.75 mm					
	<b>LOC-NB-RP10</b>	<b>LOC-NB-RP20</b>	<b>LOC-NB-RP30</b>	<b>LOC-NB-RP40</b>	<b>LOC-NB-RP50</b>




### Overlock Attachments Compatible Tools & Parts







Product	H (mm)	Ø (mm)	Ref:
 Analog	10.3	3.75	<b>LOC-AN</b>
 Impression Transfer	11.3	4.75	<b>LOCW-PU</b>


### Angulated Overlock Attachments Conical Connection NP 3.5

L	1.0	2.0	3.0
Angle 18°			
	Ref: <b>LOC-NB-NP1810</b>	<b>LOC-NB-NP1820</b>	<b>LOC-NB-NP1830</b>
Angle 30°			
	Ref: <b>LOC-NB-NP3010</b>	<b>LOC-NB-NP3020</b>	<b>LOC-NB-NP3030</b>




### Angulated Overlock Attachments Conical Connection RP 4.3

L	1.0	2.0	3.0
Angle 18°			
	Ref: <b>LOC-NB-RP1810</b>	<b>LOC-NB-RP1820</b>	<b>LOC-NB-RP1830</b>
Angle 30°			
	Ref: <b>LOC-NB-RP3010</b>	<b>LOC-NB-RP3020</b>	<b>LOC-NB-RP3030</b>










### Overlock Attachments Conical Connection Compatible Tools & Parts

Product	Type	Ref:
	Universal Insertion & Extraction Tool	<b>DFL</b>

**Overlock Attachments Inserts Information Table**

**Ref:**

Product	Type	Retention	Standard	With central pin
	Black	Lab Cap (is available on request)	0 kg	<b>CN090</b> <b>CN100</b>
	Yellow	Extra-soft retention	0.6 kg / 1.3 lbs	<b>CN088</b> <b>CN098</b>
	Pink	Soft retention	1.2 kg / 2.6 lbs	<b>CN087</b> <b>CN097</b>
	Clear	Standard retention	1.8 kg / 4.0 lbs	<b>CN086</b> <b>CN096</b>
	Violet	Strong retention	2.5 kg / 5.5 lbs	<b>CN089</b> <b>CN099</b>
	Silver	Metal Housing (height 2.0 mm)	Ø 5.6 mm	<b>MH-LOCW</b>
	Pink	Protective Disc	Ø 14.0 mm/ internal Ø 2.9 mm	<b>PD</b>

## dip Overlock Attachments Kits NP 3.5

The **Full kit** is a ready-to-use solution including all the pieces required during the procedure: abutment, four retention inserts, housing, and isolation ring.

### Straight Overlock Attachments Kit NP 3.5

L (mm)	H (mm)	Ref:
1.0	9.0	<b>PLOC-NB-NP10</b>
2.0	10.0	<b>PLOC-NB-NP20</b>
3.0	11.0	<b>PLOC-NB-NP30</b>
4.0	12.0	<b>PLOC-NB-NP40</b>
5.0	13.0	<b>PLOC-NB-NP50</b>



### 18° Angulated Overlock Attachments Kit NP 3.5

L (mm)	H (mm)	Ref:
1.0	6.0	<b>PLOC-NB-NP1810</b>
2.0	7.0	<b>PLOC-NB-NP1820</b>
3.0	8.0	<b>PLOC-NB-NP1830</b>
4.0	9.0	<b>PLOC-NB-NP1840</b>



### 30° Angulated Overlock Attachments Kit NP 3.5

L (mm)	H (mm)	Ref:
1.0	6.0	<b>PLOC-NB-NP3010</b>
2.0	7.0	<b>PLOC-NB-NP3020</b>
3.0	8.0	<b>PLOC-NB-NP3030</b>
4.0	9.0	<b>PLOC-NB-NP3040</b>





## dip Overlock Attachments Kits RP 4.3

The **Full kit** is a ready-to-use solution including all the pieces required during the procedure: abutment, four retention inserts, housing, and isolation ring.

### Straight Overlock Attachments Kit RP 4.3

L (mm)	H (mm)	Ref:
1.0	9.0	<b>PLOC-NB-RP10</b>
2.0	10.0	<b>PLOC-NB-RP20</b>
3.0	11.0	<b>PLOC-NB-RP30</b>
4.0	12.0	<b>PLOC-NB-RP40</b>
5.0	13.0	<b>PLOC-NB-RP50</b>



### 18° Angulated Overlock Attachments Kit RP 4.3

L (mm)	H (mm)	Ref:
1.0	6.0	<b>PLOC-NB-RP1810</b>
2.0	7.0	<b>PLOC-NB-RP1820</b>
3.0	8.0	<b>PLOC-NB-RP1830</b>
4.0	9.0	<b>PLOC-NB-RP1840</b>



### 30° Angulated Overlock Attachments Kit RP 4.3







L (mm)	H (mm)	Ref:
1.0	6.0	<b>PLOC-NB-RP3010</b>
2.0	7.0	<b>PLOC-NB-RP3020</b>
3.0	8.0	<b>PLOC-NB-RP3030</b>
4.0	9.0	<b>PLOC-NB-RP3040</b>




# dip Conical Connection Ball Attachment







Material: Titanium (Ti6Al4V ELI). Recommended torque: 30 Ncm.


## Straight Ball Attachment Conical Connection NP 3.5

H	9.5	10.5	11.5	12.5	13.5	14.5
L	1.0	2.0	3.0	4.0	5.0	6.0
Ø 3.5 mm						
	<b>BAC-1-NP</b>	<b>BAC-2-NP</b>	<b>BAC-3-NP</b>	<b>BAC-4-NP</b>	<b>BAC-5-NP</b>	<b>BAC-6-NP</b>





## Straight Ball Attachment Conical Connection RP 4.3







H	9.5	10.5	11.5	12.5	13.5	14.5
L	1.0	2.0	3.0	4.0	5.0	6.0
Ø 5.0 mm						
	<b>BAC-1-RP</b>	<b>BAC-2-RP</b>	<b>BAC-3-RP</b>	<b>BAC-4-RP</b>	<b>BAC-5-RP</b>	<b>BAC-6-RP</b>




## Ball Attachment Conical Connection Compatible Tools & Parts

Product	H (mm)	Ø (mm)	Ref:
 Analog	15.0	3.75	<b>SBA370</b>
 Impression Transfer	5.6	4.5	<b>BAT-PU</b>

**CC Ball Attachment Inserts Information Table**

Product	Type	Retention	Ref:
 Black	Lab Cap (is available on request)	0 kg	<b>CN027</b>
 Yellow	Extra-soft Cap	0.5 kg / 1.1 lbs	<b>CN003</b>
 Pink	Soft Cap	0.9 kg / 2.0 lbs	<b>CN001</b>
 Clear	Standard Cap	1.3 kg / 2.9 lbs	<b>CN002</b>
 Silver	Metal Housing (height 3.2 mm)	Ø 4.6 mm	<b>MH-BAT</b>
 Clear	Protective Disc	Ø 14.0 mm/ internal Ø 1.6 mm	<b>DP</b>

**Ball Attachment CC Compatible tools & parts**

Product	Type	Ref:
	Insertion & Extraction Tool	<b>485IC</b>

# Conical Connection Ball Attachment Kit

The **Full kit** is a ready-to-use solution including all the pieces required during the procedure: abutment, four retention inserts, housing, and isolation ring.

## Ball Attachment Straight Kit NP 3.5

L (mm)	H (mm)	Ref:
1.0	9.5	<b>PBAC-1-NP</b>
2.0	10.5	<b>PBAC-2-NP</b>
3.0	11.5	<b>PBAC-3-NP</b>
4.0	12.5	<b>PBAC-4-NP</b>
5.0	13.5	<b>PBAC-5-NP</b>
6.0	14.5	<b>PBAC-6-NP</b>



## Ball Attachment Straight Kit RP 4.3

L (mm)	H (mm)	Ref:
1.0	9.5	<b>PBAC-1-RP</b>
2.0	10.5	<b>PBAC-2-RP</b>
3.0	11.5	<b>PBAC-3-RP</b>
4.0	12.5	<b>PBAC-4-RP</b>
5.0	13.5	<b>PBAC-5-RP</b>
6.0	14.5	<b>PBAC-6-RP</b>



Smile at strangers  
**and you just might  
change a life.**

*Steve Maraboli*

“



*Thank you.*

