



Elevate your space with our FSC certified cherry paneling, a sustainable and exquisite choice for your interior design. Crafted from responsibly sourced wood, this premium paneling showcases the natural beauty of cherry while ensuring environmental responsibility. Bring warmth and elegance to your surroundings with this eco-friendly and timeless design solution..

Dimensions and Profile	Options- Natural clear finish only
<p>Thickness 3/8"</p> <p>Width 5"</p> <p>Lengths 24" - 60"</p> <p>Precision Tongue & Groove</p>	



FSC certification ensures products come from responsibly managed forests that provide environmental, social, and economic benefits.



All finishes are Green Gold Certified for indoor air quality. Plant based & commercially durable.



Meets TSCA Title VI compliance for EPA formaldehyde Emissions.

Manufacturer	WD Walls PO Box 2222 Lake Oswego, Oregon 97035 Sales@WDwalls.com
Specify Product Name	FSC Certified American Cherry
Price per Square Foot	\$12.95
Dimensions	Thickness 3/8" Width 3-3/4" Lengths 24"-60"
Milling Profile	Precision milled tongue and groove. (end cut by installer as needed)
Finish	Greenguard Gold, VOC free, plant based hard oil finish. CARB II compliant.
Species	FSC Certified American Cherry
Character	Unlimited grain combinations; heartwood & sapwood, insect pinholes; open knots. This wood is very photo sensitive and will age to a gorgeous, dark color if left in the sun.
Grade	Character grade. We recommend ordering 9-12% additional material for onsite grading, defecting, trimming & other installation factors to achieve design intent.
Hardness	995 using Janka Ball test (ASTM D1037-96A). Natural wood products have no minimum hardness specifications since individual plank values vary depending on cell structure & wood grain.
Fire Rating	Class C. OPTION: add Class A fire retardant finish for \$2.95/ SF
Certified Sustainable	FSC® Mixed Credit (SA-COC-002372-220). Choosing this product ensures wood comes from responsibly managed forests that provide environmental, social, and economic benefits. Greenguard Gold certified finishes for indoor air quality.
Made in the USA	Sourced on the West Coast and manufactured in Portland Oregon
Shipping	Material is bundle packaged palletized for transportation. 1.05 LB per SF weight
Installation	Store, handle and install per Architectural Woodwork Standards (AWS) 2nd Edition (2014), Section 8: Wall/Ceiling Surfacing and Partitions, available at www.awinet.org . Typical installation: paneling is mechanically fastened to a backing sheet (drywall or plywood) using nails or fasteners located in the tongue, concealed from exposed surfaces. Some pieces are to be square cut by installer at the time of installation for starting or ending rows. Paneling can also be securely glued with adhesive and/or face nailed where essential.