



WD Walls is located in the heart of doug fir country on the West Coast. This gives us access to the biggest and best FSC Certified stock and the deepest inventory of consistent paneling material. Our doug fir is in a class by itself – it tells its own story when you see it. Its rich character will add a warm sense of heritage to your design.

| Dimensions and Profile | Options- Natural clear finish only |
|---|---|
| <p>Thickness 3/8" Width 3-3/4" Lengths 24" - 60"</p> <p>Precision Tongue & Groove</p> |  |



FSC certification ensures products come from responsibly managed forests that provide environmental, social, and economic benefits.



All finishes are Green Gold Certified for indoor air quality. Plant based & commercially durable.



Meets TSCA Title VI compliance For EPA formaldehyde Emissions.

| | |
|-----------------------|--|
| Manufacturer | WD Walls PO Box 2222 Lake Oswego, Oregon 97035 Sales@WDwalls.com |
| Specify Product Name | FSC Certified Douglas Fir |
| Price per Square Foot | \$12.95 |
| Dimensions | Thickness 3/8" Width 3-3/4" Lengths 24"-60" |
| Milling Profile | Precision milled tongue and groove. (end cut by installer as needed) |
| Finish | Greenguard Gold, VOC free, plant based hard oil finish. CARB II compliant. |
| Species | FSC Certified Douglas Fir |
| Character | Unlimited grain combinations; heartwood & sapwood, insect pinholes; open knots. This wood is very photo sensitive and will age to a gorgeous color if left in the sun. |
| Grade | Character grade. We recommend ordering 9-12% additional material for onsite grading, defecting, trimming & other installation factors to achieve design intent. |
| Hardness | 620 using Janka Ball test (ASTM D1037-96A). Natural wood products have no minimum hardness specifications since individual plank values vary depending on cell structure & wood grain. |
| Fire Rating | Class C. OPTION: add Class A fire retardant finish for \$2.95/ SF |
| Certified Sustainable | FSC® Mixed Credit (SA-COC-002372-220). Choosing this product ensures wood comes from responsibly managed forests that provide environmental, social, and economic benefits. Greenguard Gold certified finishes for indoor air quality. |
| Made in the USA | Sourced on the West Coast and manufactured in Portland Oregon |
| Shipping | Material is bundle packaged palletized for transportation. 1.1 LB per SF weight |
| Installation | Store, handle and install per Architectural Woodwork Standards (AWS) 2nd Edition (2014), Section 8: Wall/Ceiling Surfacing and Partitions, available at www.awinet.org . Typical installation: paneling is mechanically fastened to a backing sheet (drywall or plywood) using nails or fasteners located in the tongue, concealed from exposed surfaces. Some pieces are to be square cut by installer at the time of installation for starting or ending rows. Paneling can also be securely glued with adhesive and/or face nailed where essential. |