




One of our flagship products, Fishtail Oak wood wall cladding, is meticulously crafted from reclaimed wood salvaged from international shipping operations. This unique material boasts a striking aesthetic reminiscent of the famed Post Oak from Texas, distinguished by its prominent figuring and rich character.

Dimensions and Profile	Color Options
<p>Thickness 3/8"</p> <p>Width 1.75"</p> <p>Lengths 24" - 60"</p> <p>Precision Tongue & Groove</p>	



FSC Certified Recycled 100%
 Choosing this product saves trees
 And reduces the demand for new
 Lumber.



All finishes are Green Gold
 Certified for indoor air quality.
 Plant based & commercially durable.



Meets TSCA Title VI compliance
 For EPA formaldehyde
 Emissions.

Manufacturer	WD Walls PO Box 2222 Lake Oswego, Oregon 97035 Sales@WDwalls.com
Specify Product Name	Fishtail Oak
Price per Square Foot	\$14.95
Dimensions	Thickness 3/8" Width 1.75" Lengths 24"-60"
Milling Profile	Precision Tongue and Groove. (end cut by installer as needed)
Finish	Commercial Grade, Plant Based, Zero VOC Hard Oil Wax
Species	FSC Certified Reclaimed Oak (Quercus)
Character	Unlimited grain combinations; heartwood & sapwood, insect pinholes; filled knots.
Grade	Weathered original board faces contain slightly uneven surfaces (over/under wood), saw marks, fastener marks, indentations, oxide staining & discoloration from prior use; unlimited grain combinations; heartwood & sapwood; nail & pinholes; knots, including some that may be open/missing or extend to plank edge; & non-structural checks & cracks. We recommend ordering 7-10% additional material for onsite grading and trimming for installation.
Hardness	1150 using Janka Ball test (ASTM D1037-96A). Natural wood products have no minimum hardness specifications since individual plank values vary depending on cell structure & wood grain.
Fire Rating	Class C. OPTION: add Class A fire retardant finish for \$2.95/ SF
Certified Sustainable	FSC® Recycled 100% (SA-COC-002372-220). Post-consumer reclaimed. Choosing this product saves trees & reduces demand for new lumber. Greenguard Gold certified finishes for indoor air quality.
Made in the USA	Reclaimed on the West Coast and manufactured in Portland Oregon
Shipping	Material is bundle packaged palletized for transportation. 1.1 LB per SF weight
Installation	Store, handle and install per Architectural Woodwork Standards (AWS) 2nd Edition (2014), Section 8: Wall/Ceiling Surfacing and Partitions, available at www.awinet.org . Typical installation: paneling is mechanically fastened to a backing sheet (drywall or plywood) using nails or fasteners located in the tongue, concealed from exposed surfaces. Some pieces are to be square cut by installer at the time of installation for starting or ending rows. Paneling can also be securely glued with adhesive and/or face nailed were essential.