



Robert Frost’s musing verse, “good fences make good neighbors” was the inspiration for our most popular paneling line. Our founders’ pet project to keep gorgeous fence boards from going to the landfill has blossomed into a massive recycling operation across the West. Our weathered redwood has been exposed to years of sun, rain, and snow to create a patina that is unmistakable and genuine.

Dimensions and Profile	Color Options		
<p>Thickness 3/8” Width 5” Lengths 24”- 60”</p> <p>Precision Tongue & Groove</p>			
	Blanco	Cape Cod	Brushed
			
	Flambe	Driftwood	Natural



FSC Certified Recycled 100%
Choosing this product saves trees
And reduces the demand for new
Lumber.



All finishes are Green Gold
Certified for indoor air quality.
Plant based & commercially durable.



Meets TSCA Title VI compliance
For EPA formaldehyde
Emissions.

Manufacturer	WD Walls PO Box 2222 Lake Oswego, Oregon 97035 Sales@WDwalls.com
Specify Product Name	Good Neighbor-Brushed
Color Options also available	Brushed, Natural, Cape Cod, Blanco, Flambe and Driftwood
Price per Square Foot	Brushed \$12.95 Natural, Flambe and Driftwood \$13.95 Cape Cod and Blanco \$14.95
Dimensions	Thickness 3/8" Width 5" Lengths 24"-60"
Milling Profile	Precision Tongue and Groove. (end cut by installer as needed)
Finish	Brushed to remove some patina- No protective finish
Species	Redwood
Character	Unlimited grain combinations; heartwood & sapwood, insect pinholes; filled knots.
Grade	Weathered original board faces contain slightly uneven surfaces (over/under wood), saw marks, fastener marks, indentations, oxide staining & discoloration from prior use; unlimited grain combinations; heartwood & sapwood; nail & pinholes; knots, including some that may be open/missing or extend to plank edge; & non-structural checks & cracks. We recommend ordering 10-15% additional material for onsite grading and trimming for installation.
Hardness	450 using Janka Ball test (ASTM D1037-96A). Natural wood products have no minimum hardness specifications since individual plank values vary depending on cell structure & wood grain.
Fire Rating	Class C. OPTION: add Class A fire retardant finish for \$2.95/ SF
Certified Sustainable	FSC® Recycled 100% (SA-COC-002372-220). Post-consumer reclaimed. Choosing this product saves trees & reduces demand for new lumber. Greenguard Gold certified finishes for indoor air quality.
Made in the USA	Reclaimed on the West Coast and manufactured in Portland Oregon
Shipping	Material is bundle packaged palletized for transportation. 0.75 LB per SF weight
Installation	Store, handle and install per Architectural Woodwork Standards (AWS) 2nd Edition (2014), Section 8: Wall/Ceiling Surfacing and Partitions, available at www.awinet.org . Typical installation: paneling is mechanically fastened to a backing sheet (drywall or plywood) using nails or fasteners located in the tongue, concealed from exposed surfaces. Some pieces are to be square cut by installer at the time of installation for starting or ending rows. Paneling can also be securely glued with adhesive and/or face nailed where essential.