



Robert Frost's musing verse, "good fences make good neighbors" was the inspiration for our most popular paneling line. Our founders' pet project to keep gorgeous fence boards from going to the landfill has blossomed into a massive recycling operation across the West. Our weathered redwood has been exposed to years of sun, rain, and snow to create a patina that is unmistakable and genuine.

| Dimensions and Profile | Color Options | | |
|---|---|---|--|
| <p>Thickness 3/8" Width 5" Lengths 24" - 60"</p> <p>Precision Tongue & Groove</p> |  <p>Blanco</p> |  <p>Cape Cod</p> |  <p>Brushed</p> |
| |  <p>Flambe</p> |  <p>Driftwood</p> |  <p>Natural</p> |



FSC Certified Recycled 100%
Choosing this product saves trees
And reduces the demand for new
Lumber.



All finishes are Green Gold
Certified for indoor air quality.
Plant based & commercially durable.



Meets TSCA Title VI compliance
For EPA formaldehyde
Emissions.

| | |
|------------------------------|--|
| Manufacturer | WD Walls PO Box 2222 Lake Oswego, Oregon 97035 Sales@WDwalls.com |
| Specify Product Name | Good Neighbor-Flambe |
| Color Options also available | Brushed, Natural, Cape Cod, Blanco, Flambe and Driftwood |
| Price per Square Foot | Brushed \$12.95 Natural, Flambe and Driftwood \$13.95 Cape Cod and Blanco \$14.95 |
| Dimensions | Thickness 3/8" Width 5" Lengths 24"-60" |
| Milling Profile | Precision Tongue and Groove. (end cut by installer as needed) |
| Finish | Greenguard Gold, VOC free, plant based hard oil finish. CARB II compliant. |
| Species | Redwood |
| Character | Unlimited grain combinations; heartwood & sapwood, insect pinholes; filled knots. |
| Grade | Weathered original board faces contain slightly uneven surfaces (over/under wood), saw marks, fastener marks, indentations, oxide staining & discoloration from prior use; unlimited grain combinations; heartwood & sapwood; nail & pinholes; knots, including some that may be open/missing or extend to plank edge; & non-structural checks & cracks. We recommend ordering 10-15% additional material for onsite grading and trimming for installation. |
| Hardness | 450 using Janka Ball test (ASTM D1037-96A). Natural wood products have no minimum hardness specifications since individual plank values vary depending on cell structure & wood grain. |
| Fire Rating | Class C. OPTION: add Class A fire retardant finish for \$2.95/ SF |
| Certified Sustainable | FSC® Recycled 100% (SA-COC-002372-220). Post-consumer reclaimed. Choosing this product saves trees & reduces demand for new lumber. Greenguard Gold certified finishes for indoor air quality. |
| Made in the USA | Reclaimed on the West Coast and manufactured in Portland Oregon |
| Shipping | Material is bundle packaged palletized for transportation. 0.75 LB per SF weight |
| Installation | Store, handle and install per Architectural Woodwork Standards (AWS) 2nd Edition (2014), Section 8: Wall/Ceiling Surfacing and Partitions, available at www.awinet.org . Typical installation: paneling is mechanically fastened to a backing sheet (drywall or plywood) using nails or fasteners located in the tongue, concealed from exposed surfaces. Some pieces are to be square cut by installer at the time of installation for starting or ending rows. Paneling can also be securely glued with adhesive and/or face nailed where essential. |