Section 1 - Identification

Product Name: Hot Caustic (24000)

Gently Wash Products 4458 Legendary Drive Ste 210 #814 Destin. FL 32541 850-806-2416

Emergency Phone: 1-800-535-5053

Section 2 - Hazards Identification

GHS Ratings:

Corrosive to metals May be corrosive to metals Acute Tox. 4 Acute Toxicity - Oral Oral>300+<=2000mg/kg

Skin corrosion/irritation Destruction of dermal tissue: Exposure < 3 min. Observation

< 1 hour, visible necrosis in at least one animal

1 Serious eye damage: Irreversible damage 21 days after Serious eye damage/eye irritation

exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5

GHS Hazards

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

GHS Precautions

P234 Keep only in original container

P260 Do not breathe dust/fume/gas/mist/vapours/spray

P264 Wash hands thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P310 Immediately call a POISON CENTER or doctor/physician if you feel unwell after

exposure of this product

P321 Specific treatment (see First Aid below or label) P363 Wash contaminated clothing before reuse P390 Absorb spillage to prevent material damage

P301+P330+P331 IF SWALLOWED: Call a POISON CENTER or doctor/physician. Rinse mouth. Do

NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing

P405 Store locked up

P406 Store in a corrosive resistant/... container with a resistant inner liner

P501 Dispose of contents/container in conformance with State, Local, and Federal

regulations.

Signal Word: Danger



SDS for: Hot Caustic (24000) Page 1 of 6

Printed: 6/8/2022 at 1:23:42PM

Section 3 - Composition, Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Sodium Hydroxide	1310-73-2P	70.00%
Calcined soda	497-19-8	11.00%
Disodium oxosilanediolate	6834-92-0	3.00%
Sodium Nitrite	7632-0-0	2.00%

⁽¹⁾ The Exposure limits given are for Particulates Not Otherwise Classified

Section 4 - First Aid Measures

INHALATION: If inhalation of mists, vapors, or spray occurs and adverse effects result, remove to uncontaminated area. Evaluate ABC's (is Airway constricted, is Breathing occurring, and is blood Circulating) and treat symptomatically. GET MEDICAL ATTENTION IMMEDIATELY. There is no specific antidote, treat symptomatically.

EYE CONTACT: Immediately flush contaminated eyes with a directed stream of water for as long as possible. Remove contact lenses, if present and easy to do. Continue rinsing. GET MEDICAL ATTENTION IMMEDIATELY. Washing eyes within several seconds is essential to achieve maximum effectiveness.

SKIN CONTACT: Immediately flush contaminated areas with water. Remove contaminated clothing, jewelry, and shoes immediately. Wash contaminated areas with large amounts of water.

GET MEDICAL ATTENTION IMMEDIATELY. Thoroughly clean and dry contaminated clothing before reuse. Discard contaminated leather goods.

INGESTION: If swallowed, do not induce vomiting. For definite or probable ingestion, do not administer oral fluids. If vomiting occurs spontaneously, keep airway clear. Monitor airway. Volume resuscitation (IV fluids) and circulatory support (CPR) may be required. Never give anything by mouth to an unconscious or convulsive person. GET MEDICAL ATTENTION IMMEDIATELY.

Notes to Physician: Medical observation and assessment is recommended for all ingestions, all eye exposures, and symptomatic inhalation and dermal exposures. For symptomatic ingestion, do not administer oral fluids and consider investigation by endoscopy, X-ray, or CT scan. Esophageal perforation, airway compromise, hypotension, and shock are possible. For prolonged exposures and significant exposures, consider delayed injury to exposed tissues. There is no antidote. Treatment is supportive care. Follow normal parameters for airway, breathing, and circulation. Surgical intervention may be required.

Section 5 - Fire Fighting Measures

Flash Point: 537 C (F)

LEL: UEL:

Fire Hazard: Negligible fire hazard.

Flash point: Not flammable

Extinguishing Media: Use extinguishing agents appropriate for surrounding fire.

Sensitivity to Mechanical Impact: Not sensitive. Sensitivity to Static Discharge: Not sensitive. GHS:Physical

Hazards: - Corrosive to Metals

Hazardous Decomposition:

None Known

Fire Fighting: Move container from fire area if it can be done without risk. Cool containers with water. Avoid contact with skin.Do not apply water directly on this product. Heat is generated when mixed with water. Wear NIOSH

SDS for: Hot Caustic (24000)

Page 2 of 6

Section 6 - Accidental Release Measures

Personal Precautions: Do not get in eyes, on skin or on clothing. Avoid breathing mist, vapor, or spray. Do not ingest. Wear appropriate personal protective equipment recommended in Section 8 of the SDS.

Methods and Materials for Containment and Cleaning Up: In case of spill or leak, stop the leak as soon as possible, if safe to do so. Completely contain spilled materials with dikes, sandbags, etc. Shovel dry material into suitable container. Liquid material may be removed with a vacuum truck. Remaining material may be diluted with water and neutralized with dilute acid, then absorbed and collected. Flush spill area with water, if appropriate. **Environmental Precautions:** Keep out of water supplies and sewers. Do not flush into surface water or sanitary sewer system. This material is alkaline and may raise the pH of surface waters with low buffering capacity. Releases should be reported, if required, to appropriate agencies.

Section 7 - Handling & Storage

Handling Procedures: Avoid breathing vapor or mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Do not ingest. Do not eat, drink or smoke in areas where this material is used. Wear personal protective equipment as described in Exposure Controls/Personal Protection (Section 8) of the SDS. NEVER add water to product. When

mixing, slowly add to water to minimize heat generation and spattering.

Storage Conditions: Store and handle in accordance with all current regulations and standards. Keep container tightly closed and properly labeled. Do not store in aluminum container or use aluminum fittings or transfer lines, as flammable hydrogen gas may be generated. Keep separated from incompatible substances (see Section 10 of SDS).

Section 8 - Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Sodium Hydroxide 1310-73-2P	2 mg/m3 (PEL)	2 mg/m3 (ceiling)	10 mg/m3 IDLH
Calcined soda 497-19-8	Not Established	Not Established	Not Established
Disodium oxosilanediolate 6834-92-0	Not Established	Not Established	Not Established
Sodium Nitrite 7632-0-0	15 mg/m3 TWA (Total Dust) 5 mg/m3 TWA (Respirable fraction)	10 mg/m3 TWA (Inhalable fraction) 3 mg/m3 TWA (Respirable fraction)	Not Established

ENGINEERING CONTROLS:

Provide local exhaust ventilation where dust or mist may be generated. Ensure compliance with applicable exposure limits.

Respiratory Protection: An approved respirator with N95 (dust, fume, mist) cartridges may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure. If eye irritation occurs, a full face style mask should be used. A respiratory protection program that meets applicable regulatory requirements must be followed whenever workplace conditions

warrant use of a respirator.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear chemical safety goggles with a faceshield to protect against eye and skin contact when appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

SDS for: Hot Caustic (24000)

Page 3 of 6

Skin and Body Protection: Wear chemical resistant clothing and rubber boots when potential for contact with the material exists. Contaminated clothing should be removed, then discarded or laundered.

Hand Protection: Wear appropriate chemical resistant gloves

Protective Material Types: Natural rubber, Neoprene, Nitrile, Polyvinyl chloride (PVC), Tyvek, Tychem.

Respiratory Protection: A NIOSH approved respirator with N95 (dust, fume, mist) cartridges may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure. If eye irritation occurs, a full face style mask should be used. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

HYGIENE MEASURES: Handle in accordance with good industrial hygiene and safety practices. Wash hands and affected skin immediately after handling, before breaks, and at the end of the workday. When using do not eat or drink. When using do not smoke.

Section 9 - Physical & Chemical Properties

Boiling Range 320 to 1390 °C	Appearance Powder
Color White	

Section 10 - Stability & Reactivity

Reactivity/ Stability: Stable at normal temperatures and pressures.

Conditions to Avoid: Mixing with acid, or incompatible materials may cause splattering and release of large amounts of heat. Will react with some metals forming flammable hydrogen gas. Carbon monoxide gas may form upon contact with reducing sugars, food and beverage products in enclosed spaces.

STABLE

Incompatibilities:

Acids and halogenated compounds. Prolonged contact with aluminum, brass, bronze, copper, lead, tin, zinc, or other alkali sensitive metals or alloys. Releases heat when diluted in water.

This product is incompatible with amines, acids, organic materials, permanganates, cyanides, chlorates, iodides, sulfates, urea and ammonium compounds. Incompatible with aminoguanidine salts, butadiene, phthalic acid, phthalic anhydride, reductants, sodium amide, sodium disulfite, sodium thiocyanate, urea wood. Addition of Solid Nitrite to molten amide causes immediate gas evolution, followed by violent explosion. Mixture of sodium nitrite and sodium thiocyanate explodes on heating. Interaction of nitrites when heated with metal aminosulfates ('sulfamates') may become explosively violent owing to liberation of nitrogen & steam. Mixtures with ammonium sulfamate form ammonium nitrate which decomposes violently around 80 deg C. Violent explosion occurs if an ammonium salt is melted with nitrite salt. When sodium nitrite & thiosulfate mixture was heated to evaporate to dryness, violent explosion occurred. Solutions of potassium and sodium nitrite in liquid ammonia form disodium nitrite, which is very reactive & easily explosive. Lithium reacts with sodium nitrite to form lithium sodium hydronitrite, a compound which decomposes violently around 100-130 deg C.

None Known

Reactivity

Corrosive action on metals. Reacts with reducing agents. Reacts with alkali (lyes). Reacts with organic substances. Ammonia (NH3), fluorine, sulfur trioxide (SO3), phosphorus pentoxide (P2O5). Chemical stability No decomposition if used and stored according to specifications. Possibility of hazardous reactions. Reacts with metals forming hydrogen.

Reacts with alkali (lyes). Conditions to avoid To avoid thermal decomposition do not overheat. Incompatible materials: Alkalis, Metals, Organic materials.

Hazardous Decomposition:

Hazardous Decomposition Products: Toxic fumes of sodium oxides

SDS for: Hot Caustic (24000)

Page 4 of 6

Hazardous Polymerization: Will not occur

Upon heating, nitrogen oxides, and oxygen are released, which increases potential of fire. In contact with all acids, Sodium Nitrite decomposes to form nitrogen oxides.

None Known

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 634mg/kg Inhalation Toxicity LC50: 275mg/L

Component Toxicity

497-19-8 Calcined soda

Oral LD50: 2,300 mg/kg (Rat) Dermal LD50: 2,004 mg/kg (Rabbit)

6834-92-0 Disodium oxosilanediolate

Oral LD50: 1,251 mg/kg (RAT) Dermal LD50: 5,000 mg/kg (RAT)

ACUTE TOXICITY:

The severity of the tissue damage is a function of its concentration, the length of tissue contact time, and local tissue conditions. After exposure there may be a time delay before irritation and other effects occur. This material is a strong irritant and is corrosive to the skin, eyes, and mucous membranes. This material may cause severe burns and permanent damage to any tissue with which it comes into contact. Inhalation will cause severe irritation, possible burns with pulmonary edema, which may lead to pneumonitis. Skin contact with this material may cause severe irritation and corrosion of tissue. Repeated exposure may cause dermatitis. Eye contact can cause severe irritation, corrosion with possible corneal damage and blindness. Ingestion may cause irritation, corrosion/ulceration, nausea, and vomiting.

CARCINOGENICITY: This product is not classified as a carcinogen by NTP, IARC or OSHA.

Inhalation Skin Contact Eye Contact Ingestion

Eyes Skin Respiratory System

Effects of Overexposure

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

Section 12 - Ecological Information

ECOTOXICITY DATA:

Aquatic Toxicity: This material has exhibited moderate toxicity to aquatic organisms. Data provided are for sodium

hydroxide. Fish Toxicity:

LC50 Brook trout: 25 ppm/ 24 hr LC50 King salmon: 48 ppm Invertebrate Toxicity:

LC50 Daphnia magna: 100 ppm LC50 Shrimp: 33 - 100 ppm/48 hr LC50 Cockle: 330 - 1000 ppm/48 hr

FATE AND TRANSPORT:

BIODEGRADATION: No information available

PERSISTENCE: Soluble in water, persistence is unlikely based on information available. **BIOCONCENTRATION:** This material is not expected to bioconcentrate in oganisms.

ADDITIONAL ECOLOGICAL INFORMATION: This material has exhibited slight toxicity to terrestrial organisms.

Component Ecotoxicity

Section 13 - Disposal Considerations

SDS for: Hot Caustic (24000)

Page 5 of 6

Printed: 6/8/2022 at 1:23:43PM

Section 14 - Transportation Information

Proper Shipping Name Hazard Class Agency UN Number Packing Group DOTLQ Limited Quantity

DOT Corrosive Solid, basic, inorganic, n.o.s (Sodium UN3262 PGII 8

Hydroxide),

Section 15 - Regulatory Information

Country Regulation **All Components Listed**

EU Risk Phrases


Safety Phrase

Section 16 - Other Information

Hazardous Material Information System (HMIS)

HMIS & NFPA Hazard Rating HEALTH 3 **FLAMMABILITY** 0 * = Chronic Health Hazard 0 = INSIGNIFICANT PHYSICAL HAZARD 1 = SLIGHT PERSONAL PROTECTION Ε 2 = MODERATE 3 = HIGH

National Fire Protection Association (NFPA)



The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.

Reviewer Revision

Printed: 6/8/2022 at 1:23:43PM

Date Prepared: 6/8/2022

SDS for: Hot Caustic (24000) Page 6 of 6