

FALL PROTECTION

MILLER® ARC-RATED SHOCK-ABSORBING LANYARD

- Designed to protect workers from electric arc-flash and arc-blast exposure
 - Arc-rated Kevlar® webbing
 - Available with Kevlar® choke-off loop for a "metal-less" connection
 - Arc-Flash Standards: ASTM F887-05
 - Connectors' Gate Load Capacity: 3600 lbs.
 - Shock Absorber Type: Pack
 - CSA Minimum Mass: 120 lbs.
 - CSA Maximum Mass: 335 lbs.
- Certification(s): CSA Standard Z259.11

Honeywell
MILLER

SGT531



Model No.	Mfg. No.	Length'	No. of Legs	Harness Connection	Anchorage Connection	Price /Each
GREY						
SGT522	M1FSFC-ES6C	6	One	Locking Snap Hook	Scaffold Hook	
SGT506	M1FSFS-ES6C	6	One	Locking Snap Hook	Locking Snap Hook	
SGT531	M1WLFC-ES6C	6	One	Choke-Off Loop	Scaffold Hook	
SGT512	M1WLFS-ES4C	4	One	Choke-Off Loop	Locking Snap Hook	
SGT537	M1WLFS-ES5C	5	One	Choke-Off Loop	Locking Snap Hook	
SGT502	M1WLFS-ES6C	6	One	Choke-Off Loop	Locking Snap Hook	
SGT544	M2FSFC-ES6C	6	Two	Locking Snap Hook	Scaffold Hook	
SGT529	M2FSFS-ES6C	6	Two	Locking Snap Hook	Locking Snap Hook	
BLACK						
SGT533	M1FSFC-KS6C	6	One	Locking Snap Hook	Scaffold Hook	
SGT541	M1FSFS-KS4C	4	One	Locking Snap Hook	Locking Snap Hook	
SGT493	M1FSFS-KS6C	6	One	Locking Snap Hook	Locking Snap Hook	
SGT471	M2FSFS-KS6C	6	Two	Locking Snap Hook	Locking Snap Hook	

V-SERIES STANDARD LANYARDS

MSA

- The New V-Series shock absorbing lanyard line simplifies product selection by offering a concise line of standard lanyards that meet a wide range of customer needs
- Includes a clear, durable protective cover on the labels to increase service life, and allow for easy inspection
- Meets the new CSA Z259.11-17 standard for shock absorbing safety lanyards, with a current selection of standard (150-310 lbs.) and lightweight (100-230 lbs.) worker options

SGK246



Model No.	Mfg. No.	Number of Legs	Anchorage Connections	Length'	Price /Each
CSA (150-310 LBS.)					
SGK246	10188100	One	36C Small Snap Hook	6	
SGK956	10188102	Two	36C Small Snap Hook	6	
SGK957	10188103	One	Rebar Hook	6	
SGK958	10188101	Two	36L Large Snap Hook	6	
LIGHTWEIGHT CSA (100-230 LBS.)					
SGK959	10190397	One	36C Small Snap Hook	6	
SGK960	10190399	Two	36C Small Snap Hook	6	
SGK961	10190398	One	Rebar Hook	6	
SGK962	10190400	Two	36L Large Snap Hook	6	

V-SERIES TIE-BACK LANYARDS

- A new easy identifiable symbol system to indicate the type of lanyard
- 5000 pound gate strength in any direction allows the FPSK carabiner to be tied directly to the lanyard
- Unique carabiner body shape that helps avoid confusion with standard connectors not designed for tie-back applications
- Meets the new CSA Z259.11-17 standard for shock absorbing safety lanyards, with a current selection of standard (150-310 lbs.)

MSA



SGK963

Model No.	Mfg. No.	Number of Legs	Anchorage Connection	Length'	Price /Each
SGK963	10193943	One	Carabiner	6	
SGK964	10193944	Two	Carabiner	6	

REBEL™ WEB SELF-RETRACTING LIFELINES

- Self-locking hooks
- Great value with superior features
- Compact and lightweight
- Swivel carabiner anchorage connection
- Certified to CSA standard Z259.2.2

SEB349



3M

PROTECTA
Fall Protection

SAFETY

Model No.	Mfg. No.	Length'	Harness Connection	Lifeline	Price /Each
TYPE 1					
SDP278	3100406	6	Snap Hook	Web	
SDP279	3100407	6	Swivel Snap Hook	Web	
SEB349	3100429	10	Swivel Snap Hook	Web	
TYPE 2					
SEB350	3100435	20	Swivel Snap Hook	Web	

REBEL™ SELF RETRACTING LIFELINE

- Lifeline Material: Galvanized Cable
- Harness Connection: Snap Hook
- Anchorage Connection: Carabiner
- Certification(s): CSA Standard Z259.2.2
- Rugged and extremely lightweight thermoplastic housing
- Stackable housing design
- Built-in carrying handle
- Galvanized steel cable lifeline is abrasion resistant and extremely durable
- Internal energy absorption system
- Swiveling self-locking snap hook with impact indicator
- Reserve lifeline system
- Swiveling anchorage point
- Side lifeline exit with ergonomic handle
- High strength, corrosion resistant components
- Self-locking anchorage carabiner keeps the SRL securely attached to the anchorage device
- **SE5695**: Designed for the abusive leading edge applications, incorporating over-sized cable and an external energy absorption system that helps maintain lifeline integrity over abrasive edges



3M

PROTECTA
Fall Protection

SAFETY

Model No.	Mfg. No.	Length'	Thickness"	Price /Each
SE5695	3590541	20	7/32	
SE717	3590502	33	3/16	
SE718	3590552	50	3/16	