



ENGINEERED
FOR THE
OUTDOORS

CLADDING SPECIFICATION



RECYCLED MATERIALS
100% QUALITY INSPECTED

SPLINTER FREE
LOW MAINTENANCE

BRITISH DESIGN
FIRE-RESISTANT OPTIONS

ANTI-SLIP




SUBFRAME • DECKING • FENCING • **CLADDING**
GATES • BALUSTRADE • FIRE RATED OPTIONS

Scan here to
find out more



CLADDING SPECIFICATION

	A	B
		
		
	A	B
	HERITAGE	URBAN
Board Size	3.6m	3.6m
Board Width	208mm (180mm face when installed)	150mm (120mm face when installed)
Board Depth	20mm	21mm
Board Finish	Deep Embossed Wood Grain	Deep Embossed Wood Grain
Board Weight	11.16kg per board	6.84kg per board
Board Coverage	0.648sqm	0.45sqm
Available Colours	Grey, Coffee, Charcoal	Grey, Coffee, Charcoal
Material	FSC 100% WPC	FSC 100% WPC
Application	Domestic	Domestic
Water Absorption - EN 317:1993	0.20%	0.20%

	A	B	C
			
	A	B	C
FIXINGS AND ACCESSORIES			
A	Back powder coated aluminium starter strip for installation. 1m length		
B	Cladding batons. 50mm x 30mm x 3.6m FSC 100%		
C	L shape corner trim with sanded finish in Charcoal, Grey and Coffee. 50mm x 55mm x 3.6m FSC 100%		

COMPOSITE MIX

Approximately 90% recycled materials consisting of around 60% recycled wood fibres, 30% recycled plastic and 10% toxin free additives including colour and UV stabilisers.

GREY

COFFEE

CHARCOAL