Environmental / Chemical Processing Blowers

EN / CP 833

7.5 HP High Pressure Sealed Regenerative w/Explosion-Proof Motor

ROTRON®

FEATURES

- · Manufactured in the USA ISO 9001 and NAFTA compliant
- Maximum flow: 120/180 SCFM
- Maximum pressure: 200/195 IWG
- Maximum vacuum: 155/155 IWG
- Standard motor: 7.5 HP, explosion-proof
- Cast aluminum blower housing, impeller, cover & manifold; cast iron flanges (threaded); teflon® lip seal
- UL & CSA approved motor with permanently sealed ball bearings for explosive gas atmospheres Class I Group D minimum
- Sealed blower assembly
- · Quiet operation within OSHA standards

MOTOR OPTIONS

- International voltage & frequency (Hz)
- · Chemical duty, high efficiency, inverter duty or industry-specific designs
- · Various horsepowers for application-specific needs

BLOWER OPTIONS

- · Corrosion resistant surface treatments & sealing options
- · Remote drive (motorless) models
- · Slip-on or face flanges for application-specific needs

ACCESSORIES

- · Flowmeters reading in SCFM
- · Filters & moisture separators
- · Pressure gauges, vacuum gauges, & relief valves
- · Switches air flow, pressure, vacuum, or temperature
- · External mufflers for additional silencing
- Air knives (used on blow-off applications)
- · Variable frequency drive package



Blower Performance at Standard Conditions 60 Hz Air Flow Rate - m³/hour 68 102 136 170 204 238 272 306 340 374 0 34 300 750 250 625 200 500 of 150 375 है Inches 001 Water 250 50 125 0 20 40 100 120 140 160 180 200 Air Flow Rate - SCFM 100 Motor Winding 0 Temperature curves are based on standard model 100 **Blower Air** Temp Rise

This document is for informational purposes only and should not be considered as a binding description of the products or their performance in all applications. The performance data on this page depicts typical performance under controlled laboratory conditions. AMETEK is not responsible for blowers driven beyond factory specified speed, temperature, pressure, flow or without proper alignment. Actual performance will vary depending on the operating environment and application. AMETEK products are not designed for and should not be used in medical life support applications. AMETEK reserves the right to revise its products without notification. The above characteristics represent standard products. For product designed to meet specific applications, contact AMETEK Technical & Industrial Products Sales department.

