

3 Bag Housing

Multi Bag Filter Housing for industrial filtration requirements.

Industrial Size Multi-Bag (3 bag) Housing, 316L Stainless Steel. Uses #2 Size Standard Bags. Standard design pressure is 150 PSI max. and design, materials, and construction conform to CE and ASME code.

Features Include:

- 316L Stainless Steel Construction Electropolish Finish
- 2" Tri-Clamp Inlet and Outlet
- EPDM Food Grade O-rings
- 150 psi Maximum Working Pressure
- Stainless Steel Strainer Baskets and Internal Bag Hold Down Support
- Uses (3) #2 Size Filter Bags (7-1/16" Dia. x 32" L)



PRM PART #: BFHBFM3CTRI316LSSXV2

**** Options and Services ****

- Skid mounting, pre plumbed filter array
- Steel, Stainless Steel, or PVC Piping with Valves
- Custom Integration Into Existing Systems
- Replacement Bag Filters available in stock

NO.	ITEM	QTY.	MATERIAL	NOTES
1	LEGS	3	316 SS	
2	SHELL	1	316 SS	
3	SWING ARM MOUNT	1	316 SS	
4	INLET	1	316 SS	2" TRI-CLAMP
5	LID	1	316 SS	
6	SWING ARM	1	316 SS	
7	SWING ARM PORT	1	316 SS	
8	EXHAUST VENT	1	316 SS	2" TRI-CLAMP
9	SWING BOLTS	10	304 SS	M16
10	BRACKETS	10	316 SS	
11	OUTLET	1	316 SS	2" TRI-CLAMP

NOTES:

1. PRM FILTRATION IS ONLY A SUPPLIER OF THIS EQUIPMENT.
2. PRM IS NOT RESPONSIBLE FOR SPECIFYING THIS PRODUCT FOR THE APPLICATION.
3. BUYERS AND/OR USER SHOULD REQUIRE AN ENGINEER FOR ENSURING THAT THE PROPER EQUIPMENT IS INSTALLED FOR THE APPLICATION INCLUDING ALL PROPER SAFETY PRACTICES.
4. PRM IS NOT RESPONSIBLE FOR ANY DAMAGES TO PROPERTY AND/OR INJURY/DEATH RELATED TO IMPROPER INSTALLATION. FILTRATION EQUIPMENT INSTALLATIONS SHOULD ALWAYS INCLUDE ANCILLARY SAFETY DEVICES AND/OR OPERATIONAL PRACTICES. IT IS AGREED THAT PRM NOR ITS OWNERS HAVE LIABILITY WITH THE INSTALLATION AND OPERATION OF THESE OR OTHER PRODUCTS PURCHASED FROM PRM.
6. ALLOW UP TO $\frac{1}{4}$ " TOLERANCE ON ALL MEASUREMENTS.
7. MODEL LINK: <https://a360.co/43ZqfK1>

