

## #2 High Pressure Top Loading Bag Filter Housing



PRM provides top loading bag filter housings for high pressure applications in remediation and industrial filtration projects.

### Standard Features:

- 304 Stainless Steel Construction
- Trade Size # 2 Housing
- 2" Flanged Inlet and Outlet Connections  
- 150# Flange, 4 Bolt Pattern
- 100 GPM Flow Rate
- Viton® O-rings Standard
- 250 psi Maximum Working Pressure
- Stainless Steel Strainer Basket
- Adjustable Mounting Stand



### \*\* Options and Services \*\*

- Skid mounting, pre plumbed filter array
- Steel, Stainless Steel, or PVC Piping w/Valves
- Custom Integration Into Existing Systems
- Field Installation, Startup and Maintenance
- Replacement Bag Filters available in stock

888-TREAT-IT • [www.prmfiltration.com](http://www.prmfiltration.com) • [sales@prmfiltration.com](mailto:sales@prmfiltration.com)

NO.	ITEM	QTY	MATERIAL	NOTES
1	LEG	3	304 SS	ADJUSTABLE HEIGHT
2	OUTLET	1	304 SS	2" FLANGE
3	SHELL	1	304 SS	
4	SHELL CLAMP	1	304 SS	
5	INLET	1	304 SS	2" FLANGE
6	INLET O-RING	1	VITON	
7	HANDLE	1	304 SS	
8	LID	1	304 SS	
9	VENT	1	304 SS	1" NPT
10	SWING BOLTS	4	304 SS	M16
11	HOUSING O-RING	1	VITON	
12	BRACKETS	4	304 SS	

NOTES:

- PRM FILTRATION IS ONLY A SUPPLIER OF THIS EQUIPMENT.
- PRM IS NOT RESPONSIBLE FOR SPECIFYING THIS PRODUCT FOR THE APPLICATION.
- BUYERS AND/OR USER SHOULD REQUIRE AN ENGINEER FOR ENSURING THAT THE PROPER EQUIPMENT IS INSTALLED FOR THE APPLICATION INCLUDING ALL PROPER SAFETY PRACTICES.
- PRM IS NOT RESPONSIBLE FOR ANY DAMAGES TO PROPERTY AND/OR INJURY/DEATH RELATED TO IMPROPER INSTALLATION. FILTRATION EQUIPMENT INSTALLATIONS SHOULD ALWAYS INCLUDE ANCILLARY SAFETY DEVICES AND/OR OPERATIONAL PRACTICES.
- IT IS AGREED THAT PRM NOR ITS OWNERS HAVE LIABILITY WITH THE INSTALLATION AND OPERATION OF THESE OR OTHER PRODUCTS PURCHASED FROM PRM.
- ALLOW UP TO 1/4" TOLERANCE ON ALL MEASUREMENTS.
- MODEL LINK: <https://a360.co/42aCICA>

