

Multi-Cartridge Filter Housings work by evenly distributing unfiltered water around the filter cartridges. Suspended solids are captured in the filters and the filtered water exits through the outlet. PRM Stainless Steel Cartridge housings use industry standard 2.5 Inch x 40 Inch cartridge filters.

PRM Part #: BFCARTSSC24304X

Features:

- 304 Stainless Steel Housing
- 3 Inch Flanged Inlet/Outlet Connections
- 1/2 Inch NPT Drain Connections
- Filtration for Silt, Odor, Sediment, and More
- Easily Cleaned and Maintained
- Accepts standard length cartridges
- Air vent for use before start-up or draining
- Accepts complete range of filter media
- EPDM O-Rings
- Operating pressure: 145 psig max.
- Operating temperature: 40° - 140°F

BFCARTSSC24304X: 6 Cartridge Housing

- Uses (6) 2.5" x 40" Filter Cartridges
- Inlet/Outlet: 3 Inch Flange
- Flow Rate: 144 GPM



REPLACEMENT FILTERS AVAILABLE

PRM 2.5" x 40" spun polypropylene sediment filters are kept in stock for quick delivery.

Available in a variety of micron ratings and sizes. PRM spun polypropylene sediment filters meet NSF standards.

| NO. | ITEM | QTY. | MATERIAL | NOTES |
|-----|----------------------|------|----------|-----------|
| 1 | LEG | 4 | 304 SS | |
| 2 | INLET | 1 | 304 SS | 3" FLANGE |
| 3 | SHELL | 1 | 304 SS | |
| 4 | LID | 1 | 304 SS | |
| 5 | VENT | 1 | 304 SS | 1" NPT |
| 6 | SWING BOLTS | 6 | 304 SS | M12 |
| 7 | O-RING | 1 | EPDM | |
| 8 | BRACKETS | 6 | 304 SS | |
| 9 | INLET PRESSURE PORT | 1 | 304 SS | 1" NPT |
| 10 | OUTLET PRESSURE PORT | 1 | 304 SS | 1" NPT |
| 11 | OUTLET | 1 | 304 SS | 3" FLANGE |

NOTES:

- PRM FILTRATION IS ONLY A SUPPLIER OF THIS EQUIPMENT.
- PRM IS NOT RESPONSIBLE FOR SPECIFYING THIS PRODUCT FOR THE APPLICATION.
- BUYERS AND/OR USER SHOULD REQUIRE AN ENGINEER FOR ENSURING THAT THE PROPER EQUIPMENT IS INSTALLED FOR THE APPLICATION INCLUDING ALL PROPER SAFETY PRACTICES.
- PRM IS NOT RESPONSIBLE FOR ANY DAMAGES TO PROPERTY AND/OR INJURY/DEATH RELATED TO IMPROPER INSTALLATION. FILTRATION EQUIPMENT INSTALLATIONS SHOULD ALWAYS INCLUDE ANCILLARY SAFETY DEVICES AND/OR OPERATIONAL PRACTICES.
- IT IS AGREED THAT PRM NOR ITS OWNERS HAVE LIABILITY WITH THE INSTALLATION AND OPERATION OF THESE OR OTHER PRODUCTS PURCHASED FROM PRM.
- ALLOW UP TO 1/4" TOLERANCE ON ALL MEASUREMENTS.
- MODEL LINK: <https://a360.co/46Am1jq>

TYP 1 OF 4:
 $\varnothing 1\frac{1}{2}$ " FOOT HOLE

