

Stainless Steel Multi (9) Cartridge Filter Housing



PRM stocks Stainless Steel Multi-Cartridge Filter Housings ideal for most industrial or commercial applications. SSC housings use standard 2.5 Inch x 40 Inch cartridge filters and are ideal for most industrial/commercial applications.

Features:

- 304 Stainless Steel Housing
- 3 Inch Flanged Inlet/Outlet Connections
- 1/2 Inch NPT Drain Connections
- Filtration for Silt, Odor, Sediment, and More
- Easily Cleaned and Maintained
- Accepts standard length cartridges
- Air vent for use before start-up or draining
- Accepts complete range of filter media
- Silicone O-Rings
- Operating pressure: 145 psig max.
- Operating temperature: 40° - 140°F

BFCARTSSC36304X: 9 Cartridge Housing

- Uses (9) 2.5" x 40" Filter Cartridges
- Inlet/Outlet: 3 Inch 150# Flange
- Flow Rate: 216 GPM



(888-TREAT-IT) • www.prmfiltration.com • sales@prmfiltration.com

NO.	ITEM	QTY	MATERIAL	NOTES
1	LEG	4	304 SS	
2	DRAIN	1	304 SS	1/2" NPT
3	INLET	1	304 SS	2" FLANGE
4	SHELL	1	304 SS	
5	LID	1	304 SS	
6	EXHAUST VENT	1	304 SS	1/4" NPT
7	SWING BOLTS	12	304 SS	M12
8	BRACKETS	12	304 SS	
9	INLET PRESSURE PORT	1	304 SS	1/2" NPT
10	OUTLET PRESSURE PORT	1	304 SS	1/2" NPT
11	OUTLET	1	304 SS	2" FLANGE

NOTES:

1. PRM FILTRATION IS ONLY A SUPPLIER OF THIS EQUIPMENT.
2. PRM IS NOT RESPONSIBLE FOR SPECIFYING THIS PRODUCT FOR THE APPLICATION.
3. BUYERS AND/OR USER SHOULD REQUIRE AN ENGINEER FOR ENSURING THAT THE PROPER EQUIPMENT IS INSTALLED FOR THE APPLICATION INCLUDING ALL PROPER SAFETY PRACTICES.
4. PRM IS NOT RESPONSIBLE FOR ANY DAMAGES TO PROPERTY AND/OR INJURY/DEATH RELATED TO IMPROPER INSTALLATION. FILTRATION EQUIPMENT INSTALLATIONS SHOULD ALWAYS INCLUDE ANCILLARY SAFETY DEVICES AND/OR OPERATIONAL PRACTICES.
5. IT IS AGREED THAT PRM NOR ITS OWNERS HAVE LIABILITY WITH THE INSTALLATION AND OPERATION OF THESE OR OTHER PRODUCTS PURCHASED FROM PRM.
6. ALLOW UP TO 1/4" TOLERANCE ON ALL MEASUREMENTS.
7. MODEL LINK: <https://a360.co/3MRHWWb>

