

4 Bag Housing

Industrial multi-bag filter housings made of 304 stainless steel for big flow requirements. Filter Housings provide excellent filtration in both industrial and chemical applications.

Standard design pressure is 150 PSI max. and design, materials, and construction conform to CE and ASME code.

Features Include:

- 304 Stainless Steel Construction
- 4" Flanged Inlet and Outlet
- 525 GPM Flow Rate
- Viton® O-rings Standard
- 150 psi Maximum Working Pressure
- Stainless Steel Strainer Baskets and Internal Bag Hold Down Support
- Uses (4) #2 Size Filter Bags (7-1/16" Dia. x 32" L)



PRM PART #: BFHBFM4FSSXV2

** Options and Services **

- Skid mounting, pre plumbed filter array
- Steel, Stainless Steel, or PVC Piping with Valves
- Custom Integration Into Existing Systems
- 316 Stainless Steel or Carbon Steel Option
- Replacement Bag Filters available in stock

NO.	ITEM	QTY	MATERIAL	NOTES
1	LEG	3	304 SS	
2	DRAIN	1	304 SS	1" NPT
3	SHELL	1	304 SS	
4	SUPPORT ARM MOUNT	1	304 SS	
5	INLET	1	304 SS	4" FLANGE
6	LID	1	304 SS	
7	SUPPORT ARM	1	304 SS	
8	SUPPORT ARM PORT	1	304 SS	
9	EXHAUST VENT	1	304 SS	1/4" NPT
10	SWING BOLTS	12	304 SS	M16
11	BRACKETS	12	304 SS	
12	OUTLET	1	304 SS	4" FLANGE

NOTES:

- PRM FILTRATION IS ONLY A SUPPLIER OF THIS EQUIPMENT.
- PRM IS NOT RESPONSIBLE FOR SPECIFYING THIS PRODUCT FOR THE APPLICATION.
- BUYERS AND/OR USER SHOULD REQUIRE AN ENGINEER FOR ENSURING THAT THE PROPER EQUIPMENT IS INSTALLED FOR THE APPLICATION INCLUDING ALL PROPER SAFETY PRACTICES.
- PRM IS NOT RESPONSIBLE FOR ANY DAMAGES TO PROPERTY AND/OR INJURY/DEATH RELATED TO IMPROPER INSTALLATION. FILTRATION EQUIPMENT INSTALLATIONS SHOULD ALWAYS INCLUDE ANCILLARY SAFETY DEVICES AND/OR OPERATIONAL PRACTICES.
- IT IS AGREED THAT PRM NOR ITS OWNERS HAVE LIABILITY WITH THE INSTALLATION AND OPERATION OF THESE OR OTHER PRODUCTS PURCHASED FROM PRM.
- ALLOW UP TO 1/4" TOLERANCE ON ALL MEASUREMENTS.
- MODEL LINK: <https://a360.co/3J0GqnI>

