
SCH 80 TRUE UNION BALL VALVE



PVC true union ball valves offer a simple way to start and stop flow in a system. The term true union means that the carrier or main part of the valve can be removed from the piping system and be either repaired or replaced without completely disassembling the system, saving time and money. ERA true union ball valves are made from durable dark gray Schedule 80 PVC and have an easy-to-grip red handle that turns with minimal effort. Unless specifically noted, ERA PVC is not NSF certified.



Specifications:

 Schedule 80, suitable for both Sch. 40 and 80 pipe

Working Pressure: 150 PSI @ 73°F

Full Port Valve

EPDM O-Rings

Socket Connection, NPT Available

Color: Dark Gray

SCHEDULE 80 PVC TRUE UNION BALL VALVE SPECIFICATION OF MATERIALS								
Number	Part	Material	Qty.					
1	Stem	PVC	1					
2	Handle	ABS	1					
3	Stem O-Ring	EPDM	2					
4	Union Nut	PVC	2					
5	End Connector	PVC	2					
6	Body O-Ring	EPDM	2					
7	O-Ring	EPDM	2					
8	Body	PVC	1					
9	Ball	PVC	1					
10	Seat Seal	PTFE	2					
11	Seat Carrier	PVC	1					
12	Carrier O-Ring	EPDM 1						

SCHEDULE 80 PVC TRUE UNION BALL VALVE											
DIMENSIONS (INCHES)											
Part #	Size	Α	В	С	D	Е	F	Н	1		
PVC80BVTU050X	1/2 INCH	2.015	0.854	0.84	0.551	4.429	2.559	1.988	0.811		
PVC80BVTU075X	3/4 INCH	2.578	1.401	1.05	0.736	5.125	2.952	2.303	0.968		
PVC80BVTU100X	1 INCH	2.901	1.637	1.314	0.944	5.61	3.346	2.586	1.102		
PVC80BVTU125X	1-1/4 INCH	3.409	2.047	1.659	1.259	6.338	3.818	3.011	1.22		
PVC80BVTU150X	1-1/2 INCH	4.015	2.342	1.9	1.574	7.25	4.33	3.385	1.24		
PVC80BVTU200X	2 INCH	4.724	2.952	2.375	1.968	8.425	5.255	3.996	1.574		
PVC80BVTU250X	2-1/2 INCH	5.314	3.444	2.875	2.362	8.976	6.338	4.429	1.574		
PVC80BVTU300X	3 INCH	7.401	4.232	3.5	3.11	10.59	7.874	6.318	1.889		
PVC80BVTU400X	4 INCH	8.503	5.196	4.5	3.897	12.165	9.448	6.83	2.204		

888-TREAT-IT • www.prmfiltration.com • sales@prmfiltration.com