

## Cam & Groove Fittings—Aluminum



Durable cam and groove fittings from PRM can be ideal for low-pressure fluid-handling applications. Use them to help rapidly connect and disconnect hose or pipe fittings. Aluminum for added strength and resistance to abrasion, corrosion, and chemicals.

### Materials:

Body: Aluminum

Arms: Brass

Pins: Stainless Steel

Gasket: Nitrile Rubber (NBR)

Max. Operating Pressure @70°F: 3/4 inch to 2 inch - 250 psi  
3 inch to 4 inch - 150 psi;  
6 inch - 75 psi

Maximum Temperature Rating: 185° F



TYPE A MALE CAM LOCK/ FNPT

3/4", 1", 1-1/4", 2", 3", 4", 6"



TYPE B FEMALE COUPLER / MNPT

3/4", 1", 1-1/4", 2", 3", 4", 6"



TYPE C FEMALE COUPLER/  
HOSE FITTING

3/4", 1", 1-1/4", 2", 3", 4", 6"



TYPE D FEMALE COUPLER/  
FNPT

3/4", 1", 1-1/4", 2",  
3", 4", 6"



TYPE DC CAM LOCK CAPS

3/4", 1", 1-1/4", 2",  
3", 4", 6"



TYPE E MALE CAM LOCK/  
HOSE SHANK

3/4", 1", 1-1/4", 2",  
3", 4", 6"



TYPE F MALE CAM LOCK/  
MNPT

3/4", 1", 1-1/4", 2",  
3", 4", 6"

888-TREAT-IT • [www.prmfiltration.com](http://www.prmfiltration.com) • [sales@prmfiltration.com](mailto:sales@prmfiltration.com)