

## Cam & Groove Fittings—Polypropylene



Durable cam and groove fittings from PRM can be ideal for low-pressure fluid-handling applications. Use them to help rapidly connect and disconnect hose or pipe fittings. Polypropylene for strength and resistance to abrasion, corrosion, and chemicals.

### Materials:

Body: Polypropylene

Arms: Stainless Steel

Pins: Stainless Steel

Gasket: Nitrile Rubber (NBR)

Max. Operating Pressure @70°F: 125 psi

Maximum Temperature Rating: 185° F



**TYPE A MALE CAM LOCK/ FNPT**  
3/4", 1", 1-1/4", 2"



**TYPE B FEMALE COUPLER / MNPT**  
3/4", 1", 1-1/4", 2"



**TYPE C FEMALE COUPLER/ HOSE FITTING**  
3/4", 1", 1-1/4", 2"



**TYPE D FEMALE COUPLER/ FNPT**  
3/4", 1", 1-1/4", 2"



**TYPE DC CAM LOCK CAPS**  
3/4", 1", 1-1/4", 1-1/2", 2"



**TYPE E MALE CAM LOCK/ HOSE SHANK**  
3/4", 1", 1-1/4", 2"



**TYPE F MALE CAM LOCK/ MNPT**  
3/4", 1", 1-1/4", 1-1/2", 2"

888-TREAT-IT • [www.prmfiltration.com](http://www.prmfiltration.com) • [sales@prmfiltration.com](mailto:sales@prmfiltration.com)