

Cam & Groove Fittings— 304 Stainless Steel



Durable cam and groove fittings from PRM can be ideal for low-pressure fluid-handling applications. Use them to help rapidly connect and disconnect hose or pipe fittings. 304 Stainless Steel for added strength and resistance to corrosion and chemicals.

Materials:

Body: 304 Stainless Steel

Arms: 304 Stainless Steel

Pins: 304 Stainless Steel

Gasket: Nitrile Rubber (NBR)

Max. Operating Pressure @70°F: 3/4 inch to 2 inch - 250 psi

Maximum Temperature Rating: 250° F



TYPE A MALE CAM LOCK/ FNPT

3/4", 1", 1-1/4", 1-1/2", 2"



TYPE B FEMALE COUPLER / MNPT

3/4", 1", 1-1/4", 1-1/2", 2"



TYPE C FEMALE COUPLER/
HOSE FITTING

3/4", 1", 1-1/4", 1-1/2", 2"



TYPE D FEMALE COUPLER/
FNPT

3/4", 1", 1-1/4", 1-1/2", 2"



TYPE DC CAM LOCK CAPS

3/4", 1", 1-1/4", 1-1/2", 2"



TYPE E MALE CAM LOCK/
HOSE SHANK

3/4", 1", 1-1/4", 1-1/2", 2"



TYPE F MALE CAM LOCK/
MNPT

3/4", 1", 1-1/4", 1-1/2", 2"

888-TREAT-IT • www.prmfiltration.com • sales@prmfiltration.com