

## PRM Guardian Xtreme Tanker Hose



### Tanker Hose, 150 PSI

PRM Guardian Xtreme Tanker Hose is designed for tank tanker, rail tanker, in-plant and oilfield loading operations to transfer gasoline, oil, ethanol blends and other petroleum based products up to 50% aromatic content. It is designed for pressure, gravity flow, or full-suction service.

#### Features:

Tube: Nitrile Rubber Hose, smooth

Cover: Synthetic Rubber, oil, fuel, weather resistant

Reinforcement: High strength synthetic fiber with anti-static helix wire

Temperature Range: -90°F (-32°C) to +180°F (+82°C)

Pressure: 150 psi operating pressure

Weather and Abrasion Resistant

Light in weight, easy to handle

Application: Hardwall hose for suction and delivery of petroleum fuel with aromatic content up to 50%

The hoses can be cut to the desired length, and compatible fittings can be added on the ends of the hoses to connect them to equipment.



#### PRM PART #

***HS038GUARDXBLNX—3/8" ID***

***HS050GUARDXBLNX—1/2" ID***

***HS075GUARDXBLNX—3/4" ID***

***HS100GUARDXBLNX—1" ID***

***HS125GUARDXBLNX—1-1/4" ID***

***HS200GUARDXBLNX—2" ID***

888-TREAT-IT • [www.prmfiltration.com](http://www.prmfiltration.com) • [sales@prmfiltration.com](mailto:sales@prmfiltration.com)