PRM Guardian Xtreme Nitrile General Purpose Hose



Nitrile Air/Water/Fuel Discharge Hose, 300 PSI

Bulk general purpose hoses have a nitrile tube that provides excellent resistance to oils and moderate resistance to aromatics. They also have a nitrile cover that offers good resistance to ozone, animal fats and oils, and petroleum. These nitrile hoses are used for air, water, and petroleum oils for agricultural, construction, and industrial equipment. Recommended for transfer of aromatic or non aromatic hydrocarbon fluids.



Features:

Tube: Nitrile Rubber Hose, smooth

Reinforcement: Multi-ply high strength synthetic

fiber

Temperature Range: -22°F to +176°F

Pressure: 300 psi operating pressure

Weather and Abrasion Resistant

Flexible Hose with Less Distortion

Application: Softwall hose Designed for the delivery of petroleum-based products, diesel, gasoline, lubricants, fuel, with aromatic content up to 50%, good general industrial properties.

The hoses can be cut to the desired length, and compatible fittings can be added on the ends of the hoses to connect them to equipment.



PRM PART #

HS038GUARDXBLNX—3/8" ID

HS050GUARDXBLNX—1/2" ID

HS075GUARDXBLNX—3/4" ID

HS100GUARDXBLNX—1" ID

HS125GUARDXBLNX—1-1/4" ID

HS200GUARDXBLNX—2" ID

888-TREAT-IT • www.prmfiltration.com • sales@prmfiltration.com