

RT-5642 AS/SVE Rental System Trailer



SVE and Air Sparge Extraction System - 8' x 22' enclosed trailer

Features:

SVE Capabilities: 700 CFM @ 11.6" Hg
AS Capabilities: 75 CFM @ 20 PSI
System Rating: 120/230 V, 3 phase, 200 Amp, UL Listed System
Interior of Process room rated for Class 1, Division 2 Hazardous Locations

Controls:

NEMA 4/12 control panel
PLC Controller with wireless connectivity and remote login
Interface with full SCADA remote system control and data and event logging

SVE Package

Eurus ZZ6M Rotary Lobe Vacuum Blower, Blower package mounted on steel base frame with silencer
SVE Manifold includes 6 - 2" SVE legs
Carbon by-pass manifold so blower can pull through carbons, eliminates the need for heat exchanger
PRM model HP-200 liquid phase carbon vessel inline before final discharge through side of trailer

Air Sparge System

Busch 1252AP Rotary Claw Compressor rated for 75 CFM @ 20 PSI
Integrated Inlet Filter Silencer
Heat Exchanger plumbed inline
6 - 1" sparge legs, each with check valves, pressure gauges, rotameter

Deep Air Sparge System

(2) Schulz 10HP tandem oilless compressors
Rated for up to 63 CFM @ 45 psi
Includes integral air cooled aftercooler
Deep Air Sparge Manifold includes 5 - 3/4" sparge legs, each with check valves, pressure gauges, rotameter

Carbon Units

VP-1000 Vapor Phase Carbon Vessel



**Short or Long Term Lease or
Option to Purchase Available!**

Contact PRM for Details

(888-TREAT-IT) • www.prmfiltration.com • sales@prmfiltration.com

