## Product data sheet Characteristics

### SDSA4040

# Surge Protect - 40kA - 480Y/277VAC - 3P4W - T4X

Product availability: Stock - Normally stocked in distribution facility

#### Main

Product Surge protection device



Complementary

<u></u>		
Surge Current	40 kA	
Voltage Rating	480Y/277 V AC	
Number of Phases	3 phases	
Wiring Configuration	4-wire	
Connection	Wire AWG 12 copper	
MCOV	180 V	
Nominal Discharge Current	10 kA	
SCCR	200 kA	
Local Signalling	Status LED normal operation	
Mounting Support	Panel mounting	
Height	3.07 in (78 mm)	
Width	3.62 in (92 mm)	
Depth	2.64 in (67 mm)	

#### Environment

Enclosure Rating	NEMA 4X	
Enclosure Material	Black plastic	
Standards	UL 1449:ed. 4 CSA C22.2 No 8:1986	
Ambient Operating	149 °F (65 °C)	

#### Ordering and shipping details

Category	08462 - SURGE PROTECTION SDSA
Discount Schedule	DE1B
GTIN	00785901558200
Package weight(Lbs)	0.45 kg (1 lb(US))
Returnability	Yes
Country of origin	MX

#### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP which is known to the State of California to cause cancer and DIDP which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration