



**HERON**  
INSTRUMENTS INC.



## SKINNY DIPPER (Series 1300)

### Static & drawDown levels Specifications

Reel Assembly:	Standard	Large	Double
Height	36cm (14")	43cm (17")	51cm (20")
Depth	21cm (9")	23cm (9")	51cm (20")
Width	29cm (11.5")	34cm (13.5")	37cm (14.5")
Weight (Reel Assembly Only)	2.6kg (5.7lb)	4.2kg (9.3lbs)	7.1kg (15.7lbs)
Plate Size	27cm (10.5")	34cm (13.5")	38cm (15")
Plate Material	Nylon Fibre Composite	Aluminum	Aluminum
Brake	Ergonomic Dial	Ergonomic Dial	Spring Loaded Pin
Stainless Ball Bearing	Yes	Yes	Yes
Hanger	Included on frame	Included on frame	No
Tape Guide	Included on frame	Included on frame	No
Test Points	Use Conductive Material	Use Conductive Material	Use Conductive Material
Tape Lengths	30m, 100ft	180m, 600ft	450m, 1500ft
	60m, 200ft	200m, 750ft	600m, 2000ft
	100m, 300ft	300m, 1000ft	+ 600m/2000ft
	150m, 500ft		Power Reel Available
<b>Tape:</b>		<b>Electronic Panel:</b>	
Tape	Polyethylene	Operating Mode	Static & drawDown
Jacketing	No	Power Source	9 Volt Alkaline
Conductors	7 strand S/S	Sensitivity Control	S/S & Aluminum
Markings	Metric or Engineering Scale	Audio/Visual Indication	Ultra Bright LED & 80dbi Buzzer
Width	6.35mm (1/4")	Rating	IP65
Dog Bone Profile	No	Removable	Yes
Break Strength	N/A	Maximum Temperature	80°C
<b>Probe:</b>		<b>Included:</b>	
Weight	32g (.07lbs)	Padded Carry Case	Included
Length	Probe 8.75cm (3.5") with weights 22.5cm (9")		
Diameter	6.35mm (1/4")		
Removable	No	<b>Warranty:</b>	5 Year (Probe 1 Year)
Depth Rating	Up to 100m/300ft for 20 min.		
Break Strain	N/A		
Wetted Material	S/S & Delrin		

Heron Instruments Inc. 447 Moxley Rd. Dundas, ON L9H 5E2, CANADA info@heroninstruments.com, 1-800-331-2032

A-825-1300-003 Rev A Heron2021