



## Serie PNEUMATIC ACTUATORS

### Articolo 8P0130(L) - 8P0132(L)

- DA - SR actuator with 3 way L-port brass ball valve direct mount (RB 365N).

- OPERATING CONDITIONS: fluid H2O - T 68°F - Actuator P 90 ÷ 100 PSI

#### 8P00130 (L)

##### VALVE WITH DOUBLE ACTING ACTUATOR

PSI	400	400	400	400	400	400	400	400	400	400
DN - A	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"
B	4.43	4.43	4.43	4.12	6.58	7.03	7.76	9.04	10	10.02
C	3.76	3.76	3.76	3.85	5.63	5.85	6.34	7.35	7.80	7.80
D	1.77	1.77	1.77	1.77	2.80	2.80	2.80	3.17	3.17	3.17
E	2.64	2.64	2.87	3.19	3.74	4.39	4.86	5.73	6.93	7.08
F	4.33	4.33	4.33	4.33	5.55	5.55	5.55	6.46	6.46	6.46
G	1.32	1.32	1.44	1.60	1.87	2.20	2.43	2.87	3.47	3.54
ACT.	DA 32	DA 32	DA 32	DA 32	DA 52	DA 52	DA 52	DA 63	DA 63	DA 63

#### 8P0132(L)

##### VALVE WITH SPRING RETURN ACTUATOR

PSI	400	400	400	400	400	400	400	400	400	400
DN - A	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"
B	5.87	5.87	5.87	6.01	7.02	7.48	8.21	10.03	11.25	11.28
C	5.2	5.2	5.2	5.29	6.08	6.3	6.79	8.61	9.06	9.06
D	2.80	2.80	2.80	2.80	3.17	3.17	3.17	4.17	4.17	4.17
E	2.64	2.64	2.87	3.19	3.74	4.39	4.86	5.73	6.93	7.08
F	5.55	5.55	5.55	5.55	6.46	6.46	6.46	9.47	9.47	9.47
G	1.32	1.32	1.44	1.60	1.87	2.20	2.43	2.87	3.47	3.54
ACT.	SR 52	SR 52	SR 52	SR 52	SR 63	SR 63	SR 63	SR 85	SR 85	SR 85