

Key	Part	Description	Key	Part	Description	
1	R6E2	Spindle Screw Set	11	R5F3	Fish Alert Spring	
2	R6P1	Nitrile Washer	12	R5B1	Fish Alert Wheel	
3	R6D1	D Washer	13	R7A5	Friction Tube	
4	R6C4	Spindle Spring	14	R6A15	Spindle	
5	R4H1	Handle Plug	15	R7L2	Silent Drag Cam	
6	R7E3	Handle-plate Assy	16	R7J8	Drag Pawl	
7	R7F1	Handle-plate Lock Nut	17	R7K12	Drag On/Off Lever	
8	R7D3	Drag Star Nut	18	R1A	Reel without Spool	
9	R7B/C14	Friction Washer Set	19	R6F1	Spindle Hex Nut	
10	R4A	Spool Only				

Special Note: The 50GCZ cannot be converted from right hand wind to left hand wind. A left-hand wind version is available.



50GCZ ADVENTURER



CONGRATULATIONS and thank you for purchasing one of our Australian made graphite backed reels as your choice of fishing reel. These reels are constructed from the highest quality materials to ensure your reel will last for many years.

Plus, all these other advantages -

Long, accurate casts:

Now, with only the minimum of practise you will be able to cast further and more accurately than ever before.

Control large fish with ease: Powerful one-to-one wind means you only need about a quarter of the effort required to lift a similar weight on a spinning reel.

You can fish harder and longer: Simple, rugged construction means you can fiddly forget that maintenance, because your Alvey reel will resist the effects of saltwater and sand.

Special Features

- → Star Drag
- → Easy Cast Operation
- → Multi-plate Clutch
- → On/Off Drag Switch
- → Fibreglass Spool

More comfortable fishing: Low winch-mount rods let you fish with your arms in a relaxed position.

No line twist: Use a small free-running swivel as the last piece in any rig and you'll minimise any line twist. (See illustrations inside)



Alvey 10 Year Guarantee: Any faulty Alvey part or reel will be replaced at no charge providing the manufacturer finds the part or reel has had normal usage and attention.

Reel Icon Pty Ltd Trading as Alvey Reels Australia ABN 57 625 261 707 2-6 Antimony Street Carole Park Qld 4300 t: +61 7 3271 2844 f: +61 7 3271 2451

For more hints and tips on maintenance, please visit the **spare parts** page at www.alvey.com.au e: info@alvey.com.au #alveyreels

Recommended Line Size

Your 50GCZ reel will hold approximately 500 metres of 5 kg line. If fishing near rocks or other hazards use heavier line to help avoid line breakage.

Filling the Spool with Line


Always take the line from the front of the dispenser, never the side.

Wind firmly and evenly onto the spool, spreading the line with your fingers to give a smooth casting base.

Never stretch a nylon monofilament onto a spool; when it goes back to its original length it will exert strong enough crushing action to damage your spool.

Never allow loose coils to develop on your spool through careless uneven winding.

Adopt the habit of applying light finger tension when retrieving line and spread evenly over its bed.



Selecting a Rod

Your rod and reel outfit should be balanced so you can hold it comfortably over long periods. A matched set, which has a point of balance where it's held in the left hand, will give you the most comfortable posture. The ideal rod for this reel should be 2.0 to 3.0m in length.

The use of a short butt brings the reel into a natural position for rewinding with your elbows at your side and without strain.

Four easy steps to casting like a champion



Rigs & Swivels

When used properly a brass swivel is a very inexpensive and efficient way to keep a fishing line in good condition. Curls and twists in a line can be caused by many things, but can be kept to a minimum by the correct use of a swivel

Swivel Sizes

Line breaking strain	Swivel size		
1 – 5 kg	No 14		
5 – 8 kg	No 12		
8 – 15 kg	No 10		
15 – 20 kg	No 9		

Swivel must be above sinker

*HOOK No!, No2, No! / 0 SHOR	TRACE Long		SWIVEL	LINE	BREAM
*HOOK No3, No4, No6	SWIVEL SINKER	TRACE 2FT. OR MORE	SWIVEL -	LINE	WHITING
HOOK 4/0 4 HOOK RIG	SHORT TRACE	SINKER TRACE 2FT. OR MORE	SWIVEL	LINE	TAILOR
SPINNER OR LURE	SWIVE	=L = = = = = = = = = = = = = = = = = =	LINE		TAILOR
BLOOD KNOT	SWIVEL		HOOK WILL	vary in size	TO SUIT BAIT

50GCZ



Non-Reversing Drag Models

The non-reverse series of reels allows line to be released under a pre-set pressure while the reel handle remains in a stationary position. This model incorporates the new *Belleville Power Washer* that improves the range of tension settings available through the star drag system. The position of the star on the front of the reel allows easy adjustment while playing a fish.

The small lever on the back of the reel operates the on/off mechanism that allows you to disengage the non-reverse action when required.

Setting the Drag

Make sure the drag activating lever on the back of the reel is in the 'On' position. Using a small spring balance pull the line off the reel. Set the tension of the drag to be approximately one third of the breaking strain of your line by rotating the star on the front of the reel.

(Clockwise to increase tension.)

It is better to have the drag set light as a short sharp run from a large fish could snap the line on an over set drag. The tension is easily adjusted while fighting the fish and the unique style of the Alvey reel allows extra drag pressure to be applied directly to the spool by using the palm of your hand against the bottom of the reel.

Playing the fish

Once the fish has been hooked always keep a bend in the rod by holding it at an angle to the fish. With the power of an Alvey reel you are in control. Do not rush the fish. Allow the drag to tire the fish. Many times the fish is lost in the shore break. Keep a steady tension on your line, a bend in the rod and ease the fish ashore.

Fish Alert

This model has an automatic fish alert built into the spool. When the drag is on and spool releases line a ratchet sound alerts the angler. This will only operate when the drag is on and line is being stripped from the reel.

Maintenance

Use light machine oil on working spindles, handles, index mechanism and drag pawl. After each day of fishing relieve the drag tension, wash off salt and sand and lubricate as above before storage.