



A BETTER WAY TO FISH.™



A BETTER WAY TO FISH.™



82WGVC2 PARTS LIST	
Part No	Part Description
D2A-MW	Stainless Steel Base Clamp
D3A-BCV	Stainless Steel Guide Assembly
D4F-RM	Handle Assembly
R5B5	Ratchet Wheel
R5C7	Drag Lever & Activator
R5E10	Ratchet Button & Spring
R5G3	Silent Drag Pawl Spring Light
R5K1	ON/OFF Cam
R6A18	Spindle
R6C5	Spindle Spring
R6D2	Spindle D Washer
R6E4	Spindle Screw
R6F3	Dome Hex Nut
R6J7	Spindle Washer
R6P2	Nitrile Washer Spindle Screw
R7A4	Drag Friction Tube
R7B/C15	Drag Clutch Washer Set 82
R7D5	Drag Star Adjusting Nut
D7E-MW	Drag Handle Plate
R7F2	Drag Handle Plate Lock Nut
R7J4	Silent Drag Pawl
R7L1	Silent Drag Cam
R7M7	Drag Pawl Post 825



82WGVC2



CONGRATULATIONS and thank you for purchasing one of our new winches as your choice of fishing reel. These reels are constructed from the highest quality materials to ensure your reel will last for many years.

Plus, all these other advantages -

High speed recovery: Offset handle plate allows for extra fast retrieve on unbaited rig. Allows you to rebait and be back fishing in a flash.

Control large fish with ease: Powerful one-to-one direct wind means you only need about a quarter of the effort required to lift a similar weight on a spinning reel.

You can fish harder and longer: Simple, rugged construction means you can forget that fiddly maintenance, because your Alvey reel will resist the effects of salt water and sand

Special Features

- Heavy Duty Handle Plate
- Vented Back
- Belleville Power Washer and Multi-plate Clutch
- On/Off Drag Switch
- Vented Fibreglass Spool

Fixed G clamp: Stainless steel clamp will fit rails up to 50mm diameter.

Alvey 5 Year Guarantee: Any faulty Alvey part or reel will be replaced at no charge providing the manufacturer finds the part or reel has had normal usage and attention.



Alvey 10 Year Guarantee: Any faulty Alvey part or reel will be replaced at no charge providing the manufacturer finds the part or reel has had normal usage and attention.

Reel Icon Pty Ltd Trading as
Alvey Reels Australia ABN 57 625 261 707
2-6 Antimony Street Carole Park Qld 4300
t: +61 7 3271 2844 f: +61 7 3271 2451

For more hints and tips on maintenance, please visit the **spare parts** page at
www.alvey.com.au
e: info@alvey.com.au
[#alveyreels](https://twitter.com/alveyreels)



Instructions for Use

Congratulations and thank you for choosing an Alvey Reel

After firmly attaching the Deck Winch Reel to the rail or mounting system of your launch, the line is passed through the ring in the line guide. The rig, bait and sinker are then attached and dropped overboard.

With the Star Nut slackened, the sinker will quickly take your baited line down, but you must be ready to stop the spool with your hand immediately the sinker hits the bottom to prevent overrun. You should then tighten the Star Adjusting Nut to apply the desired tension on the line from the spool.



**Alvey products are guaranteed against
faulty materials or workmanship**
Spare parts and service, if necessary, are readily available.

Removing the Spool only requires the spindle screw fittings to be removed to take the spool off.


The process of removing the spool, freeing the line and replacing it should take only a few seconds, but will not be necessary if a little care is taken to prevent overrun when playing out line with a free spool.

Correct assembly for silent drag pawl & cam

Ensure that Drag pawl pin is inside of silent drag cam slot or reel will click when winding.

Spring loop to go over pin for correct operation of the drag.

In assembling spool to reel, have the drag in OFF position.



Replacing the Spool requires the Silent Drag Cam and pin to be realigned

Maintenance:

- Wash off with fresh water after each use. Oil handles and roller guides with light oil.
- Oil or light grease in grease nipple occasionally depending on use.

Major Service:

- Oil clutch washers (Remove clutch cover plates if applicable).