

## SECTION 1. Identification

**Product Code** 99-A-100

**Product Name:** Quantum99 Urethane Spray Activator

**Supplied by:** Engineered Marine Coatings, Inc.  
2134 Cainhoy Rd  
Huger, SC 29450 United States  
T 855-544-3648  
E ask@quantumpaint.com www.quantumpaint.com

24 Hour Emergency:  
CHEMTEL: 800-255-3924

NOTE: National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

## SECTION 2. Hazard(s) Identification

**\*\*\* EMERGENCY OVERVIEW \*\*\*:** Highly flammable liquid and vapor. May damage fertility or the unborn child. Suspect cancer hazard.

**GHS Classification**

Acute Tox. 4 Inhalation, Carc. 2, Flam. Liq. 2, Repr. 1A, Resp. Sens. 1, Skin Sens. 1, STOT SE 3 RTI

**Symbol(s) of Product**



**Signal Word**

Danger

**GHS HAZARD STATEMENTS**

Flammable Liquid, category 2	H225	Highly flammable liquid and vapor.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Respiratory Sensitizer, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Reproductive Toxicity, category 1A	H360	May damage fertility or the unborn child.

**GHS PRECAUTIONARY STATEMENTS**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

P284	[In case of inadequate ventilation] wear respiratory protection.
P302+P352	IF ON SKIN: Wash with plenty of water
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor/physician if you feel unwell.
P321	Specific treatment (see first aid section on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use appropriate method to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### SECTION 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Hexane, 1,6-Diisocyanato-,Homopolymer	28182-81-2	50-75	GHS07-GHS08	H317-332-334-335
Dimethyl carbonate	616-38-6	25-50	GHS02	H225
n-Butyl Acetate	123-86-4	2.5-10	GHS02-GHS07	H226-336
Petroleum hydrocarbon	64742-94-5	2.5-10	GHS07-GHS08	H227-304-315-332-336-351
Naphthalene	91-20-3	0.1-1.0	GHS06-GHS08	H227-315-320-330-351
3-Ethyl-2-methyl-2-(3-methylbutyl)-1, 3-oxazolidine	143860-04-2	0.1-1.0	GHS05-GHS08	H227-314-360

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### SECTION 4. First-Aid Measures



**FIRST AID - EYE CONTACT:** Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

**FIRST AID - SKIN CONTACT:** Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse. Remove contaminated shoes and clothes and clean before reuse.

**FIRST AID - INHALATION:** Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

**FIRST AID - INGESTION:** Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

### SECTION 5. Fire-Fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Highly flammable liquid and vapor. Vapors/dust may cause flash fire or explosion. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning. Closed container may explode under extreme heat.

**SPECIAL FIREFIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Do not use water. Avoid use of solid water streams. Water spray to cool containers or protect personnel. Use with caution. Small fires: carbon dioxide or dry chemical. Large fire: alcohol-type aqueous film-forming foam or water spray.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

## SECTION 6. Accidental Release Measures

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Use water mist or spray to disperse vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Clean up spill area with a decontamination solution made up of 50% isopropyl alcohol, 45% water and 5% concentrated ammonia solution. The solution should cover the area for at least one hour then be collected for disposal.

## SECTION 7. Handling and Storage



**HANDLING:** Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Material accumulates static charge (ignition source). Use spark-proof tools and explosion proof equipment. When transferring, follow proper grounding procedures. Use spark-resistant tools. Do not load into compartments adjacent to heated cargo. Always open containers slowly to allow any excess pressure to vent. After opening, purge container with nitrogen before reclosing. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

**STORAGE:** Keep away from heat, sparks, and flame. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated place. Keep from freezing. Keep container closed when not in use. Storage under nitrogen atmosphere is recommended. Protect from direct sunlight.

## SECTION 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Hexane, 1,6-Diisocyanato-,Homopolymer	N.D.	N..D.	N.D.	N.D.
Dimethyl carbonate	N.D.	N.D.	N.D.	N.D.
n-Butyl Acetate	150 ppm	200 ppm	150 ppm	N.D.
Petroleum hydrocarbon	N.D.	N.D.	N.D.	N.D.
Naphthalene	10 ppm	15 ppm	10 ppm	15 ppm
3-Ethyl-2-methyl-2-(3-methylbutyl)-1, 3-oxazolidine	N.A.	N.A.	N.A.	N.A.

### Personal Protection



**RESPIRATORY PROTECTION:** NIOSH/MSHA approved respirators may be necessary if airborne concentrations are expected to exceed exposure limits.



**SKIN PROTECTION:** Wear impervious gloves to prevent contact with the skin. Wear long sleeves when contact is likely to occur. Wear protective gear as needed - apron, suit, boots.



**EYE PROTECTION:** Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).



**OTHER PROTECTIVE EQUIPMENT:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



**HYGIENIC PRACTICES:** Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

## SECTION 9. Physical and Chemical Properties

<b>Appearance:</b>	Liquid	<b>Physical State:</b>	Liquid
<b>Odor:</b>	Typical	<b>Odor Threshold:</b>	N.D.
<b>Density, g/cm<sup>3</sup>:</b>	1.084	<b>pH:</b>	N.D.
<b>Freeze Point, °F:</b>	N.D.	<b>Viscosity:</b>	N.D.
<b>Solubility in Water:</b>	Insoluble	<b>Explosive Limits, vol%:</b>	0.8 - 7.6
<b>Boiling Range, °F:</b>	194 - 401	<b>Flash Point, °F:</b>	70
<b>Evaporation Rate:</b>	Not determined	<b>Auto-ignition Temp., °F:</b>	N.D.
<b>Vapor Density:</b>	N.D.	<b>Vapor Pressure:</b>	N.D.

(See "Other information" Section for abbreviation legend)

## SECTION 10. Stability and Reactivity

**STABILITY:** No Information

**CONDITIONS TO AVOID:** Avoid impact, friction, heat, sparks, flame and source of ignition.

**INCOMPATIBILITY:** Keep separate from alkalis. Avoid contact with moisture and/or water. Prevent contact with strong oxidizing agents. Keep away from strong bases. Keep away from acids.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Toxic gases/fumes are given off during burning or thermal decomposition. During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed. Decomposition releases nitrogen oxides.

**HAZARDOUS POLYMERIZATION:** No Information

## SECTION 11. Toxicological Information



### Information on Toxicological Effects

**EFFECTS OF OVEREXPOSURE - INHALATION:** Breathing in the material may irritate the mucous membranes of the nose, throat bronchi and lungs. Vapors are irritating to the respiratory tract. Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). Prolonged exposure to high concentrations can cause central neurological depression and EEG abnormalities. May cause dizziness and drowsiness. May cause central nervous system depression. Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness. Vapors have a narcotic effect and may cause headache, fatigue/drowsiness, dizziness and nausea. Harmful if inhaled.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes eye irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Ingestion may cause gastrointestinal tract irritation. May cause nausea and vomiting. May cause central nervous system depression. May cause dizziness and drowsiness and/or stupor.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Suspect cancer hazard. This product contains naphthalene. A National Toxicology Program (NTP) draft report states that lifetime inhalation exposure to naphthalene resulted in increases in tumors of the nose in rats. In a previous NTP study, lifetime inhalation exposure to naphthalene increased lung tumors in female mice. The relevance of the rodent findings to humans is questionable. Overexposure may cause nervous system damage. Possible reproductive hazard. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

**Primary Route(s) of Entry:** Eye Contact, Ingestion, Inhalation, Skin Contact

**Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50, mg/kg</u>	<u>Dermal LD50, mg/kg</u>	<u>Vapor LC50, mg/L</u>
28182-81-2	Hexane, 1,6-Diisocyanato-,Homopolymer	>2500	>2000	>10
616-38-6	Dimethyl carbonate	13000.0	>2500.0	140.0
123-86-4	n-Butyl Acetate	14,130	>16,000	>20.0
64742-94-5	Petroleum hydrocarbon	>5,000	>2,000	>20.0
91-20-3	Naphthalene	>2000	>2500.0	>0.04
143860-04-2	3-Ethyl-2-methyl-2-(3-methylbutyl)-1, 3-oxazoldine	4400	>2000	>20

**SECTION 12. Ecological Information**

ECOLOGICAL INFORMATION: No Information

**SECTION 13. Disposal Considerations**

For more guidance and information contact our Waste Services Division at (262) 658-4000.

Always dispose of any waste in accordance with all local, state, and federal regulations.

**DISPOSAL METHOD:** Dispose of waste in accordance with all local, state and federal regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED:** Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Use water mist or spray to disperse vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Clean up spill area with a decontamination solution made up of 50% isopropyl alcohol, 45% water and 5% concentrated ammonia solution. The solution should cover the area for at least one hour then be collected for disposal.

**SECTION 14. Transport Information**

<b>DOT Proper Shipping Name:</b>	Paint Related Material	<b>Packing Group:</b>	II
<b>DOT Hazard Class:</b>	3	<b>Hazard SubClass:</b>	No Information
<b>DOT UN/NA Number:</b>	UN1263	<b>Resp. Guide Page:</b>	128

**SECTION 15. Regulatory Information****U.S. Federal Regulations:****CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Reactive Hazard, Acute Health Hazard, Chronic Health Hazard

**SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Petroleum hydrocarbon	64742-94-5
Naphthalene	91-20-3
1,2,4 trimethylbenzene	95-63-6

1,6-Hexamethylene Diisocyanate

822-06-0

**TOXIC SUBSTANCES CONTROL ACT:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
Naphthalene	91-20-3

**U.S. State Regulations:****NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

**PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

**CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
Naphthalene	91-20-3

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

**International Regulations: As follows -****CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

**SECTION 16. Other Information**

Revision Date: 12/9/2015 Supersedes Date: 8/22/2015

Datasheet produced by: EH&S - Regulatory Department

**HMIS Ratings:**

Health:	2	Flammability:	3	Reactivity:	1	Personal Protection:	X
---------	---	---------------	---	-------------	---	----------------------	---

Volatile Organic Compounds, gr/ltr: 1,623

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, EMCO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/ REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

H320	Causes eye irritation
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



GHS05



GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.