

13-FL03

FILM TAPE

PRODUCT DESCRIPTION

A high coat weight double sided PVC tape with incredibly aggressive adhesive making it one of the highest performing double sided film tapes available.

PRODUCT FEATURES

Adhesive system designed to bond well to medium surface energy substrates.
 Exceptionally high tack and peel adhesion
 Good conformability
 Bonds to rough and uneven surfaces
 Excellent humidity, solvent & UV resistance
 Suitable for outdoor use
 Available in 3mm - 1240mm widths

CARRIER

PVC

ADHESIVE TYPE

Modified Acrylic

TOTAL THICKNESS

0.310mm

ADHESIVE TAPE COLOUR

White

RELEASE LINER

Amber Glassine Paper 80gsm

PEEL ADHESION

Very High

SHEAR STRENGTH

High

ELONGATION

60%

CONTINUOUS TEMP. RANGE

-30°C to 70°C

MINIMUM APPLICATION TEMP.

15°C

AVAILABLE FORMATS

Logs, rolls, discs, pads, and die-cut shapes




SHELF LIFE

1 Year stored at 21°C, 50% RH and out of direct sunlight

MAIN APPLICATIONS (NOT LIMITED TOO)

Used across variety of industries & critical bonding applications such as Automotive mirror mounting, kick plates, machine labels, decorative trim, battery pack mounting and plastic mouldings.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com



08
07
06
05
04
03
02
01